

## USB 3.0 to VGA External Video Card Multi Monitor Adapter for Mac® and PC – 1920x1200 / 1080p

StarTech ID: USB32VGAPRO



The USB32VGAPRO USB 3.0 to VGA Adapter turns an available USB 3.0 port on your desktop or laptop into a VGA output, with high resolution 1920x1200/1080p video support - a convenient external video solution that makes it easy to add multi-monitor capability to a USB 3.0-enabled Mac® or PC (optimal performance from USB 3.0, backward compatible with USB 2.0).

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, and powered by the DisplayLink chipset, the USB32VGAPRO is our highest performing USB to VGA adapter, delivering high-resolution content to your VGA-capable display. The external graphics card can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

USB 3.0 port (backward compatible with USB 2.0)

### Applications

- Add a secondary VGA display and extend your desktop without taking apart your computer to install a new video card
- Add multi-monitor capability to a single computer, to create engaging multimedia presentations
- Use the adapter to connect your PC to your VGA-equipped TV, for showing family pictures and movies
- Great for researchers and writers, offering the ability to have reference material on one display and a working document copy on the other
- Increase productivity by running multiple applications on different screens, check your e-mail on one display and search the web on the other
- View a large spreadsheet or several individual spreadsheets across multiple displays
- A compact, lightweight solution for traveling business associates using laptop PCs, enabling connection to a secondary display/projector

## Features

- SuperSpeed USB 3.0 (5 Gbps)
- Supports video resolutions up to 1920x1200/1080p
- USB-powered - No external power adapter required
- Supports Mirrored, Extended or Primary display configurations
- Supports display rotation

Technical Specifications

Warranty	2 Years
Chipset ID	DisplayLink - DL3100N
Memory	512MB DDR2 SDRAM
Connector A	1 - USB 3.0 A (9 pin; SuperSpeed) Male
Connector B	1 - VGA (15 pin; High Density D-Sub) Female
Maximum Analog Resolutions	1920x1200/1080p
Note	If using OS X 10.8, Apple update 10.8.3 must be installed before installing DisplayLink software. 10.8.3 fixes several serious OS X bugs exposed when DisplayLink software is installed.
Supported Resolutions	Widescreen(16/32 bit): 1920x1200, 1920x1080, 1680x1050, 1366x768, 1280x800, 1280x768, 1280x720  Standard(16/32 bit): 1600x1200, 1400x1050, 1280x1024, 1024x768, 800x600, 640x480
Wide Screen Supported	Yes
OS Compatibility	Windows® 8/8.1 (32/64bit), 7 (32/64bit), Vista(32/64), XP(32/64), 2000 (Aero 3D interface supported) Apple® OSX Mavericks (10.9) Mountain Lion (10.8), Lion (10.7), Snow Leopard (10.6)
Color	Black
Enclosure Type	Plastic
Product Height	0.8 in [19.4 mm]
Product Length	3.6 in [90.4 mm]
Product Width	2.2 in [55.8 mm]
Power Adapter Included	USB-Powered
Operating Temperature	10°C to 40°C (50°F to 104°F)
Storage Temperature	-10°C to 80°C (14°F to 167°F)
Humidity	<85% RH Non-Condensing
Shipping (Package) Weight	15.9 oz [450 g]
Included in Package	1 - USB 3.0 to VGA Video Adapter
Included in Package	1 - Driver/Software CD
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

