



AVAYA WLAN 9132 ACCESS POINT

(REGULATORY MODEL WAP9102)

The Avaya WLAN Access Point 9132 is a high performance 802.11ac (2x2) Access Point (AP). It is part of the next generation Avaya wireless portfolio that delivers wired-like performance and predictability. It supports application QoS enforcement within the AP to provide a high quality user experience and ensure that business critical applications are not impacted by personal applications. Additionally, Avaya unified access offers automated provisioning of APs and end clients/users while extending Avaya's Fabric intelligence all the way to the APs.

Overview

The WLAN Access Point 9132 provides an economical solution for deploying an 802.11ac wireless network. With a 2x2 radio design that provides twice the performance of 3x3 802.11n, the WLAN AP 9132 delivers uncompromising performance.

With a powerful integrated controller, application-level intelligence, automated provisioning and cloud management, the WLAN AP 9132 is the ideal solution for environments where users predominantly connect to wireless using tablets and smart phones which utilize 1x1 and 2x2 antenna technologies. Example applications for the WLAN 9132 include BYOD environments, hotel rooms, hospital rooms, retail areas and similar. The Access Points are managed centrally by the Avaya WLAN Orchestration System.

The WLAN AP 9132 optimizes wireless performance by automatically segmenting faster 802.11ac clients from slower Wi-Fi clients. Since Wi-Fi is a shared medium, this separation ensures slower 802.11 a/b/g/n clients do not slow down 802.11ac clients from achieving high performance.

At A Glance

- Dual radio 2x2 802.11ac AP with 1.7Gbps total Wi-Fi bandwidth
- Two software programmable radios for mixed 2.4/5GHz or dual concurrent 5GHz operation
- 802.11ac speed optimization
- 2X the performance of a 3x3 802.11n AP
- Supports up to 240 users with 2 - 1Gbps uplinks
- Integrated Controller
- On-premise or cloud-based (future) management

Key Benefits

Application Control
Firewall, apply QoS, and manage 1300+ individual or groups of applications under 15 categories using Layer 7 Deep Packet Inspection (DPI) and other contextual application detection techniques.

5GHz Optimization

With its 2.4GHz and 5GHz radios (both software programmable to either band), the WLAN 9132 will help you easily make the transition to a 5GHz centric network, when you are ready.

Up to 70% more Wi-Fi bandwidth

The 802.11ac Speed Optimization Technology leverages dual concurrent 5GHz radio operation to ensure that 802.11ac clients communicate at 802.11ac speeds and are not affected by the slower speeds of legacy 802.11n clients. One 5GHz radio automatically services 802.11ac clients and the other 5GHz radio services 802.11n clients – thus ensuring that 802.11ac/n clients are segregated to maximize throughput.

Bring Your Own Device (BYOD)

Integration with Avaya Identity Engines allows guests and employees alike to use personal wireless devices while the WLAN AP 9132 enforces appropriate access policies.

Uncompromising Performance

Distributed architecture with Integrated controller and multi core processor delivers twice the speed of 802.11n 3x3 APs. The WLAN AP 9132 delivers linear scalability, high resiliency and superior network performance by processing network traffic at the network edge.

Bonjour Director Support

Extend Apple Bonjour protocols across Layer 3 boundaries for simple setup and configuration of commonly used shared Apple services such as Airplay and Airprint.

Automated Provisioning

Avaya's holistic Unified Access solution provides automated identification and provisioning of APs by extending its innovative Fabric technology to the wireless edge.

Configuration Specifications

| | WLAN AP 9132 |
|----------------------------------|--|
| Chassis Size | 7.7" |
| Total Radios | 2 |
| Radio Type | Two Software Programmable Radios (2.4GHz or 5GHz) |
| Maximum Wi-Fi Bandwidth | 1.7Gbps (2 – 867Mbps radios) |
| Number of Integrated Antennas | 4 integrated antennas |
| Max Wi-Fi Backhaul | 867Mbps |
| Gigabit Ethernet Uplink Ports | 2 ports supports 4 different operating modes: <ul style="list-style-type: none">• IEEE 802.3ad link aggregation• Daisy chaining (bridge)• Port mirroring (traffic duplication)• Client connectivity (phone, printer etc.) |
| Maximum Associated Users | 384 (192 per radio) |
| Power Requirements | PoE+ (802.3at) |
| Mean Time Between Failure (MTBF) | 463990 hours |



Technical Specifications

| FEATURE | SPECIFICATIONS | |
|--------------------|--|---|
| CPU | OCTEON® III CN70XX Quad-Core Embedded Processors | |
| Installed Memory | 1GB | |
| RF Management | In-band per radio Spectrum Analysis Dynamic channel configuration Dynamic cell size configuration Wired and wireless packet captures (including 802.11 headers) Radio assurance for radio self test and healing RF monitor 2.4 & 5.0GHz Honeypot Control – Increase available 2.4 and 5GHz wireless device density through management of spurious association traffic Ultra Low Power Mode – Maximize wireless channel re-use and increase wireless device density through tight power controls | |
| Wireless Protocols | IEEE 802.11a, 802.11ac, 802.11b, 802.11d, 802.11e, 802.11g, 802.11h, 802.11i, 802.11j, 802.11k, 802.11n | |
| Wired Protocols | IEEE 802.3 10-BASE-T, IEEE 802.3u 100BASE-TX, 1000BASE-T, IEEE 802.3ab 1000BASE-T IEEE 802.1Q – VLAN Tagging IEEE 802.1D – Spanning Tree IEEE 802.1p – Layer 2 Traffic Prioritization IPv6 Control – Increase wireless device density through control of unnecessary IPv6 traffic on IPv4-only networks IEEE 802.3ad – Link Aggregation | |
| RFC Support | RFC 768 UDP RFC 791 IP RFC 2460 IPV6 (Bridging only) RFC 792 ICMP RFC 793 TCP | RFC 826 ARP RFC 1122 Requirements for internet hosts – communication layers RFC 1542 BOOTP RFC 2131 DHCP |
| Security | WPA™ – Enterprise, Personal WPA2™ – Enterprise, Personal EAP Type(s) EAP-TLS EAP-TTLS/MSCHAPv2 PEAPv0/EAP-MSCHAPv2 | PEAPv1/EAP-GTC EAP-SIM EAP-AKA EAP-AKA Prime EAP-FAST Protected Management Frames |
| Encryption Types | Open, WEP, TKIP-MIC: RC4 40, 104 and 128-bit SSL v3.0 and TLS v1.0: RC4 128-bit and RDA 1024 and 2048-bit | |







Avaya WLAN AP 9132 Receive Sensitivity

| RATE | 2.4GHz RX SENSITIVITY (dBm) | 5.0GHz RX SENSITIVITY (dBm) |
|---------------------|-----------------------------|-----------------------------|
| 802.11a | | |
| 6Mbps | | -92 |
| 9Mbps | | -92 |
| 12Mbps | | -91 |
| 18Mbps | | -90 |
| 24Mbps | | -87 |
| 36Mbps | | -83 |
| 48Mbps | | -79 |
| 54Mbps | | -78 |
| 802.11b | | |
| 1Mbps | -91 | |
| 2Mbps | -91 | |
| 5.5Mbps | -93 | |
| 11Mbps | -93 | |
| 802.11g | | |
| 6Mbps | -93 | |
| 9Mbps | -93 | |
| 12Mbps | -92 | |
| 18Mbps | -91 | |
| 24Mbps | -90 | |
| 36Mbps | -88 | |
| 48Mbps | -83 | |
| 54Mbps | -80 | |
| 802.11n HT20 | | |
| MCS 0 | -93 | -93 |
| MCS 1 | -93 | -90 |
| MCS 2 | -92 | -88 |
| MCS 3 | -88 | -85 |
| MCS 4 | -86 | -81 |
| MCS 5 | -82 | -77 |
| MCS 6 | -80 | -76 |
| MCS 7 | -79 | -75 |
| MCS 8 | -95 | -93 |
| MCS 9 | -92 | -90 |
| MCS 10 | -89 | -88 |
| MCS 11 | -87 | -85 |
| MCS 12 | -83 | -81 |
| MCS 13 | -79 | -77 |
| MCS 14 | -78 | -76 |
| MCS 15 | -76 | -75 |
| MCS 16 | -92 | -93 |
| MCS 17 | -91 | -90 |
| MCS 18 | -89 | -88 |
| MCS 19 | -86 | -85 |
| MCS 20 | -82 | -81 |
| MCS 21 | -78 | -77 |
| MCS 22 | -77 | -76 |
| MCS 23 | -76 | -75 |
| 802.11n HT40 | | |
| MCS 0 | -93 | -91 |
| MCS 1 | -92 | -88 |
| MCS 2 | -90 | -86 |
| MCS 3 | -87 | -83 |

| RATE | 2.4GHz RX SENSITIVITY (dBm) | 5.0GHz RX SENSITIVITY (dBm) |
|-----------------------|-----------------------------|-----------------------------|
| 802.11ac VHT20 | | |
| MCS 0 | | -82 |
| MCS 1 | | -79 |
| MCS 2 | | -77 |
| MCS 3 | | -74 |
| MCS 4 | | -70 |
| MCS 5 | | -66 |
| MCS 6 | | -65 |
| MCS 7 | | -64 |
| MCS 8 | | -59 |
| MCS 9 | | -57 |
| 802.11ac VHT40 | | |
| MCS 0 | | -88 |
| MCS 1 | | -85 |
| MCS 2 | | -83 |
| MCS 3 | | -80 |
| MCS 4 | | -76 |
| MCS 5 | | -72 |
| MCS 6 | | -71 |
| MCS 7 | | -69 |
| MCS 8 | | -67 |
| MCS 9 | | -66 |
| 802.11ac VHT80 | | |
| MCS 0 | | -86 |
| MCS 1 | | -83 |
| MCS 2 | | -81 |
| MCS 3 | | -78 |
| MCS 4 | | -74 |
| MCS 5 | | -70 |
| MCS 6 | | -69 |
| MCS 7 | | -68 |
| MCS 8 | | -66 |
| MCS 9 | | -64 |

Avaya WLAN AP 9132 Specifications

| FEATURE | SPECIFICATIONS | |
|---|--|--|
| Authentication | IEEE 802.1X Extensible Authentication Protocol RFC 2548 Microsoft vendor-specific RADIUS attributes RFC 2716 PPP EAP-TLS RFC 2865 RADIUS Authentication RFC 2866 RADIUS Accounting RFC 2867 Tunnel Accounting RFC 2869 RADIUS Extensions RFC 3576 Dynamic Authorizations extensions to RADIUS RFC 3579 RADIUS Support for EAP RFC 3748 EAP-PEAP RFC 5216 EAP-TLS | RFC 5281 EAP-TTLS RFC 2284 EAP-GTC RFC 4186 EAP-SIM RFC 4187 EAP-AKA RFC 3748 LEAP Pass through RFC 3748 Extensible Authentication Protocol Web Page Authentication • WPR, Landing Page, Redirect • Support for Internal WPR, Landing Page and Authentication • Support for External WPR, Landing Page and Authentication |
| Regulatory Compliance | UL 60950-1, CAN/CSA - C22.2 No. 60950-1, IEC 60950-1, EN 60950-1 FCC Part 15, Subpart B, ICES 003, EN 55022/24 Class B FCC part 15C, FCC Part 15E, RSS-210 EN 300 328, EN 301 893 | EN 301 489-1/17 R & TTE Directive 1999/5/EC EN 50385 EN 301 893 V1.6.1 EN 60601-1-2 |
| Physical Specifications | Dimensions (WxDxH): 1.96 x 7.70 x 7.70 | Weight: 1.6lbs |
| Environmental Specifications | Operating Temperature: 0-40C, 0-90% humidity, non-condensing, altitude 0-2000m Non-Operating Temperature: 0-60C, 0-95% humidity, non-condensing | |
| Channel Support 2.4GHz (Exact channels available will be based on country code selected) | 1 2 3 4 5 6 7 8 9 10 11 12 13 14 | |
| Channel Support 5GHz (Exact channels available will be based on country code selected) | UNII-1 - Non DFS Channels 36 40 44 48 UNII-2A - DFS Channels 52 56 60 64 | UNII-2C - DFS Channels 100 104 108 112 116 120 124 128 132 136 140 UNII-3 - Non DFS Channels 149 153 157 161 165 |
| Management Interfaces | Command Line Interface (CLI); Web Interface (HTTP and HTTPS) | |
| Management Protocols and Standards | SNMP v1 SNMPv2c as per RFCs 1901, 2580 SNMPv3 as per RFC 3410-3415 RFC 854 Telnet RFC 1155 Management Information for TCP/IP Based Internets RFC 1156 MIB RFC 1157 SNMP RFC 1212 Concise MIB Definitions RFC 1213 SNMP MIB II RFC 1215 A Convention for Defining Traps for use with the SNMP RFC 1350 TFTP RFC 1643 Ethernet MIB RFC 2030 Simple Network Time Protocol SNTP RFC 2578 Structure of Management Information Version 2 (SMIV2) RFC 2579 Textual Conventions for SMIV2 RFC 2616 HTTP 1.1 RFC 2665 Definitions of Managed Objects for the Ethernet Like Interface Types | |

| FEATURE | SPECIFICATIONS | |
|------------------------|--|---|
| Gain | 2.4 Gbps: 4.20 dBi | 5 Gbps: 5.6 dBi |
| Maximum Transmit Power | 2.4 Gbps: 17 dBm | 5 Gbps: 15 dBm |
| Antenna Patterns | <p>2.4 Gbps, Horizontal</p> <p>WAP9122/WAP9132 2.4 GHz Azimuth (Horizontal)</p>  <p>5 Gbps, Horizontal</p> <p>WAP9122/WAP9132 5 GHz Azimuth (Horizontal)</p>  | <p>5 Gbps, Horizontal</p> <p>WAP9122/WAP9132 5 GHz Azimuth (Horizontal)</p>  |
| | <p>2.4 Gbps, Vertical</p> <p>WAP9122/WAP9132 2.4 GHz Elevation (Vertical)</p>  <p>5 Gbps, Vertical</p> <p>WAP9122/WAP9132 5 GHz Elevation (Vertical)</p>  | <p>5 Gbps, Vertical</p> <p>WAP9122/WAP9132 5 GHz Elevation (Vertical)</p>  |

About Avaya

Avaya is a leading, global provider of customer and team engagement solutions and services available in a variety of flexible on-premise and cloud deployment options. Avaya's fabric-based networking solutions help simplify and accelerate the deployment of business critical applications and services. For more information, please visit www.avaya.com.

© 2016 Avaya Inc. All Rights Reserved.

Avaya and the Avaya logo are trademarks of Avaya Inc. and are registered in the United States and other countries. All other trademarks identified by ®, TM, or SM are registered marks, trademarks, and service marks, respectively, of Avaya Inc. Other trademarks are the property of their respective owners.

04/16 • DN7518-09