

SG4P1

5 Port 10/100/1000 Desktop Switch with 4 x 10/100/1000 PoE 802.3af and 1xGIG Uplink

Designed for use with Power over Ethernet (PoE) devices, the SG4P1 switch provides up to 15.4W of power to 802.3af PoE compatible devices connected to the switch's PoE ports.

The Switch allows these devices to draw power from the switch and remove the need for a power adapter.

Some devices that may have support for 802.3af are Wireless Access Points, IP Phones and IP Cameras.

The Switch's ports automatically negotiate between 10BASE-T and 100BASE-TX network speeds, as well as


between full and half duplex modes, so any port can connect to a Fast Ethernet or Ethernet network. The ports also support Auto MDIX, allowing the automatic detection of a straight through or cross-over cable, this feature reduces support problems commonly caused by incorrect cable usage.



Key Features and Benefits:

- Standard IEEE802.3af support

With the IEEE802.3af support and the use of PoE there are several advantages. With PD (Powered Devices) which are either located in locations with difficult access or areas where cable density would not be ideal. The PoE switch offers a solution due to the removal of the need for a power outlet to be dropped to the location of the device. There is also a benefit with the use of a uninterruptible power supply that can be placed only on the PoE switch itself instead of at each device. This increases the reliability of the network and ultimately decreases the maintenance and deployment cost. The 802.3af port on the switches also offers automatic detection of a PD (Powered Device). The switch will be able to determine if power is to be supplied to any of the PoE supported ports. This helps in the reduction of power used by the switch to power unused ports as well as insuring that power is not put out on wiring that is not connected to a PD.



- Metal Chassis Construction

The metal construction of the chassis allows for a more secure and reliable installation. The heat dissipation for the unit is increased allowing for a higher reliability over common plastic chassis. The metal construction also increases the units durability by not being as prone to cracking or melting if there was ever a power surge or other electrical problem.

- Wall and Desktop Mounting

With the compact design the unit can be placed easily in many locations. The unit also can be mounted to a wall or under a desk or other object with the wall mounting kit which easily aids in the placement of the unit where you may need it.

SG4P1

5 Port 10/100/1000 Desktop Switch with 4 x 10/100/1000 PoE 802.3af and 1xGIG Uplink

- RJ-45 Port Alignment

The SG4P1 is designed with the RJ-45 ports on the unit rotated from a more traditional configuration to one that allows the RJ-45 cable's connector to have its release tab on the top of the switch. The advantage here is in wall mounted installations where the switch is physically anchored with the release tab on the bottom, the access to the removal of the cables are difficult without dismounting the switch. With the top aligned tab the cabling can be easily access for reconfiguration of for troubleshooting.

Specifications

- **Performance**

- Switching Capacity: • 8 Gbps
- MAC Address Table Size: • 1K MAC address entries per device
- Buffer Memory: • 3 MB
- Networking Standards: • IEEE802.3i 10 BASE-T;
IEEE802.3u 100 BASE-TX,
IEEE802.3x Flow control;
IEEE802.3ab/z 1000 BASE -TX
IEEE802.3af Power over Ethernet

- **Ports & Port Features**

- RJ-45 10/100/1000 Base-T: • 4 x 1 Gigabit PoE Ethernet Ports
1 x 1 Gigabit Ethernet Port
- PoE Features: • Up to 15.4W per PoE port (IEEE802.3af)
PoE pin pairs 1/2 and 3/6
- Forwarding Mode: • Store and Forward
- Flow Control: • Half-duplex back pressure and
IEEE802.3X full-duplex flow control
- LED Indicator: • System: Power, PoE max. power;
Per port: Link, speed, PoE active,
PoE error
- Minimum Cable Requirement: • UTP cat5 or higher

- **Warranty and Support**

- Warranty: 3 Years
- Support: Free technical support (phone/email)

- **Electronic Features & Electrical Emissions**

- Emissions: • CE, FCC, ROHs
- Power Supply: • External cUL 48V 1.25A
- Power Consumption: • Total power consumption: 70W
Total PoE power budget: 60W

- **Environmental Parameters**

- Operating Temperature Range: • 32° to 104° F (0° to 40° C)
- Storage Temperature Range: • 14° to 158° F (-10° to 70° C)
- Operating Humidity Range: • 20%-85%, Non-condensing

- **Physical Features, Dimentions & Weight**

- Width x Depth x Height: • 118 x 85 x 28 mm
4" 5/8 x 3" 5/16 x 1"
- Weight: • 0.68lbs(310g)
- Case Material: • Metal
- Mounting: • Desk or Wall Mount