

Nio Color 3MP (MDNC-3421)

3MP high-bright color display



- Best image quality on the market for 3MP color
- Automated Quality Assurance and calibration for stable DICOM images
- Fully-tested system solution from a single source, for ultimate peace of mind

Nio Color 3MP is a 3 megapixel high-bright color display system with LED backlights, providing excellent image quality for confident diagnoses. Its exceptional brightness (calibrated at 500 cd/m²) helps you discern even the tiniest detail - even after many years of use.

The best 3MP color solution on the market

The new Nio Color 3MP offers the best image quality in the market for a 3MP color solution. Its high brightness and high contrast ratio enable you to unveil even the subtlest details and make accurate diagnoses. With the integrated smart features, you can easily take control and improve your productivity. SpotViewTM, for example, allows you to focus on an area of interest to unveil even more details. And with DimViewTM, any auxiliary displays can be automatically dimmed. The Nio Color 3MP is also an excellent solution for radiologists who want to angle their desktop: it lets you choose your preferred viewing angle and offers highly ergonomic display configuration.

Stable image quality, durable investment

Using Barco's integrated front sensor, the Nio Color 3MP works perfectly with Barco's online MediCal QAWeb solution for automated Quality Assurance and calibration. QAWeb guarantees stable DICOM images throughout the display's lifetime. By default, Barco displays are equipped with a protective cover to safeguard your investment. Thanks to the high-performance LED backlights, the Nio Color 3MP requires less power, even at higher calibrated luminance. This has a positive impact on both maintenance and operational costs.

Ultimate peace of mind

Barco is the only company that provides complete system solutions, from display and controllers to workflow tools and calibration via QAWeb. All components are covered by our full 5-year warranty. At product release, Barco extensively tests the



displays compatibility with all major PACS applications.

PRODUCT SPECIFICATIONS	NIO COLOR 3MP (MDNC-3421)
Screen technology	IPS-TFT Color LCD
Active screen size diagonal	540 mm (21.3")
Active screen size H x V	432 x 324 mm (17.0 x 12.8")
Aspect ratio HV	4:3
Resolution	3MP (2048 x 1536 pixels)
Pixel pitch	0.2109 mm
Color imaging	Yes
Gray imaging	Yes
Bit depth	30 bit
Viewing angle H V	178°
Uniformity correction	ULT
Ambient light presets	Yes, reading room selection
Backlight Output Stabilization BLOS	No
Front sensor	Yes
Maximum luminance (panel typical)	900 cd/m ²
DICOM calibrated luminance	500 cd/m ²
Contrast ratio (panel typical)	1400:1
Response time _ Tr Tf _ typical	20 ms
Housing color	RAL 9003 / RAL 9004
Video input signals	DVI-D Dual Link DisplayPort
USB ports	1x USB 2.0 upstream (endpoint) 2x USB 2.0 downstream
Power Requirements	External power supply (100-240 Vac, 47-63 Hz)
Power consumption	50 W (nominal) < 0.5 W (standby)
OSD languages	English, German, French, Dutch, Spanish, Italian, Portuguese, Polish, Russian, Swedish, Chinese (simplified), Japanese, Korean, Arabic
Dimensions with stand W x H x D	Portrait: 378 x 528~628 x 235 mm Landscape: 491 x 472~572 x 235 mm
Dimensions wo stand W x H x D	Portrait: 378 x 491 x 84 mm Landscape: 491 x 378 x 84 mm
Dimensions packaged W x H x D	500 x 280 x 670 mm
Net weight with stand	11.2 kg
Net weight wo stand	6.2 kg
Net weight packaged	15.7 kg (without accessories)
Tilt	-10° to +30°
Swivel	-45° to +45°
Pivot	90°
Height adjustment range	100 mm
Mounting standard	VESA (100 mm)
Screen protection	Protective, anti-reflective glass cover
Recommended modalities	All digital images, except digital mammography

PRODUCT SPECIFICATIONS**NIO COLOR 3MP (MDNC-3421)**

Certifications	CE0120 (MDD 93/42/EEC; A1:2007/47/EC class IIb product), CE 2014/30/EU, CE93/42/EEC; A1:2007/47/EC class II b, IEC 609501:2005 + A1:2009 (2NDEDITION), IEC 606011:2005 + C1:2006 + C2:2007 + A1:2012, ANSI/AAMI ES606011:2005 + C1:2009 + R1:2012, CAN/CSAC22.2No. 606011:2014, DEMKO EN606011:2006 + A11:2011 + A12:2014 + A1: 2013, EN 6060112:2007, CCC GB92542008+ GB4943.12011+ GB17625.12003,KC, VCCI, FCC class B, ICES001Level B, FDA 510(k), RoHS
Supplied accessories	User guide Documentation disc System disc Video cable (1 x DisplayPort) Mains cables (UK, European (CEBEC/KEMA), USA (UL/CSA; adaptor plug NEMA515P),Chinese (CCC)) USB 2.0 cable External power supply
Optional accessories	Graphics board
QA software	MediCal QAWeb
Warranty	5 years, including 20000 hrs backlight warranty
Operating temperature	0 °C to 40 °C (15 °C to 35 °C within specs)
Storage temperature	-20 °C to 60 °C
Operating humidity	8% to 80% (non-condensing)
Storage humidity	5% to 85% (non-condensing)
Operating pressure	70 kPa minimum
Storage pressure	50 to 106 kPa

Last updated: 11 Jul 2017

Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.