

## DisplayPort Extension Cable with Latch, 4K @ 60 Hz, HDCP 2.2 (M/F), 15 ft. (4.57 m)

MODEL NUMBER: P579-015



Extends your existing DisplayPort™ connection by 15 ft. Latching male connector prevents accidental disconnections.

### Description

The P579-015 DisplayPort Extension Cable (M/F) attaches to your current DisplayPort cable to extend it by 15-ft. (4.57 m). To ensure a continuous audio/video signal, the latching male end prevents the cable from coming loose or getting accidentally disconnected. This 15-ft. (4.57 m) cable supports UHD video resolutions up to 3840 x 2160 (4K x 2K) at 60 Hz, allowing you to stream digital video and audio from a DisplayPort computer to a monitor or television with a DisplayPort input.

Premium foil and braid shielding delivers reliable, error-free signal quality and protection from EMI/RFI interference. Molded nickel-plated connectors with corrosion-resistant gold-plated contacts provide maximum conductivity and minimize data loss. Integral strain relief with ridges on each end gives the cable extra flexibility, reduces stress, and helps the cable and connectors move freely without cracking.

### Features

#### Extends an Existing DisplayPort Cable an Extra 15-ft. (4.57 m)

- Female connector attaches to current DisplayPort cable to add length
- Supports UHD video resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Supports DisplayPort v1.2, DPCP and HDCP 2.2

#### Latching Male Connector Ensures Continuous A/V Signal

- Prevents cable from coming loose or getting accidentally disconnected
- Easy one-touch release button allows unplugging

#### First-Rate Construction for Superior Signal Transfer

### Highlights

- Supports 4K x 2K video resolutions @ 60 Hz
- Latching DisplayPort plug ensures secure connection
- Molded nickel-plated connectors with gold-plated contacts
- Supports DisplayPort v1.2, DPCP and HDCP 2.2
- Smaller connector footprint than VGA or DVI

### Package Includes

- P579-015 DisplayPort Extension Cable with Latch (M/F), 15-ft. (4.57 m)



- Premium foil and braid shielding for EMI/RFI noise protection
- Gold-plated contacts for maximum conductivity and minimum data loss
- Integral strain relief reduces stress and adds flexibility
- Flexible PVC jacket
- Smaller connector footprint than VGA or DVI saves space

## Specifications

| OVERVIEW                            |                               |
|-------------------------------------|-------------------------------|
| UPC Code                            | 037332202024                  |
| Technology                          | DisplayPort                   |
| PHYSICAL                            |                               |
| Color                               | Black                         |
| Cable Length (ft.)                  | 15                            |
| Cable Length (m)                    | 4.6                           |
| Cable Length (in.)                  | 180                           |
| Shipping Dimensions (hwd / cm)      | 25.40 x 20.32 x 1.27          |
| Shipping Dimensions (hwd / in.)     | 10.00 x 8.00 x 0.50           |
| Shipping Weight (kg)                | 0.26                          |
| Shipping Weight (lbs.)              | 0.58                          |
| ENVIRONMENTAL                       |                               |
| Operating Temperature Range         | -4 F TO 140 F (-20 C TO 60 C) |
| Storage Temperature Range           | 5 F TO 122 F (-15 C TO 50 C)  |
| Relative Humidity                   | 10% TO 80% RH, NON-CONDENSING |
| CONNECTIONS                         |                               |
| Side A - Connector 1                | DISPLAYPORT (MALE)            |
| Side B - Connector 1                | DISPLAYPORT (FEMALE)          |
| WARRANTY                            |                               |
| Product Warranty Period (Worldwide) | Lifetime limited warranty     |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>