



RocketStor 6628A

2nd Generation Thunderbolt™ 3 40Gb/s Hardware RAID Storage Enclosure



Refined Performance, Reliability & Management Features

Streamlined RAID Management for Professionals

Each RocketStor 6628 RAID Enclosure includes our newly redesigned, easy to use web-based management utility. The built-in Array Configuration Wizard allows users of any experience level to create any type of RAID array in three easy steps; simply select your RAID level, pick your drives and go!

Optional Advanced Management Features allow customers to fine tune RAID arrays for specific projects, with options to specify block size, enable DV Mode for digital media projects, designate spare disks for recovery, and schedule routine automated maintenance sessions with Email notification to keep one abreast of changing storage conditions while outside of the work environment.

Fast, Consistent, & Smooth Data Transfer for large block size Applications

The RocketStor 6628A 2nd Generation
Series Thunderbolt™ 3 RAID enclosures
feature the latest iteration of HighPoint's
industry proven Hardware RAID stack,
which features substantial refinements to
both transfer performance and stability for
professional storage applications.
RocketStor 6628A benefits from
streamlined performance and highly stable
transfers for large block size applications
such as video production and editing,
media streaming and content creation.

Enhanced Storage Cooling Solution

The ability to manage the high-levels of heat generated by pronged, sustained I/O sessions on today's high-capacity hard disks is a prime concern when choosing the right RAID enclosure solution.

RocketStor 6628 Series RAID enclosures seamlessly integrate LED's, audible alarms, and superior cooling apparatus to ensure

your storage investments and the critical data they host stay cool, healthy and productive. Proactive monitoring systems intelligently adjust fan speed on the fly to eject waste heat from the chassis and prolong the life of today's high-capacity SAS and SATA hard drives.

High-Speed, Big Data or All-In-One: Your Choice!

RocketStor 6628 Series RAID enclosures are significantly more versatile that conventional external storage solutions, which rely on pre-packaged storage comprised solely of drives of the same speed and capacity. Customers are free to mix and match disks of different capacities and speed levels to meet the needs of any application; SSD's for Maximum Performance, HDD's for Mass Storage, or a combination of both for tasks that call for high-speed workspace and archiving capability.

Equipped with the latest Thunderbolt™ 3 USB-C technology, the RocketStor 6628A can deliver 40Gbps transfer rates. Projects utilizing 4K DPX 16 bit footage require approximately 1,790MB/s of transfer performance; it is capable of supporting full 4K uncompressed video production, In addition, if the source is ProRes 444, the RocketStor 6628A can support over 5 individual streams!

Uncompromised Hardware RAID Architecture

Hardware RAID 5 and 6 protection shields storage configurations from 1 or 2 disk failures, respectively. Storage Health Inspector SHI) proactively maintains the health of arrays and keep storage ready & able.

HighPoint DV Mode for Streaming Performance

DV Mode Technology intelligently manages the flow of large data blocks and

Key Benefits

- 2x Thunderbolt™ USB-C Ports featuring 40Gb/s Speed bandwidth
- Performance up to 2,700MB/s
- Integrated SAS/SATA Hardware RAID Technology
- Storage Capacity up to 8x 10TB or Larger Spindle HDD
- High-Speed Storage up to 8x SSD
- Blazing Fast, Consistent, & Smooth Data Transfer for large block size Applications
- Enhanced Storage Cooling Solution
- Refined 2nd Generation Chassis Design eases Maintenance

Suggested Applications

- Mac and Windows based Media Workstations
- High-Speed data transfer & backup

write-back caching to minimize latency and ensure consistent, sustained highperformance transfers for media-rich applications.

Robust RAID Protection

The built-in NVRAM constantly tracks inprogress writes to preserve the integrity of data in the event of a drive failure or system crash, and streamline recovery procedures while minimizing downtime.

Storage Expansion Ready

Daisy-Chain capability allows customers to link as many as 6 independent RocketStor 6628A units using a single Thunderbolt™ 3 host port. The Online Capacity Expansion and RAID Migration allow customers to modify RAID configurations or expand existing storage while avoiding complicated, time consuming backup and restoration procedures.



Feature Specifications			
Connection Type	Thunderbolt™ 3		
Host Ports	2x Thunderbolt™ 3 Ports		
Daisy Chain	Supports Daisy Chain connections of up to six Thunderbolt™ devices. (Note: the Daisy Chain will end when connecting a USB device or Display via USB-C)		
TB3 Technology	 Daisy Chain up to 6 devices Bi-directional, dual-protocol (PCI Express and DisplayPort) 8 lanes of Display Port 1.2 - supports dual 4K displays or one 5K display Power delivery: 15W to bus-powered devices Backward compatible with Thunderbolt™ 2 devices USB-C ports compatible with existing USB devices and cables, support up to USB 3.1 10Gb/s speed 		
RAID Type	Hardware RAID		
RAID Support	0, 1, 5, 6, 10, 50 and JBOD		
Capacity	Unlimited (Click here for recommended HDD and SSD)		
Number of Devices	Up to 8		
Device Type	SAS, SATA		
Device Form Factor	3.5" & 2.5"		
Power Supply	250W Low Noise PSU AC INPUT: 100-240 V 50/60Hz		
Cooling	Dual 80 x 80 x25mm Cooling Fans, Heat-Dissipating Aluminum Enclosure		
Alarm Buzzer	Buzzer beeping when failed drive or array occurs		
Material	Matte Plastic & Coated Aluminum		
Dimension	13.00" (H) x 5.67" (W) x 10.12" (D)		
Weight	12.9 lbs.		
Warranty	3 Years		
Performance	HDD: 8x disks RAIDD 2000/1900 MB/s RAID5 1700/1000 MB/s SSD: 8x disk (Read/Write) RAIDD 2700/2400 MB/s RAID5 2700/1000 MB/s		
System Requirements			
Hardware	 Computer with a USB-C (Thunderbolt™ 3) Computer with a Thunderbolt™ 2 (via Thunderbolt™ 3 to Thunderbolt™ 2 Adapter) 		
Windows	Window 8 and later Note: Your PC may require updates for the Thunderbolt™ 3 ports to function properly. See here for more information.		
Mac	Mac OS X 10.10 and later		
RAID Management	Browser-Based management tool		
	Default no password needed to access WebGUI in Mac		
	HDD Power, Present, Active, Fail, Rebuilding and Identify		
	Email Alert Notification		
Compliance Certification	CE FCC RoHS REACH WEEE		

Compliance Certification	CE FCC RoHS REACH WEEE		
Operating Environment			
Temperature	(operating) 5°C – 45°C (non-operating) -40°C – 65°C		
Humidity	(operating) 8% – 90% RH (Non-condensing) (non-operating) 5% – 95% RH (Non-condensing)		



Advanced RAID Features	
Configurable RAID Block Size up to 1MB	Online Capacity Expansion (OCE)
Flash ROM for Upgradeable BIOS	RAID Initialization Background/Foreground/Quick
DV Mode Technology	Global Hot Spare Disk support
Storage Health Inspector	Automatic and configurable RAID Rebuilding Priority
Redundant RAID Configurations	NVRAM with Write Journaling enhances RAID integrity
Bootable RAID Array	Disk Format compatible: 512, 512e, 4Kn
EFI BIOS for Mac Platform	Larger than 2 TB Drive and RAID Array support
Multiple RAID Partitions supported	Spin down Massive Arrays of Idle Disks support
Online Array Roaming	Native Command Queuing
Online RAID Level Migration (ORLM)	Write Back and Write Through

Product Model	RocketStor 6628A
Product Image	CONTENT.
Retail Box Dimensions	15.35" x 9.25" x 13.39"
Retail Box Weight	12.9 lbs.
Kit Contents	1x 8-Bay Enclosure 8x Drive Trays 1x Thunderbolt™ 40Gb/s Cable 1x UL Power Cord 32x 3.5" HDD mounting screws 32x 2.5" SSD mounting screws 1x Quick Installation Guide

HighPoint Headquarters

Phone 1-408-942-5800
Fax 1-408-942-5801
E-mail sales@highpoint-tech.com
Website www.highpoint-tech.com
Address 1161 Cadillac Ct. Milpitas
CA, 95035

HighPoint Taiwan

Phone + 886-2-2218-3435
Fax + 886-2-2218-3436
E-mail sales@highpoint-tech.com
Website www.highpoint-tech.com
Address 5F., No.3, Swei Lane, Jhongjheng
Rd., Sindian District, New Taipei City
23148, Taiwan (R.O.C.)

HighPoint China

Phone + 86-10-6213-0920
Fax + 86-10-6897-5074
E-mail sales@highpoint-tech.com
Website www.highpoint-tech.cn
Address 4th Floor Kehaifulin Building,
NO. 12 Zhong Guan Cun South
Rd, Aidian District Beijing
China 100081

