

# ThinkStation P330 Tiny 30CF000XMH

**Region**  
WE

**Country**  
Netherlands

**Machine Type**  
30CF

**TopSeller**  
TopSeller

**Processor**  
Core i7-8700T 6C/12T/2.4GHz/12MB/35W/DDR4-2666

**Memory**  
1x 16GB SoDIMM DDR4-2666 Non-ECC

**Processor Graphics**  
Intel UHD Graphics 630

**Discrete Graphics Card**  
1x Quadro P620 2GB

**Monitor Cable**  
None

**Disks**  
None

**Optane Memory**  
None

**M.2 Drives**  
1x 256GB SSD M.2 PCIe Opal

**Optical**  
None

**WLAN + Bluetooth**  
None

**Wi-Fi Antenna**  
None

**Available Networking Ports**  
1x GbE

**Optional Rear Ports - via Punch out Cable**  
None

**Optional Rear Ports - via PCIe Adapter**  
None

**vPro**  
vPro

**System Management**  
Intel AMT 12

**Keyboard**  
USB Full

**Mouse**  
USB Optical

**VESA Mount**  
None

**Cable Lock**  
Cable Lock

**Dust Filter**  
None

**Tool-less Chassis**  
None

**Floor Stand for Tiny**  
None

**Operating System**  
Windows 10 Pro 64

**Power Supply**  
135W Adapter

**External Adapter Cage for Power Adapter**  
None

**Warranty**  
3-year, Onsite

**Global**  
No

**End of Support**  
2024/08/31

**Ann Date**  
2018/07/31

## Note:

Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "\*\*\*" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<http://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2018. All rights reserved.



# ThinkStation P330 Tiny Platform Specifications

Product Specifications Reference (PSREF)

Components	Specification															
Machine Type	MT 30CF for Transactional model and MT 30CE for Relationship model. For configuration of all 30CF EMEA and US models, please visit: <a href="http://psref.lenovo.com/Product/ThinkStation/ThinkStation_P330_Tiny">http://psref.lenovo.com/Product/ThinkStation/ThinkStation_P330_Tiny</a>															
Form factor	1L. Optional VESA mount bracket kit, supports VESA 75mm and 100mm. Optional floor stand for vertical orientation. Optional tool-less chassis open. Optional dust filter															
Dimensions	Height: 179 mm (7.0 in). Width: 36.5 mm (1.437 in). Depth: 182.9 mm (7.2 in)															
Weight	Maximum configuration: 3.08 lb (1.4kg)															
Supported TIO monitors	Tiny-in-One 23 (MT: 10DQ). Tiny-in-One 22 (MT: 10LK). Tiny-in-One 24 (MT: 10LL). Tiny-in-One22 Gen3 (MT: 10R1). Tiny-in-One22 Gen3 Touch (MT: 10R0). Tiny-in-One24 Gen3 (MT: 10QY). Tiny-in-One24 Gen3 Touch (MT: 10QX).															
Processor	Up to one Intel Core family processor, i7, i5, or i3. Core i7 supports 65W or 35W, 6 cores, up to 3.2GHz, 12MB cache, DDR4-2666 memory speed. Core i5 supports 65W or 35W, 6 cores, up to 3.1GHz, 9MB cache, DDR4-2666 memory speed. Core i3 supports 65W, 62W, or 35W, 4 cores, up to 3.7GHz, 6MB or 8MB cache, DDR4-2400 memory speed.															
Chipset	Intel Q370 Chipset															
Memory	2 DIMM sockets. DDR4-2666. SoDIMM. Non-ECC															
Expansion slots	One PCIe slot via specific riser card: PCIe 3.0 x16 (negotiable link width x8) and low profile for discrete graphics card; PCIe 3.0 x4 and low profile for i350-T4 adapter and quad COM ports adapter															
Graphics	65W or 62W processor models supports processor graphics only. 35W processor models come with processor graphics plus a discrete graphics adapter															
Graphics - Processor graphics	Integrated Intel UHD Graphics 630. Works along with discrete graphics to support multi-display															
Graphics - Discrete graphics card	One of the following discrete graphics cards on 35W processor models: <table><tr><th>Adapter</th><th>Cores</th><th>Memory</th><th>Power</th><th>Connectors</th></tr><tr><td>Quadro P620</td><td>512</td><td>2GB GDDR5</td><td>40W</td><td>4x miniDP</td></tr><tr><td>Quadro P1000</td><td>640</td><td>4GB GDDR5</td><td>47W</td><td>4x miniDP</td></tr></table>	Adapter	Cores	Memory	Power	Connectors	Quadro P620	512	2GB GDDR5	40W	4x miniDP	Quadro P1000	640	4GB GDDR5	47W	4x miniDP
Adapter	Cores	Memory	Power	Connectors												
Quadro P620	512	2GB GDDR5	40W	4x miniDP												
Quadro P1000	640	4GB GDDR5	47W	4x miniDP												
Storage controllers	Integrated Intel SATA AHCI controller in chipset, 6Gbps SATA, one onboard SATA port for 2.5" HDD															
Internal storage bay	Up to one 2.5" HDD															
Disks	2.5" HDD supports up to 1TB, 6Gbps SATA, 7.2K or 5.4K															
M.2 slot for SSD	Two onboard M.2 slots for M.2 SSD, one for M.2 2280 SSD, one for M.2 2280 or 2242 SSD															
M.2 SSD	M.2 2280 SSD supports up to 1TB each, PCIe 3.0 x4, NVMe, optional Opal. M.2 2242 SSD supports up to 128GB, PCIe 3.0 x2, NVMe															
Optane memory	Up to one 16GB Optane memory per system. Optane memory must work with a 2.5" HDD															
M.2 slot for Wi-Fi and Bluetooth	One dedicated M.2 2230 slot for optional Wi-Fi card, supports one of the following: Intel Wireless-AC 9560, 2x2, 2.4GHz/5GHz (160MHz channels), 802.11ac, Bluetooth 5, up to 1.73Gbps. Intel Wireless-AC 8265, 2x2, 2.4GHz/5GHz, 802.11ac, Bluetooth 4.2, up to 867Mbps. <i>Note: Wi-Fi card, or specific functions of Wi-Fi card may not be supported in some countries</i>															
Wi-Fi antenna	Optional Tiny 2.4GHz/5GHz SMA antenna kit															
Optical	Optional one 9.0mm optical drive via optical drive kit, DVD-ROM or DVD±RW. VESA mount is required															
Media reader	None. Using USB adapter															
Network interfaces	One onboard GbE port via integrated gigabit ethernet Intel i219LM, supports Wake-on-LAN. Optional Intel i350-T4 for 4x GbE ports, using PCIe slot															
Security features	Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant. Chassis intrusion switch. Optional Kensington lock															

Components	Specification
Intel vPro Technology	Supports vPro on models with the following processors: Core i7-8700T, Core i7-8700, Core i5-8600T, Core i5-8600, Core i5-8500T, Core i5-8500. vPro also requires Wireless-AC 9560 if Wi-Fi is needed
Systems management	Intel Active Management Technology 12 on vPro models, Intel Standard Manageability on other models
Base warranty	US models comes with 3-year limited onsite service with 9x5/NBD. 1 or 3-year limited onsite service with 9x5/NBD in EMEA or other GEOs
HD Audio	Intel HD Audio interface with Realtek ALC233 Codec
Front standard ports	1x USB 3.1 Gen 1 Type A (charging). 1x USB 3.1 Gen 1 Type-C. 1x Mic-in. 1x Combo jack
Rear standard ports	2x USB 3.1 Gen 2 Type A. 2x USB 3.1 Gen 1 Type-A. 1x RJ-45. 1x DP. 1x HDMI
Optional rear ports - via punch out cable	Up to two optional rear ports via punch out cable. Port 1 supports one of the following: 1x USB 3.1 Gen 1 Type-C, also supports DP function. 1x COM. 1x VGA. 1x DP. 1x HDMI. Port 2 supports one COM
Optional rear ports - via PCIe adapter	Supports one of the following: 4x miniDP with Quadro P620 or P1000, 35W processor models only 2x USB 3.1 Gen 1. 4x RJ-45 GbE with Intel I350-T4. 4x COM <i>Note: Punch out cable and PCIe adapter are mutually exclusive</i>
Temperature	Operating: 50 °F to 95 °F (10 °C to 35 °C) Non operating (with package): -40 °F to 140 °F (-40 °C to 60 °C)
Altitude	Operating: -15.2 m (-50 ft) to 3048 m (10 000 ft). Storage: -15.2 m (-50 ft) to 10, 668 m (35 000 ft)
Humidity	Operating: 20%~80%, non-condensing Storage (with package): 20%~90%, non-condensing
Environmental certification	RoHS-compliant. GREENGUARD. EPEAT Gold rating and ENERGY STAR 7 qualified
Power supply	Supports one 135W power adapter, 100V - 240V, 88% PSU
ISV certifications	Please visit <a href="http://www.thinkworkstations.com/isv-certifications/">www.thinkworkstations.com/isv-certifications/</a>

Lenovo

# ThinkStation P330 Tiny

