


NEC Direct View LED-Q048e (4.8mm Q-Series Outdoor)



NEC Direct View LED - Intelligent display solutions for a brighter world

The S[quadrat] Q-Series by NEC provide crystal clear images for the ultimate visual experience. With pixel spacing options of 2.8mm, 3.9mm & 4.8mm, the optimum display resolution can be achieved regardless of viewing distance; plus, the front serviceable design allows easy access and quick maintenance when needed. Designed for vibrant and colorful content visualization, the S[quadrat] Q-series dvLED is the ideal solution for auditoriums, reception areas, retail stores, control and meeting rooms, museums, broadcast studios and

airports or train stations. NEC offers full design & planning services plus post installation service plans, ensuring you get a custom tailored solution allowing you to focus on what's most important - your business

BENEFITS

Easy front access for installation and maintenance


Application in corporate, transport, retail, cinema, entertainment, museum and arenas

Low power consumption and less heat dissipation make "Ocean Series" an environment-friendly product

High efficient LED chip plus black mask for higher contrast ratio

Unique strong, light weight modules with quick lock devices to easily enable rental LED system





DISPLAY	
Panel Technology	Direct View LED
Pixel Configuration	3-1 SMD (Black)
Panel Resolution	104 x 104
Pixel Pitch	4.8mm
Brightness (maximum)	5000cd/m2
Display	80,000 hours
Contrast Ratio(typical)	6000:1
Viewing Angle	70/70 horizontal / 70/70 vertical
Dimming Capability	256 levels
Color Processing	16 bit
Displayable Colors	281 Trillion
Refresh Rate(Hz)	1920
Orientation	Landscape
Connectivity	
Input Terminals	Digital: DVI-D Dual Link in/out or HDMI External Control: RS232 / USB
External Control	USB
PowerConsumption(typical)	
On	245Watts/sqm
Max	700Watts/Sqm
Physical Specifications	
Dimensions (W x H x D) [mm]	500 x 500 x 78mm
Weight [kg]	19.8lbs (9kg)
Environmental Conditions	
Operating Temperature	-4° to 122°f / -20° to 50°c
Environmental Conditions	10% to 90%
Storage Temperature	-4° to 122°f / -20° to 50°c
Servicability	
Rear Service	
IP Level	
IP65	
Accessories	
Controller	
Mounting Frame	
Ambient Light Sensor	
Power Box with remote On/Off Control	
Onsite Installation	

All rights reserved in favor of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice.

©2018 NEC Display Solutions of America, Inc. and the NEC logo are registered trademarks of NEC.

Cat.No. 25.NEC.80.GL.UN.248 | 8.15.2018

www.necdisplay.com