



VTrak E5000 Series Data Sheet



16Gb Fibre Channel to 12Gb SAS/SATA
High-Availability Storage System for Big Data



Benefits

- ▶ High-performance, high-bandwidth allowing more than 12.8 GB/s aggregate transfer rate
- ▶ High-Availability provides assurance of continuous operation
- ▶ Active-Active Dual Controller with ALUA for performance and access flexibility
- ▶ Virtualization Ready
- ▶ 80 PLUS GOLD certified PSUs, Deliver power efficiency, and Energy Star Ready
- ▶ Advanced diagnostics and reporting with persistent error log
- ▶ Support massive capacity by cascading up to 9 J5000 12Gb or SAS/SATA JBOD Storage Expansions

Tech Highlights

- ▶ Quad 16 Gb FC ports per Controller provides maximum bandwidth
- ▶ 12 Gb SAS backend storage interface to support the fastest HDD/SSD
- ▶ Backward compatible to 8 Gb and 4 Gb on Fibre Channel interface, and to 6 Gb on SAS/SATA interface
- ▶ Conveniently accessible persistent error logging and HTML formatted Service Report
- ▶ Online Capacity Expansion allows Volume size to grow with ease
- ▶ Software Updates without disrupting operation
- ▶ Background Data Integrity Checking and Parity Rebuild
- ▶ Predictive Data Migration (PDM) minimizes maintenance requirement

Affordable Enterprise-level Storage

Delivers an affordable high-performance Fibre Channel to SAS Storage solution with advanced enterprise level reliability and functionality.

Four 16Gb Fibre Channels ports and Two 12Gb SAS port (SFF-8644) per controller for connecting Host and Storage Expansion, respectively. Perfect for applications requiring huge bandwidth.

Redundant and Active-Active components of controllers, power supplies, and cooling units providing optimal data availability for any unforeseen circumstance.

Full featured Enterprise-level Storage System to accommodate any size of business environment.

IT/Data Center Ready

The ability to deploy 6/12 Gb SAS/SATA hard drives and SSDs in the E5000 Series.

Efficient power supplies provide up to 90% power efficiency that improves TCO by conserving power, reducing heat output and improving cooling costs.

Flash arrays enable optimized speed for key enterprise applications that need High-speed transfer rate and reduced latency.

Intel multi-cores processors allows saturation of line rate speeds for both 16Gb Fibre Channel Front-end and 12Gb SAS Backend interfaces.

Delivers high capacity for archiving and backup




Transport feature allows portability to move and/or store Petabytes from one location to another with data intact

Virtualization Ready

Ready to confront any challenge in today's virtualized IT environment, the VTrak E5000 Series is certified with VMware vSphere, Citrix XenServer, Microsoft Hyper-V, Veeam, and DataCore SANsymphony.

Virtualization enables dynamic storage allocations such that physical layers of storage can be utilized most effectively. As virtual machines continue to increase with more virtualized deployments, 16Gb Fibre Channel performance delivers the faster bandwidth needed for growing infrastructures.

Technical Specifications

	VTrak E5300f	VTrak E5600f	VTrak E5800f
Models	2U/12 Bay 	3U/16 Bay 	4U/24 Bay 
Drive Support	Up to 12 3.5" drives	Up to 16 3.5" drives	Up to 24 3.5" drives
External I/O Ports	6/12 Gb SAS, 6 Gb SATA HDD and SSD Supports any mix of SAS and SATA drives simultaneously in the same enclosure		
Operational Features	Each SBB2.0 RAID Controller has four 16 Gb FC SFP ports for Host interface and two 12 Gb SAS standard Mini SAS HD ports (SFF-8644) for Storage Expansion, RJ45 1Gb Ethernet and RS232 for Management ports		
RAID Levels	0, 1, 5, 6, 10, 50, 60		
RAID Stripe Size Support	64K, 128K, 256K, 512K and 1MB		
Hot Spares	Global or dedicated with revertible option		
Max LUNs per Subsystem	1024		
Max Luns per array	32		
Advanced Storage Features	<ul style="list-style-type: none"> Advanced Cache Mirroring over PCIe Gen3 Simple, drag-and-drop LUN Masking and Mapping Asymmetric LUN Unit Access (ALUA) Volume Copy 	<ul style="list-style-type: none"> PerfectFlash - Non-Disruptive Software Update I/O performance & power monitoring tools USB Service Log LDAP Support for central user management 	
Background Activities	<ul style="list-style-type: none"> Media Patrol Background Synchronization Foreground Initialization Rebuild Redundancy Check 	<ul style="list-style-type: none"> Disk SMART Polling Online Capacity Expansion (OCE) RAID Level Migration (RLM) UPS Monitoring Feature rich task scheduler for background activities 	
PerfectRAID Features	<ul style="list-style-type: none"> Predictive Data Migration (PDM) Intelligent Bad Sector Remapping SMART Error Handling NVRAM Error Logging 	<ul style="list-style-type: none"> Disk Slot Power Control Read/Write Check Table Write Hole Table 	
GreenRAID Features	<ul style="list-style-type: none"> Four levels of advanced power management disk drive (MAID) support Efficient 80Plus Certified power supplies 		
System Management	<ul style="list-style-type: none"> Web Based management using WebPAM PROe (Ethernet) Command Line Interface (CLI) or Command Line Utility (Serial Port or Ethernet via Telnet, SSH) Third Party Management Support via SNMP, CIM 		
Supported OSs	Windows Server 2008, 2012, OS X 10.x, RHEL 6.5, 6.6, 6.7, and 7.2, SLES 11, 11 SP4, and 12 SP1		
Software Certification	VMware ESXi 6.0, VEEAM Backup & Replication 9.0, Citrix Server 7.0, Data Core SANSymphony 10.0 PSP6, Windows, Arcserve UDP v6.0.3792 Update 3 Build 776, XSAN 5, StorNext v5.3		
Mechanical Specifications			
Voltage	100--240 Vac Auto--Ranging		
Current (Maximum)	9A @ 100 Vac; 4A @ 240 Vac		
Power Conversion Efficiency	>80% @ 110V (>20% load), >80% @ 240V (>20% load) Temperature Range		
Temperature Range	Operational: 5° to 35°C, Non-Operational: -40° to 60°C		
Humidity	Operational: 20% to 80% (Non-Condensing), Non--Operational: ~ 95% (Non-Condensing)		
Acoustic Noise Levels	< 60dB, 25C		
Shock	Operational: 5G, 11 ms duration, Non-Operational: 30G, 11ms duration		
Vibration	Operational: 0.2G, 5 to 500Hz (sine wave) ; 0.41G, 3-10-200-500Hz (Random) , Non-Operational: 1G, 5 to 500Hz (sine wave) ; 2.256G, 5-80-350-500Hz (Random)		
Safety and Emission Certification	EMC Class A: CE, FCC, VCCI, BSMI, RCM Safety: IEEE CB, UL/cUL and TUV VT50002U12, VT50003U16, VT50004U24		
Environmental Standards	RoHS, GreenPC, WEEE		
Power Supply	Efficient 80PLUS GOLD Certified redundant PSU		
Dimensions (H x W x D)	88 x 446.7 x 507 mm	131 x 446.7 x 507 mm	174.4 x 446.7 x 507 mm
Weight	18.9Kg (41.7 lbs) w/o drives 26.8Kg (59.1 lbs) w/ drives	23Kg (50.7 lbs) w/o drives 33.4Kg (73.6 lbs) w/ drives	24.8Kg (54.7 lbs) w/o drives 40.5Kg (89.2 lbs) w/ drives
Warranty and Support			
Warranty	3-year full system limited warranty, optional extended warranty, onsite parts replacement program		
Support	24/7 e-mail and phone support, 24/7 access to PROMISE site-drives, firmware, and compatibility list		

SATA drives require a SAS-SATA adapter

Contact us



© 2017 PROMISE Technology, Inc. All Rights Reserved. PROMISE, the PROMISE logo, Pegasus, SANLink, Vess, VTrak logos are registered or pending trademarks of PROMISE Technology, Inc. in the U.S. and other countries. All other trademarks are the property of their respective owners. Information regarding products, services, and offerings may be superseded by subsequent documents and are subject to change without notice. P/N: G6130000000071 2017 August