

# Compact USB C to HDMI Adapter - 4K 30Hz USB Type-C to HDMI Video Display Converter with Keychain Ring - USB-C DP Alt Mode to HDMI Monitor Dongle - Thunderbolt 3 Compatible

Product ID: CDP2HDFC



This compact USB-C<sup>™</sup> to HDMI® adapter offers an ultra-portable solution for connecting your USB Type-C laptop or other device with a USB 3.1 Type-C port to a 4K HDMI monitor or display. The adapter is equipped with a removable, quick-connect keychain ring that easily attaches to your laptop or projector bag, maximizing portability.

For added convenience, this USB-C adapter is also available with <u>Mini DisplayPort</u> or <u>VGA</u> outputs.

## **Perfect Travel Companion**

This lightweight USB-C video converter can easily be taken with you wherever you go. It conveniently attaches to your carrying case and is small enough to fit in your pocket, making it ideal for BYOD (Bring Your Own Device) applications at the office or road warriors who need to connect on the go.





#### It's the perfect solution for:

- Delivering high-resolution presentations while in the office or traveling
- Connecting your smartphone or tablet to an HDMI monitor
- Hot-desking environments

### **Keep Your Adapter with You**

Avoid misplacing your display adapter with the attached keychain that securely snaps to your carrying case so you can always keep it with your devices; the keychain can easily be removed or reattached to the adapter so you can customize it to your preference and need. The adapter also features a built-in 1.3 in. flex cable that has a folding design, adding to the compact form factor.

#### **Plug-and-Play Connectivity**

To ensure a hassle-free connection, this video adapter works with all your Mac and Windows® USB Type- $C^{\text{TM}}$  devices and is also compatible with Thunderbolt<sup>TM</sup> 3. It requires no additional software or drivers, supporting true plug-and-play connectivity.

CDP2HDFC is backed by a StarTech.com 3-year warranty and free lifetime technical support.





# Certifications, Reports and Compatibility











#### **Applications**

- Connect to virtually any 4K HDMI monitor when you're in the office or traveling
- Connect your USB-C equipped tablet or smartphone to a larger display
- Add a secondary monitor to your workstation

#### **Features**

- PERFORMANCE: USB-C (DP 1.2 Alt Mode/HBR2) to HDMI 1.4 Adapter supports UHD 4K 30Hz (3840x2160) video, 7.1ch Audio, HDCP 2.2/1.4 | 1080p & Thunderbolt 3 compatible USB C to HDMI dongle
- PORTABLE DESIGN: Compact & lightweight USB C to HDMI adapter is perfect for travelling; equipped with a flexible wrap-around cable & removable keychain ring that securely attaches to your bag
- COMPATIBILITY: Dell XPS, Precision & Latitude, Lenovo ThinkPad X1
   Carbon & Extreme, Microsoft Surface Book & Surface Laptop 3,
   MacBook Pro, TB3 MacBook Air, HP EliteBook, Spectre & ZBook & Chromebook
- TESTED & VERIFIED: USB C to HDMI converter (male to female connector) compatible w/ 4K/1080p displays & TVs like Dell, Samsung, Asus, Acer & LG, and projectors like Sony, Christie, LG, NEC & Epson
- EASY TO USE: USB-C to HDMI adapter supports driverless plug & play setup & is compatible w/ macOS, Windows 10, Linux, Chrome OS, Android; works w/ any USB Type-C or TB3 (DisplayPort over USB-C) device



# **Data Sheet**

RandwareAudioYesAV InputUSB-CAV OutputHDMI - 1.4Chipset IDRealtek RTD2171UPorts1PerformanceAudio SpecificationsHDMI - 7.1 Channel AudioVideo RevisionAdditional resolutions and refresh rates may be supported Additional resolutions and refresh rates may be supported President Provided Provided President President President Provided President Provided President Provided President Provident President		Warranty	3 Years
AV Output Chipset ID Realtek RTD2171U Ports 1  Performance Audio Specifications HDMI - 7.1 Channel Audio Supported Resolutions 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Ves  Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - HDMI (19 pin) Female Output  Special Notes / Requirements Humidity 5-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature - 10°C to 70°C (14°F to 158°F)  Physical Characteristics Color Black Material Plastic Product Height 14.000 Product Length 13 in [3.2 cm] Product Width 48.000 Weight of Product 17.000  Packaging Information Package Height 122.000 Package Width 90.000 Shipping (Package) Weight 21.500	Hardware	Audio	Yes
Chipset ID   Ports   1		AV Input	USB-C
Performance Audio Specifications HDMI - 7.1 Channel Audio Supported Resolutions 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Video Revision Wide Screen Supported Yes  Connector(s) Connector A Connector B 1 - HDMI (19 pin) Female Output  Special Notes / Requirements Furironmental Humidity Operating Temperature O°C to 70°C (32°F to 158°F) Storage Temperature O°C to 70°C (14°F to 158°F)  Physical Characteristics Color Material Product Height Product Length Product Height Product Width Weight of Product Package Height Information Package Height Package Width Package Width Package Width Package Width Package Weight Support Alt Mode (AK) / 30Hz Additional resolutions Additional resolutions Additional resolutions and refresh rates may be supported Weight of Package Weight PDMI 1.4  BDMI 1.4  Yes  Couls C 42 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C (24 pin) DisplayPort Alt Mode Male Input  Four USB-C device must support DisplayPort Out USB-C (DP Alt Mode) to work with this adapter  Four USB-C device must support DisplayPort Out USB-C (DP Alt		AV Output	HDMI - 1.4
Performance       Audio Specifications       HDMI - 7.1 Channel Audio         Supported Resolutions       3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported         Video Revision       HDMI 1.4         Wide Screen Supported       Yes         Connector (s)       Connector A       1 - USB-C (24 pin) DisplayPort Alt Mode Male Input         Connector B       1 - HDMI (19 pin) Female Output         Special Notes / Requirements       System and Cable Requirements       Your USB-C device must support DisplayPort over USB-C (DP Alt Mode) to work with this adapter         Environmental       Humidity       5-90% RH (no condensation)         Operating Temperature       0°C to 70°C (32°F to 158°F)         Storage Temperature       0°C to 70°C (32°F to 158°F)         Physical Characteristics       Cable Length       0.1 in [0.3 cm]         Color       Black         Material       Plastic         Product Height       14.000         Product Length       1.3 in [3.2 cm]         Product Width       48.000         Weight of Product       17.000         Package Length       122.000         Package Width       90.000         Special Notes / Requirements       21.500		Chipset ID	Realtek RTD2171U
Supported Resolutions 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported  Video Revision HDMI 1.4  Wide Screen Supported Yes  Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - HDMI (19 pin) Female Output  Special Notes / Requirements  Finvironmental Humidity 5-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 70°C (14°F to 158°F)  Cable Length 0.1 in [0.3 cm]  Physical Characteristics  Color Black Material Plastic Product Height 14.000 Product Length 1.3 in [3.2 cm] Product Width 48.000 Weight of Product 17.000  Packaging Information  Package Length 122.000 Package Width 90.000 Shipping (Package) Weight 21.500		Ports	1
Additional resolutions and refresh rates may be supported Video Revision Wide Screen Supported Yes  Connector(s) Connector A Connector B 1 - HDMI (19 pin) Female Output  Special Notes / Requirements Finvironmental Humidity Operating Temperature Ove to 70°C (32°F to 158°F) Storage Temperature Ove to 70°C (14°F to 158°F)  Color Black Material Product Height Product Height Product Width Weight of Product  Package Height Package Length Package Length Package Width Package Width Package Width Sibping (Package) Weight  A USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - USB-C (24 pin) DisplayPort Alt Mode Note 1 - USB-C (24 pin) DisplayPort Alt Mode Note 1 - USB-C (24 pin) DisplayPort Alt Mode Note 1 - USB-C (24 pin) DisplayPort Alt Mode Note 1 - USB-C (24 pin) DisplayPort Alt Mode Note 1 - USB-C (24 pin) DisplayPort Alt Mode Note 1 - USB-C (24 pin) DisplayPort Alt Mode Note 1 - USB-C (24 pin) DisplayPort Alt Mode Note 1 - USB-C (24 pin) Display Port Alt Mode Note 1	Performance	Audio Specifications	HDMI - 7.1 Channel Audio
Wide Screen Supported  Connector(s) Connector A Connector B 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - HDMI (19 pin) Female Output  Special Notes / Requirements  Environmental Humidity Operating Temperature O°C to 70°C (32°F to 158°F) Storage Temperature O°C to 70°C (14°F to 158°F)  Physical Characteristics  Color Material Product Height Product Height 14.000 Product Length Neight of Product Weight of Product  Package Height Information  Package Length Package Width Shipping (Package) Weight Sugar 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 2 - HDMI (19 pin) Female Output		Supported Resolutions	
Connector (s)  Connector A Connector B 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - HDMI (19 pin) Female Output  Special Notes / Requirements  System and Cable Requirements  Finitronmental Humidity Operating Temperature Storage Temperature  Color Material Product Height Product Length Product Ushth Product Width Weight of Product  Packaging Information  Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - HDMI (19 pin) Female Output 1 - HDMI (19 pin)		Video Revision	HDMI 1.4
Special Notes / Requirements System and Cable Requirements Requirements  Environmental Humidity Operating Temperature Storage Temperature Color Material Product Height Product Length Product Length Product Width Weight of Product Weight of Product Tinformation  Package Height Package Width Shipping (Package) Weight  System and Cable Requirements Your USB-C device must support DisplayPort over USB-C (DP Alt Mode) to work with this adapter  Four USB-C (DP Alt Mode) to work with this adapter  System and Cable Requirements (DP Alt Mode) to work with this adapter  Four USB-C (DP Alt Mode) to work with this adapter  Four USB-C (DP Alt Mode) to work with this adapter  Four USB-C (DP Alt Mode) to work with this adapter  Four USB-C (DP Alt Mode) to work with this adapter  Four USB-C (DP Alt Mode) to work with this adapter  Four USB-C (DP Alt Mode) to work with this adapter  Four USB-C device must support DisplayPort over USB-C (DP Alt Mode)  Four USB-C device must support DisplayPort over USB-C (DP Alt Mode) to work with this adapter  Four USB-C device must support DisplayPort over USB-C (DP Alt Mode) to work with this adapter  Four USB-C device must support DisplayPort over USB-C (DP Alt Mode) to work with this adapter  Four USB-C device must support DisplayPort over USB-C (DP Alt Mode) to work with this adapter  Four USB-C device must support DisplayPort over USB-C (DP Alt Mode) to work with this adapter  Four Usa Manual Support DisplayPort Office of 158°F)  Four Usa Manual Support Office of 158°F)  Four Usa Manual Support Office of 158°F)  Four Usa Manual Support Office of 158°F)  Four Usa Man		Wide Screen Supported	Yes
Special Notes / Requirements   System and Cable Requirements   Your USB-C device must support DisplayPort over USB-C (DP Alt Mode) to work with this adapter	Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
Requirements       Environmental     Humidity     5-90% RH (no condensation)       Operating Temperature     0°C to 70°C (32°F to 158°F)       Storage Temperature     -10°C to 70°C (14°F to 158°F)       Physical Characteristics     Cable Length     0.1 in [0.3 cm]       Color     Black       Material     Plastic       Product Height     14.000       Product Length     1.3 in [3.2 cm]       Product Width     48.000       Weight of Product     17.000       Packaging Information       Package Height     14.000       Package Length     122.000       Package Width     90.000       Shipping (Package) Weight     21.500		Connector B	1 - HDMI (19 pin) Female Output
Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 70°C (14°F to 158°F)  Physical Characteristics  Cable Length 0.1 in [0.3 cm]  Color Black Material Plastic Product Height 14.000 Product Length 1.3 in [3.2 cm] Product Width 48.000 Weight of Product 17.000  Packaging Information  Package Length 122.000 Package Width 90.000 Shipping (Package) Weight 21.500	•	System and Cable Requirements	
Physical Cable Length	Environmental	Humidity	5-90% RH (no condensation)
Physical CharacteristicsCable Length0.1 in [0.3 cm]ColorBlackMaterialPlasticProduct Height14.000Product Length1.3 in [3.2 cm]Product Width48.000Weight of Product17.000Packaging InformationPackage Height14.000Package Length122.000Package Width90.000Shipping (Package) Weight21.500		Operating Temperature	0°C to 70°C (32°F to 158°F)
Color Black Material Plastic Product Height 14.000 Product Length 1.3 in [3.2 cm] Product Width 48.000 Weight of Product 17.000  Packaging Information Package Height 122.000 Package Width 90.000 Shipping (Package) Weight 21.500		Storage Temperature	-10°C to 70°C (14°F to 158°F)
Material Plastic Product Height 14.000 Product Length 1.3 in [3.2 cm] Product Width 48.000 Weight of Product 17.000  Packaging Information Package Length 122.000 Package Width 90.000 Shipping (Package) Weight 21.500	-	Cable Length	0.1 in [0.3 cm]
Product Height 14.000 Product Length 1.3 in [3.2 cm] Product Width 48.000 Weight of Product 17.000  Packaging Information Package Length 122.000 Package Width 90.000 Shipping (Package) Weight 21.500		Color	Black
Product Length 1.3 in [3.2 cm] Product Width 48.000 Weight of Product 17.000  Packaging Information Package Length 122.000 Package Width 90.000 Shipping (Package) Weight 21.500		Material	Plastic
Product Width 48.000 Weight of Product 17.000  Packaging Information Package Height 14.000 Package Length 122.000 Package Width 90.000 Shipping (Package) Weight 21.500		Product Height	14.000
Packaging Information  Package Height 14.000  Package Length 122.000  Package Width 90.000  Shipping (Package) Weight 21.500		Product Length	1.3 in [3.2 cm]
Packaging Information  Package Height 14.000  Package Length 122.000  Package Width 90.000  Shipping (Package) Weight 21.500		Product Width	48.000
Package Length 122.000 Package Width 90.000 Shipping (Package) Weight 21.500		Weight of Product	17.000
Package Width 90.000 Shipping (Package) Weight 21.500		Package Height	14.000
Shipping (Package) Weight 21.500		Package Length	122.000
		Package Width	90.000
What's in the Box Included in Package 1 - USB-C to HDMI Adapter		Shipping (Package) Weight	21.500
	What's in the Box	Included in Package	1 - USB-C to HDMI Adapter

Product appearance and specifications are subject to change without notice.