

AXIS P5654-E PTZ Network Camera

Wide angle PTZ with HDTV 720p and 21x zoom

AXIS P5654-E PTZ Network Camera is a cost-effective, high performance PTZ camera that offers wide area coverage with 77° field of view. It features Lightfinder 2.0 to capture low-light images with more saturated colors and sharper images of moving objects. And, Forensic WDR for clarity even when there's both dark and light areas in the scene. Electronic image stabilization for stable images and enhanced security features including signed firmware and secure boot. With IP66, NEMA 4X and IK10 ratings it's resistant to both harsh weather conditions and impacts. Plus, you get extended capabilities for advanced analytics.

- > [HDTV 720p with 21x optical zoom](#)
- > [Lightfinder 2.0 and Forensic WDR](#)
- > [Signed firmware and secure boot](#)
- > [Electronic image stabilization](#)
- > [Zipstream with support for H.264 and H.265](#)



AXIS P5654-E PTZ Network Camera

Models	AXIS P5654-E 50 Hz AXIS P5654-E 60 Hz	trap, overlay text, prioritized text, record video to SD card and network share, WDR mode	
Camera			
Image sensor	1/2.8" progressive scan RGB CMOS	Data streaming Event data	
Lens	Varifocal, 4.0–84.6 mm, F1.6 – 4.5 Horizontal field of view: 77.0°– 3.6° Vertical field of view: 43.1°– 2.0° Autofocus and auto-iris	Built-in installation aids Pixel counter	
Day and night	Automatically removable infrared-cut filter	Analytics	
Minimum illumination	Color: 0.11 lux at 50 IRE F1.6 Color: 0.1 lux at 30 IRE F1.6 B/W: 0.03 lux at 50 IRE F1.6 B/W: 0.01 lux at 30 IRE F1.6	Compute capabilities Machine learning processing unit (MLPU)	AXIS Object Analytics Object classes: humans, vehicles Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
Shutter speed	1/66500 s to 2 s	Applications Included AXIS Object Analytics AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, advanced gatekeeper, autotracker 2 Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
Pan/Tilt/Zoom	Pan: 360° endless, 0.1°– 350°/s Tilt: 180°, 0.1°– 350°/s Zoom: 21x optical, 12x digital, Total 252x zoom 256 preset positions, e-flip, limited guard tour, control queue, on-screen directional indicator, set new pan 0°, focus window, focus recall	General	
Video			Casing IP66-, NEMA 4X- and IK10 Aluminum casing, polycarbonate (PC) dome Color: white NCS S 1002-B, repaintable skin cover For repainting instructions of casing and impact on warranty, contact your Axis partner.
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Sustainability PVC free	
Resolution	1280x720 HDTV 720p to 320x180	Memory 1024 MB RAM, 512 MB Flash	
Frame rate	Up to 60/50 fps (60/50 Hz) in all resolutions	Power Axis PoE+ midspan 1–port: 100–240 V AC, max 37 W IEEE 802.3at, Type 2 Class 4 Camera consumption: typical 8 W, max 16 W (PoE+ midspan not included)	
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Controllable frame rate and bandwidth Axis Zipstream technology in H.264 and H.265 VBR/ABR/MBR H.264/H.265	Connectors RJ45 10BASE-T/100BASE-TX PoE RJ45 push-pull connector (IP66) included	
Image settings	Compression, saturation, brightness, sharpness, contrast, local contrast, white balance, exposure control, exposure zones, Forensic WDR: Up to 120 dB depending on scene, defogging, day/night shift level, tone mapping, fine tuning of low-light behavior, rotation: 0°, 180°, text and image overlay, image freeze on PTZ, electronic image stabilization, scene profiles, 20 individual polygon privacy masks	Storage Support for SD/SDHC/SDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com	
Network			Operating conditions -30 °C to +50 °C (-22 °F to 122 °F) Maximum intermittent temperature +55 °C Humidity 10–100% RH (condensing)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTP/2, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP ^b , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, NTPCIP, LLDP, CDP, MQTT v3.1.1, Syslog	Approvals EMC EN 50121-4, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), IEC 62236-4, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, EC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X Network NIST SP500-267, IPv6 USGv6	
System integration			Dimensions Height: 217 mm (8 9/16 in) ø 188 mm (7 3/8 in)
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	Weight 2.5 kg (5.5 lb)	
Event conditions	Device status: Above operating temperature, Above or below operating temperature, Below operating temperature, Fan failure, IP address removed, Network lost, New IP address, Shock detected, Storage failure, System ready, Within operating temperature, Edge storage, Recording ongoing, Storage disruption I/O: Manual trigger, Virtual input PTZ: PTZ malfunctioning, PTZ movement: Camera 1, PTZ preset position reached: Camera 1, PTZ ready Scheduled and recurring: Scheduled event Video: Day-night mode, Live stream open	Included accessories RJ45 Push-pull Connector (IP66), Hard ceiling mount, Spring pipe adaptor, U-profile pipe adaptor, Installation Guide, Windows [®] decoder 1-user license, AVHS Authentication key, smoked dome	
Event actions	Day-night mode, go to preset position, guard tour, upload of images or video clips via FTP, SFTP, HTTP, HTTPS, network share and email, notification to email, HTTP, HTTPS, TCP and SNMP	Optional accessories AXIS T91B mounts, AXIS T94A02L recessed mount, outdoor RJ45 cable with premounted connector, AXIS T8133 Midspan 30 W 1-port, repaintable skin covers For more accessories, see axis.com	

Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	Environmental responsibility: axis.com/environmental-responsibility
Warranty	5-year warranty, see axis.com/warranty	