

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

This product supports 4K 60Hz 4:4:4 subsampling for HDR televisions. To ensure optimal performance, check the factory default settings on your display:

- Frequency (Hz) should be set to 60 Hz
- HDR feature should be enabled
- HDMI input settings should be set to 2.0
- UHD Deep Color should be set to ON

# 2-Port HDMI over Cat6 Active Remote Receiver for Video/Audio, PoC, 4K @ 60 Hz, Up to 125 ft., TAA

# MODEL NUMBER: B127-200-H









Works with Tripp Lite B127-Series transmitters to extend 4K audio/video via Cat6 cable to 2 HDMI displays up to 125 ft. away.

#### Features

#### 2-Port Receiver Extends HDMI Signals for 4K Digital Signage or Video Presentations

This box-style active remote receiver works in tandem with Tripp Lite's B127-002-H or B127-004-H transmitter to extend 4K video (at 60 Hz) and 7.1 audio from an HDMI source to two HDMI displays up to 125 feet using Cat6 cabling. It can also extend a 4K HDMI signal (at 30 Hz) up to 150 feet and a 1080p HDMI signal (at 60 Hz) up to 200 feet.

# An Ideal Setup for Settings Where Conventional HDMI Cables Can't Reach

The B127-200-H is recommended for home theaters and video presentations in conference rooms, schools, trade shows, meeting facilities, houses of worship, retail settings and other digital signage applications where the source and display are farther apart than conventional A/V cables allow.

#### Built-In PoC Technology Provides Power to Avoid Bulky External Power Bricks

Built-in Power over Cable (PoC) technology powers the low-profile receiver over Cat6 cable. Green and orange LEDs will light up to indicate the unit is receiving power and a signal is being received. PoC lets you avoid the hassle of a bulky power brick and gives you the freedom to place the receiver away from an AC outlet.

### Supports Crystal-Clear 4K HDMI Video with Multi-Channel Audio and 4:4:4 Color

The B127-200-H supports Ultra HD video resolutions up to 3840 x 2160 (4K x 2K) at 60 Hz with full, rich uncompressed DTS-HD, Dolby TrueHD and 7.1-channel digital audio. Built-in equalization automatically fine-tunes the image quality at the remote displays with no time-consuming manual fiddling needed. The receiver is compatible with HDMI 2.0 standards for carrying HDR signals, which provide a wide range of vibrant colors with richer contrast, brighter whites and deeper blacks. HDCP 2.2 compliance allows you to

# Highlights

- Requires Tripp Lite B127-002-H or B127-004-H transmitter to extend HDMI signals
- Supports UHD resolutions up to 3840 x 2160 @ 60 Hz (4:4:4) for crystal-clear 4K video
- Power over Cable (PoC) technology provides power to the receiver via Cat6 cable
- Supports High Dynamic Range (HDR) for richer contrast and expanded color accuracy
- Plug-and-play operation with no software required for easy, immediate installation

# Applications

- Connect a media server, Blu-ray player, cable/satellite box, Roku, gaming system or other home theater component to largescreen 4K televisions or projectors
- Upgrade the video quality of your trade show presentation or digital signage installation in a commercial or educational setting to 4K x 2K
- Set up digital signage with a single video signal being transmitted to multiple displays

# System Requirements

- Tripp Lite B127-002-H or B127-004-H transmitter
- Display devices with HDMI input (HDTV, projector, monitor)

### **Package Includes**



stream iTunes and Netflix content with no complications. The B127-200-H also supports 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor.

### Plug-and-Play Operation for Quick Setup and Immediate Use

The receiver works right out of the box with no software required. Mounting hardware is included for installing it on a wall, pole or 19-inch rack. Connect the receiver to the display with a user-supplied high-speed HDMI cable (such as Tripp Lite's P568- or P569-Series) and to the transmitter with Cat6 Ethernet cable (such as Tripp Lite N202-Series cable).

## TAA-Compliant for GSA Schedule Purchases

The B127-200-H is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

# **Specifications**

OVERVIEW		
UPC Code	037332253866	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	Rx: x1 Green (Power) x2 Orange (Output) ; Rx RJ45 port: Green (Connected), Orange (Activity)	
PHYSICAL		
Color	Black	
Material of Construction	Metal	
Rackmountable	Yes	
Unit Dimensions (hwd / in.)	1.06 x 4.53 x 2.46	
Unit Packaging Type	Box	
Unit Weight (kg)	0.20	
Unit Weight (lbs.)	0.45	
ENVIRONMENTAL		
Operating Temperature Range	32 to 104°F (0 to 40°C)	
Storage Temperature Range	5 to 122°F (-15 to 50°C)	
Relative Humidity	0% to 85% RH, Non-Condensing	
COMMUNICATIONS		
Signal Range (ft.)	125	
Signal Range (m)	38	
CONNECTIONS		
Ports	2	
Side A - Connector 1	(2) HDMI (FEMALE)	

- B127-200-H 2-Port HDMI over
- Cat6 Active Remote Receiver
- Mounting hardware
- Owner's manual



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Side B - Connector 1	RJ45 (FEMALE)
FEATURES & SPECIFICATIONS	
Max Supported Video Resolution	4K x 2K (3840 x 2160) @60Hz
HDMI Specification	2.0
HDCP Specification	2.2
Audio Specification	True uncompressed 7.1 Channel, DTS-HD & Dolby-TrueHD digital audio
Driver Required	No
Recommended Category Cable	Solid Wire Cat6 Cables (Tripp Lite's N202-Series)
Max Supported Color Depth	24-bit True Color
EDID Compatible	Yes
Power Over Cable (PoC) Support	Yes
Technology	A/V over IP; Cat6; HDMI; HDR
Chroma Sub Sampling	4:4:4
SPECIAL FEATURES	
HDR Support	Yes
Wall Mountable	No
DIN Mountable	No
Integrated/Removable Cable	No
MST Support	No
Included Mounting Accessory	No
Multi-Resolution Support	No
CERTIFICATIONS	
Certifications	Tested to CE, FCC, REACH, RoHS
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies