

Technical Specifications

Galaxy VS UPS 30kW 208V for up to 5 internal 9Ah smart modular battery strings, Start-up 5x8 | GVSUPS30K0B5FS | Downloaded on 05/15/2020 (EST)



Galaxy VS UPS 30kW 208V for up to 5 internal 9Ah smart modular battery strings, Start-up 5x8

GVSUPS30K0B5FS

Call for More Information 800-800-4272

- Highly efficient, easy-to-deploy 30kW, 208V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. This UPS is for up to 5 smart modular high capacity battery strings, but is supplied without batteries, so you can easily customize the battery runtime. Includes 5x8 start-up service.
- Includes: Dust filter, EcoStruxure Ready, Installation Manual, Integrated network management, Start-up service

Output	
Output power capacity	30.0kWatts / 30.0kVA
Max Configurable Power (Watts)	30.0kWatts / 30.0kVA
Nominal Output Voltage	208V 3PH
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50 Hz, 60 Hz
Output Frequency (not synced)	50Hz +/-0.1% for 50Hz nominal, 60Hz +/-0.1% for 60Hz nominal
Other Output Voltages	200, 220
Load Crest Factor	2.5
Topology	Double Conversion Online
Waveform type	Sinewave
Overload Operation	150% for 1 minute 125% for 10 minutes
Output Voltage THD	<1% linear load and <5% non-linear load
Output Voltage Tolerance	+/-1% after 50ms
Bypass	Built-in Static Bypass

Input	
Nominal Input Voltage	208V 3PH
Input frequency	40 - 70Hz
Input voltage range for main operations	177 - 239 (208V)V
Input Total Harmonic Distortion	Less than 3% for full load

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Galaxy VS UPS 30kW 208V for up to 5 internal 9Ah smart modular battery strings, Start-up 5x8 | GVSUPS30K0B5FS | Downloaded on 05/15/2020 (EST)

Input	
Other Input Voltages	200, 220
Maximum Short Circuit Withstand (Icw)	65.0kAmps
Maximum Input Current	107.0A
Input Power Factor at Full Load	0.99

Batteries & Runtime	
Battery type	VRLA
Nominal Battery Voltage	480VDC
End of Discharge Maximum Battery Current	81.0A
End of Discharge Battery Voltage	384VDC
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Control panel	Touch Screen LCD User Interface
Audible Alarm	Audible and visible alarms prioritized by severity

Physical	
Maximum Height	78.0inches (1970MM, 197.0CM)
Maximum Width	22.0inches (550MM, 55.0CM)
Maximum Depth	34.0inches (847MM, 84.7CM)
Net Weight	551.16lbs. (250.0KG)
Shipping weight	552.0lbs. (250.0KG)
Shipping Height	82.0inches (2082MM, 208.2CM)
Shipping Width	30.0inches (755MM, 75.5CM)
Shipping Depth	40.0inches (1010MM, 101.0CM)
Color	Gloss level 85%, White

Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (non-condensing) %

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Galaxy VS UPS 30kW 208V for up to 5 internal 9Ah smart modular battery strings, Start-up 5x8 | GVSUPS30K0B5FS | Downloaded on 05/15/2020 (EST)

Environmental	
Operating Elevation	0-3300ftft (0-990meters)
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	10 - 80 (non-condensing) %
Storage Elevation	0-10 000ftft (0-3meters)
Audible noise at 1 meter from surface of unit	54.0dBA
Online thermal dissipation	6526.0BTU/hr
Protection Class	IP 20

Conformance	
Approvals	CSA C22.2 NO. 107.3, FCC Part 15 Class A, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, UL 1778 5th edition, OSHPD
Standard warranty	1 year on-site repair or replace with factory authorized Start-Up

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.