

# obusforme comfort seating | product specification

## Work Chairs and Stools

Models 1240-2, 1240-3, 1241-2, 1241-3, 1244-5, 1244-6, 1245-5, 1245-6, 1248-5, 1249-5, 1260-2, 1260-3, 1261-2, & 1261-3

### Work Chair Dimensions (Models 1240-2, 1240-3, 1241-2, 1241-3, 1244-5, 1244-6, 1245-5, 1245-6, 1260-2, 1260-3, 1261-2, & 1261-3)

Overall Depth		25 in / 635 mm
Overall Width	1240-#, 1241-#, 1244-#, 1260-#, & 1261-#	26 in / 660 mm
	1245-#	21 in / 533 mm
Overall Height	1240-2 & 1260-2	43.5-52.7 in / 1105-1340 mm
	1240-3 & 1260-3	43-52.2 in / 1092-1327 mm
	1241-2 & 1261-2	38.5-47.7 in / 978-1340 mm
	1241-3 & 1261-3	38-47.2 in / 965-1200 mm
	1244-5 & 1245-5	35.5-44.7 in / 902-1175 mm
	1244-6 & 1245-6	36.5-41.5 in / 927-1054 mm
Seat Depth	1240-2, 1241-2, 1260-2 & 1261-2	17.5-20 in / 445-508 mm
	1240-3, 1241-3, 1260-3 & 1261-3	17.5-20.5 in / 445-521 mm
	1244-5	17.5 in / 445 mm
	1244-6 & 1245-6	16.5-18 in / 419-457 mm
	1245-5	17.5 in / 445 mm
Seat Width		21 in / 533 mm
Seat Height	1240-2, 1241-2, 1244-5, 1245-5, 1260-2, & 1261-2	16.5-20.5 in / 419-521 mm
	1240-3, 1241-3, 1260-3, & 1261-3	16-20 in / 406-508 mm
	1244-6 & 1245-6	17-22 in / 432-559 mm
Back Height - From Seat	1240-# & 1260-#	27-32.2 in / 686-819 mm
	1241-# & 1261-#	22-27.2 in / 559-692 mm
	1244-5 & 1245-5	19-24.2 in / 483-616 mm
	1244-6 & 1245-6	19.5 in / 495 mm
Armrest Clearance	1240-#, 1241-#, 1244-#, 1260-# & 1261-#	18.5-23.5 in / 470-597 mm
	1245-#	no arms
Arm Height - From Seat	1240-#, 1241-#, 1244-#, 1260-# & 1261-#	7-10 in / 178-254 mm
	1245-#	no arms
Product Weight	1240-2, 1241-2, 1241-3, 1260-2, 1261-2 & 1261-3	58 lbs / 26.4 kgs
	1240-3 & 1260-3	60 lbs / 27.3 kgs
	1244-5	43 lbs / 19.5 kgs
	1244-6	38 lbs / 17.3 kgs
	1245-5	37 lbs / 16.8 kgs
	1245-6	32 lbs / 14.5 kgs
Shipping Cube		10.5-11 ft <sup>3</sup> / 0.30-0.31 m <sup>3</sup>

### Stool Dimensions (Models 1248-5 & 1249-5)

Overall Depth		25 in / 635 mm
Overall Width	1248-5	21 in / 533 mm
	1249-5	26 in / 660 mm
Overall Height		42.5-57.7 in / 1080-1466 mm
Seat Depth		17.5 in / 445 mm
Seat Width		21 in / 533 mm
Seat Height		23.5-33.5 in / 597-851 mm
Back Height - From Seat		19-24.2 in / 483-616 mm
Armrest Clearance	1248-5	no arms
	1249-5	18.5-23.5 in / 470-597 mm
Arm Height - From Seat	1248-5	no arms
	1249-5	7-10 in / 178-254 mm
Product Weight	1248-5	40 lbs / 18.2 kgs
	1249-5	45 lbs / 20.5 kgs
Shipping Cube		10.5 ft <sup>3</sup> / 0.30 m <sup>3</sup>

Contact sales representative for more information.

### Features

- Elastomeric back provides support without pressure points along spine  
MODELS 1260-2, 1260-3, 1261-2 & 1261-3
- Schukra mechanism provides lumbar depth adjustment  
MODELS #####-2
- Knee-tilter mechanism
- Infinite position tilt lock
- Adjustable tilt tension
- Sliding seat depth adjustment



1240-3



1249-5



# obusforme comfort seating | product specification

## MODELS #####-3

- Multi-tilter mechanism
- Infinitely adjustable back angle
- Infinitely adjustable seat depth and angle (forward and rearward incline)
- Adjustable tilt tension
- Sliding seat depth adjustment

## MODELS #####-5

- Operator mechanism allows seat/back angle adjustment
- Aluminum footring

## MODELS #####-6

- Task mechanism provides seat height and manual seat depth adjustment

### Options

- Petite seat models are available. Seat depth is reduced by 0.75 in (19 mm) and seat width is reduced by 1.5 in (38 mm)
  - Several arm options available
  - Standard seat foam may be replaced with memory foam
  - Base is standard in Black nylon. Also available in polished aluminium with Black end guards
  - Carpet casters are standard. Hard surface casters are available
  - Leather upholstery features additional stitch details
- MODELS 1240-3, 1241-3, 1260-3, & 1261-3
- Heavy duty 24 hour models with multi-tilter mechanism are available

### Construction (Arms)

- Locking, highly adjustable arm caps slide forward and backward with a 2 in (51 mm) range
- Arm caps slide inward, over seat, up to 0.75 in (19 mm) on each side
- Arm cap rotates inward and outward up to 30 degrees
- SSU arm caps
- Width adjustable arm extensions allow for arm spacing adjustments of up to 2 in (51 mm) on each side

### Construction (Seat)

- Blended recycled nylon/wood seat pan, 1 in (25 mm) thick, injection molded

### Construction (Back)

- Plywood back insert, 7/16 in (11 mm) thick, 7-ply
- Steel back upright

### Construction (Base)

- Injection molded nylon base; fiberglass reinforced
- 26.5 in (673 mm) diameter

## MODELS #####-5

- 20 in (508 mm) diameter aluminium footring

### Construction (Casters)

- 2 in (50 mm) hard (carpet) casters made of reinforced nylon
- Optional soft casters for hard floors are made of polyurethane coated nylon
- Dual wheel

### Construction (Mechanism)

- Constructed of cast aluminum and stamped steel
- Connected to gas-assisted pneumatic cylinder

### Upholstery (Seat)

- Seat can be upholstered in fabric, vinyl or leather
- Front edge of seat is a seamless waterfall

### Upholstery (Back)

- Can be upholstered in fabric, vinyl or leather

### Foam

- Seat foam is dual layer:
  - 1 in (25 mm) thick, Density: 1.8 lbs, ILD: 30
  - 1.5 in (38 mm) thick, Density: 1.8 lbs, ILD: 40
- Back foam is 1 in (25 mm) thick, Density: 1.5 lbs, ILD: 40

### Weight Capacity

Designed for an active weight capacity is 300 lbs.

### Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foams and fabrics
- 12 year warranty on control mechanisms

### Fire Rating

All fabric and foam is tested and certified, meeting California Technical Bulletin 117 (CAL 117) standards.

### Environmental

View [Environmental Data Sheets](#) online.

All foam is produced without using any ozone depleting chloro-flouro chemicals.

### Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

**Please visit [globalfurnituregroup.com](http://globalfurnituregroup.com) for additional product information including environmental certifications.**

