

ThinkStation P340 Tiny 30DF001VUS

Product
ThinkStation P340 Tiny

Region
NA

Country/Region
USA

Machine Type
30DF

TopSeller
TopSeller

Processor
Intel Core i9-10900T (10C / 20T, 1.9 / 4.6GHz, 20MB)

Integrated Graphics
Intel UHD Graphics 630

Chipset
Intel Q470 Chipset

Discrete Graphics
NVIDIA Quadro P620 2GB

Memory
1x 16GB SO-DIMM DDR4-2933 Non-ECC

M.2 SSD Drive
1x 512GB SSD M.2 PCIe NVMe Opal

Optical
None

Onboard Ethernet
1x GbE RJ-45

Additional Ethernet
None

WLAN + Bluetooth
Intel AX201 11ax, 2x2 + BT5.1

Optional Rear Ports
None

Dust Filter
None

Adapter Cage
None

Toolless Chassis Screw
Toolless Chassis Screw

Mounting
None

Color
Black

Stand
Floor Stand

Keyboard
USB Traditional Keyboard, Black, English

Mouse
USB Calliope Mouse

Power Supply
230W 89% Power Adapter

TUV Low Noise
None

System Management
Intel vPro with AMT 14

Operating System
Windows 10 Pro 64, English

Bundled Software
None

Base Warranty
3-year, Onsite

Bundled Service
3Y Premier Support Upgrade from 3Y Onsite (5WS0U26646)

EAN / UPC / JAN
195042929836

End of Support
2028-07-09

Announce Date
2020-06-30

Notes:

California Electronic Waste Recycling Fee

In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to: <https://www.calrecycle.ca.gov/Electronics/Consumer>

 WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.

<https://psref.lenovo.com>

Visit psref website for the latest version of Product specifications Reference.

© Lenovo, 2020. All rights reserved.



Components	Specification																																																																																																																																
Form factor	1L. Optional VESA mount bracket kit, supports VESA 75mm and 100mm. Optional floor stand for vertical orientation. Optional tool-less chassis open. Optional dust filter																																																																																																																																
Dimensions	Height: 179 mm (7.0 in). Width: 37 mm (1.5 in). Depth: 182.9 mm (7.2 in)																																																																																																																																
Weight	Maximum configuration: 3 lb (1.4kg)																																																																																																																																
Processor	<table border="1"> <thead> <tr> <th>Processor Number</th> <th>Cores</th> <th>Threads</th> <th>Base Frequency</th> <th>Cache</th> <th>TDP</th> <th>Memory Types</th> <th>vPro</th> </tr> </thead> <tbody> <tr><td>i9-10900T</td><td>10</td><td>20</td><td>1.9GHz</td><td>20MB</td><td>35W</td><td>DDR4-2933</td><td>Yes</td></tr> <tr><td>i9-10900</td><td>10</td><td>20</td><td>2.8GHz</td><td>20MB</td><td>65W</td><td>DDR4-2933</td><td>Yes</td></tr> <tr><td>i7-10700T</td><td>8</td><td>16</td><td>2.0GHz</td><td>16MB</td><td>35W</td><td>DDR4-2933</td><td>Yes</td></tr> <tr><td>i7-10700</td><td>8</td><td>16</td><td>2.9GHz</td><td>16MB</td><td>65W</td><td>DDR4-2933</td><td>Yes</td></tr> <tr><td>i5-10600T</td><td>6</td><td>12</td><td>2.4GHz</td><td>12MB</td><td>35W</td><td>DDR4-2666</td><td>Yes</td></tr> <tr><td>i5-10600</td><td>6</td><td>12</td><td>3.3GHz</td><td>12MB</td><td>65W</td><td>DDR4-2666</td><td>Yes</td></tr> <tr><td>i5-10500T</td><td>6</td><td>12</td><td>2.3GHz</td><td>12MB</td><td>35W</td><td>DDR4-2666</td><td>Yes</td></tr> <tr><td>i5-10500</td><td>6</td><td>12</td><td>3.1GHz</td><td>12MB</td><td>65W</td><td>DDR4-2666</td><td>Yes</td></tr> <tr><td>i5-10400T</td><td>6</td><td>12</td><td>2.0GHz</td><td>12MB</td><td>35W</td><td>DDR4-2666</td><td>No</td></tr> <tr><td>i5-10400</td><td>6</td><td>12</td><td>2.9GHz</td><td>12MB</td><td>65W</td><td>DDR4-2666</td><td>No</td></tr> <tr><td>i3-10320</td><td>4</td><td>8</td><td>3.8GHz</td><td>8MB</td><td>65W</td><td>DDR4-2666</td><td>No</td></tr> <tr><td>i3-10300T</td><td>4</td><td>8</td><td>3.0GHz</td><td>8MB</td><td>35W</td><td>DDR4-2666</td><td>No</td></tr> <tr><td>i3-10300</td><td>4</td><td>8</td><td>3.7GHz</td><td>8MB</td><td>65W</td><td>DDR4-2666</td><td>No</td></tr> <tr><td>i3-10100T</td><td>4</td><td>8</td><td>3.0GHz</td><td>6MB</td><td>35W</td><td>DDR4-2666</td><td>No</td></tr> <tr><td>i3-10100</td><td>4</td><td>8</td><td>3.6GHz</td><td>6MB</td><td>65W</td><td>DDR4-2666</td><td>No</td></tr> </tbody> </table>	Processor Number	Cores	Threads	Base Frequency	Cache	TDP	Memory Types	vPro	i9-10900T	10	20	1.9GHz	20MB	35W	DDR4-2933	Yes	i9-10900	10	20	2.8GHz	20MB	65W	DDR4-2933	Yes	i7-10700T	8	16	2.0GHz	16MB	35W	DDR4-2933	Yes	i7-10700	8	16	2.9GHz	16MB	65W	DDR4-2933	Yes	i5-10600T	6	12	2.4GHz	12MB	35W	DDR4-2666	Yes	i5-10600	6	12	3.3GHz	12MB	65W	DDR4-2666	Yes	i5-10500T	6	12	2.3GHz	12MB	35W	DDR4-2666	Yes	i5-10500	6	12	3.1GHz	12MB	65W	DDR4-2666	Yes	i5-10400T	6	12	2.0GHz	12MB	35W	DDR4-2666	No	i5-10400	6	12	2.9GHz	12MB	65W	DDR4-2666	No	i3-10320	4	8	3.8GHz	8MB	65W	DDR4-2666	No	i3-10300T	4	8	3.0GHz	8MB	35W	DDR4-2666	No	i3-10300	4	8	3.7GHz	8MB	65W	DDR4-2666	No	i3-10100T	4	8	3.0GHz	6MB	35W	DDR4-2666	No	i3-10100	4	8	3.6GHz	6MB	65W	DDR4-2666	No
Processor Number	Cores	Threads	Base Frequency	Cache	TDP	Memory Types	vPro																																																																																																																										
i9-10900T	10	20	1.9GHz	20MB	35W	DDR4-2933	Yes																																																																																																																										
i9-10900	10	20	2.8GHz	20MB	65W	DDR4-2933	Yes																																																																																																																										
i7-10700T	8	16	2.0GHz	16MB	35W	DDR4-2933	Yes																																																																																																																										
i7-10700	8	16	2.9GHz	16MB	65W	DDR4-2933	Yes																																																																																																																										
i5-10600T	6	12	2.4GHz	12MB	35W	DDR4-2666	Yes																																																																																																																										
i5-10600	6	12	3.3GHz	12MB	65W	DDR4-2666	Yes																																																																																																																										
i5-10500T	6	12	2.3GHz	12MB	35W	DDR4-2666	Yes																																																																																																																										
i5-10500	6	12	3.1GHz	12MB	65W	DDR4-2666	Yes																																																																																																																										
i5-10400T	6	12	2.0GHz	12MB	35W	DDR4-2666	No																																																																																																																										
i5-10400	6	12	2.9GHz	12MB	65W	DDR4-2666	No																																																																																																																										
i3-10320	4	8	3.8GHz	8MB	65W	DDR4-2666	No																																																																																																																										
i3-10300T	4	8	3.0GHz	8MB	35W	DDR4-2666	No																																																																																																																										
i3-10300	4	8	3.7GHz	8MB	65W	DDR4-2666	No																																																																																																																										
i3-10100T	4	8	3.0GHz	6MB	35W	DDR4-2666	No																																																																																																																										
i3-10100	4	8	3.6GHz	6MB	65W	DDR4-2666	No																																																																																																																										
Chipset	Intel Q470 Chipset																																																																																																																																
Memory Sockets	2 DIMM sockets																																																																																																																																
Memory Types	4GB/8GB/16GB/32GB DDR4-2933 SoDIMM non-ECC																																																																																																																																
Memory Capacity	64GB (2x 32GB)																																																																																																																																
Memory Protection	None																																																																																																																																
Expansion slots	One PCIe slot via specific riser card: PCIe 3.0 x16 (negotiable link width x8) and low profile for discrete graphics card; PCIe 3.0 x4 and low profile for ethernet adapter and Thunderbolt adapter																																																																																																																																
Processor graphics	Integrated Intel UHD Graphics 630. Works along with discrete graphics to support multi-display																																																																																																																																
Discrete Graphics Offering	<table border="1"> <thead> <tr> <th>Graphics</th> <th>Memory</th> <th>Power</th> <th>Connector</th> <th>Max Qty</th> </tr> </thead> <tbody> <tr><td>Quadro P620</td><td>2GB GDDR5</td><td>40W</td><td>4x miniDP</td><td>1</td></tr> <tr><td>Quadro P1000</td><td>4GB GDDR5</td><td>50W</td><td>4x miniDP</td><td>1</td></tr> </tbody> </table>	Graphics	Memory	Power	Connector	Max Qty	Quadro P620	2GB GDDR5	40W	4x miniDP	1	Quadro P1000	4GB GDDR5	50W	4x miniDP	1																																																																																																																	
Graphics	Memory	Power	Connector	Max Qty																																																																																																																													
Quadro P620	2GB GDDR5	40W	4x miniDP	1																																																																																																																													
Quadro P1000	4GB GDDR5	50W	4x miniDP	1																																																																																																																													
Storage Controller	Supports M.2 SSD RAID 0 / 1, for special bids only																																																																																																																																
Storage Support	<table border="1"> <thead> <tr> <th>Disk Type</th> <th>Interface</th> <th>RPM</th> <th>Offering</th> <th>Max Qty</th> </tr> </thead> <tbody> <tr><td>M.2 PCIe SSD</td><td>PCIe NVMe</td><td>-</td><td>256GB/512GB/1TB/2T</td><td>2</td></tr> </tbody> </table>	Disk Type	Interface	RPM	Offering	Max Qty	M.2 PCIe SSD	PCIe NVMe	-	256GB/512GB/1TB/2T	2																																																																																																																						
Disk Type	Interface	RPM	Offering	Max Qty																																																																																																																													
M.2 PCIe SSD	PCIe NVMe	-	256GB/512GB/1TB/2T	2																																																																																																																													
Storage Bays	Two M.2 slots for M.2 SSD																																																																																																																																
Media reader	None																																																																																																																																
Network interfaces	One onboard GbE port via integrated gigabit ethernet Intel i219LM, supports Wake-on-LAN. Optional PCIe ethernet adapters are available																																																																																																																																

Components	Specification
WLAN + Bluetooth	One dedicated M.2 slot for optional Wi-Fi card, supports one of the following: <ul style="list-style-type: none">Intel Wi-Fi 6 AX201, 2x2, 2.4GHz/5GHz (160MHz channels), WiFi 6, Bluetooth 5Intel Wireless-AC 9560, 2x2, 2.4GHz/5GHz (160MHz channels), 802.11ac, Bluetooth 5Realtek 8822CE, 2x2, 2.4GHz/5GHz, 802.11ac, Bluetooth 5
Security features	Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant. Chassis intrusion switch. Kensington slot
Intel vPro	Supports vPro on models with the vPro enable processors vPro also requires Wi-Fi 6 AX201 if WiFi is needed
Systems management	Intel Active Management Technology 14 on vPro models, Intel Standard Manageability on other models
Base warranty	Most models comes with 3-year limited onsite service with 9x5/NBD. Other models may have 1 or 2-year limited onsite service
HD Audio	Intel HD Audio interface with Realtek ALC233 Codec
Optical	Optional one 9.0mm optical drive via optical drive kit, DVD-ROM or DVD±RW.
Front standard ports	1x USB-A 3.2 Gen 2 (charging). 1x USB-C 3.2 Gen 1. 1x Combo jack
Rear standard ports	2x USB-A 3.2 Gen 2, 2x USB-A 3.2 Gen 1 (one supports smart power-on), 1x RJ-45, 1x DP, 1x HDMI, 1x security-lock slot, Wi-Fi antenna slot
Optional rear ports	Reserved area for two optional ports. Ports 1 supports one of the following: <ul style="list-style-type: none">1x USB-C, also supports DP function1x COM1x VGA1x DP1x HDMI Port 2 supports 2nd COM. Also supports optional Thunderbolt or 2x USB-A 3.2 Gen 1
Temperature	Operating: 50 °F to 95 °F (10 °C to 35 °C) Non operating (no package): 14 °F to 140 °F (-10 °C to 60 °C) Non operating (with package): -40 °F to 140 °F (-40 °C to 60 °C)
Altitude	Operating: -15.2 m (-50 ft) to 3048 m (10 000 ft). Storage: -15.2 m (-50 ft) to 10, 668 m (35 000 ft)
Humidity	Operating: 20%~80%, non-condensing Storage (with package): 20%~90%, non-condensing
MIL-SPEC	Certified
Environmental certification	RoHS-compliant. GREENGUARD. EPEAT Silver rating and ENERGY STAR 8 qualified
Power supply	<ul style="list-style-type: none">170W power adapter, 100V - 240V, 89% PSU230W power adapter, 100V - 240V, 89% PSU
ISV certifications	Please visit www.thinkworkstations.com/isv-certifications/

ThinkStation P340 Tiny

Lenovo

