

# DEX-BLE 10

## Wireless Adapter

TDEX/UCS is used by consumer goods suppliers and retailers to speed up direct store delivery (DSD) receiving check-in time and payment, while ensuring the accuracy of delivery data. Traditional DEX cables can be easily broken, inconvenient to carry and typically limited to a single mobile computer model.

With the Honeywell DEX Wireless Adapter, users can deploy a cost effective, versatile, maintenance-free DEX solution for DSD operations. The DEX Adapter is designed with simplicity, reliability and ease of use. Unlike other alternatives, the DEX-BLE-10 has a rechargeable, replaceable battery that goes weeks between charges and has a simple, intuitive user interface that includes on/off buttons, easy-to-understand LED status indicators and simple NFC-based pairing. The DEX Wireless Adapter supports Honeywell devices on Android™ 7.1 and higher.

The DEX solution is part of the Mobility Edge™ platform ecosystem that includes the DEX Adapter, DEX BLE SDK, DEX Toolkit (SKU 454-038-001), DEX Storefront application (SKU 454-036-001) and DEX-enabled DSD applications available from Honeywell partners.

Built on the Mobility Edge platform, the device offers many benefits as its unique software plus hardware system-on-module platform, providing unmatched security, lifecycle, productivity and accelerated deployment. For more information about Mobility Edge visit [www.honeywellaidc.com/solutions/platforms/mobility-edge](http://www.honeywellaidc.com/solutions/platforms/mobility-edge).



The Honeywell DEX Wireless Adapter has a simple, intuitive user interface for reliability and ease of use.

## FEATURES AND BENEFITS



Bluetooth® 4.0 (Bluetooth Smart) connection to mobile computers. Easy to set up with fast, fool-proof NFC and barcode scan pairing.



Enterprises can take advantage of flexible support for Android 7.1 and later versions.



Withstands multiple 1.2 m (4 ft) drops to concrete, 500 1 m (3.3 ft) tumbles and has an IP64 seal rating.



Rechargeable and removable Lithium-ion battery lasts one month between charges at 16 data transmissions per day.



Users can view battery status and other device operations through APIs.

# DEX-BLE-10 Wireless Adapter Technical Specifications

## MECHANICAL

**Dimensions:** 162 mm x 77 mm x 18.2 mm (6.4 in x 3.0 in x 0.7 in)

**Weight:** 289 g (10.1 oz) with battery pack

## ENVIRONMENTAL

### Operating Temperature:

**Charging:** 5°C to 40°C (41°F to 104°F)

**Non-charging:** -20°C to 50°C (-4°F to 122°F)

**Drop:** Withstands multiple 1.2 m (4 ft) drops to concrete

**Tumble:** 500 1 m (3.3 ft) tumbles

**ESD:** ± 20 kV air and ± 10 kV contact

**Environmental Sealing:** IP64 (IEC 60529)

## SYSTEM ARCHITECTURE

**Operating System:** Works with Honeywell mobile computers with Android 7.1 and higher

### DSD Application Software:

DEX BLE SDK

DEX Toolkit (SKU 454-038-001)

DEX Storefront application (SKU 454-036-001)

DEX-enabled DSD applications available from Honeywell partners

**Keypad:** Power button to power on/off the DEX adapter

### I/O Ports:

6.35 mm (0.25 in), 3-circuit

DEX plug communicating per DEX/

UCS communications standard – direct connect interface, revision 01

Micro USB charging port

**LED Indicator:** Product function indication device status LED and battery status LED

### Device Status (Blue LED):

BTLE discoverable, not paired (LED on)

BTLE connecting (fast flash)

BTLE connected (slow flash)

### Battery Status (Green LED):

Low or charging (flashing)

Fully charged (LED on)

### Battery:

**Rechargeable/Removeable:** Li-ion 3.7 V, 750 mAh, less than four hours to charge from completely drained

**Expected Hours of Operation:** One month between charges at 16 data transmissions per day

**Warranty:** 1-year factory warranty

## WIRELESS CONNECTIVITY

**Bluetooth:** Supports V4.0 Bluetooth Smart applications

**NFC:** Integrated NFC tag with NFC Data Exchange Format (NDEF) described in NFCForum-TS-NDEF\_1.0 Technical Specification by NFC Forum

## ACCESSORIES

**Battery:** DEX-10-BATTERY

**Charger:** USBWALL-CHARGER-U

**Cable:** CBL-500-120-S00-04

For a complete listing of all compliance approvals and certifications, please visit [www.honeywellaidc.com/compliance](http://www.honeywellaidc.com/compliance).

For a complete listing of all supported barcode symbologies, please visit [www.honeywellaidc.com/symbologies](http://www.honeywellaidc.com/symbologies).

Android is a trademark or registered trademark of Google LLC.

Bluetooth is a trademark or registered trademark of Bluetooth SG, Inc.

Mobility Edge is a trademark or registered trademark of Honeywell International Inc.

All other trademarks are the property of their respective owners.

## For more information

[www.honeywellaidc.com](http://www.honeywellaidc.com)

## Honeywell Safety and Productivity Solutions

300 S Tryon St Suite 500

Charlotte, NC 28202

800-582-4263

[www.honeywell.com](http://www.honeywell.com)