

# 4MP H.265 IP Turret Camera with Advanced Analytics

# **O4T7**

### 2.8mm fixed lens, white housing

#### **Features**

- Supports up to 4MP @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True Day/Night operation (IR cut filter)
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 98' (depending on scene reflection) 5 year warranty

### **Camera Specifications**

- Micro SD slot up to 128GB (card not included)
- True WDR (wide dynamic range) operation
- IP67 compliant, weather resistant
- Junction box included
- Conformant with ONVIF Profile T



**4** WDR (\*) MP WDR (\*) NIGHT (\*) NIGHT (\*) ANAUTICS POE SLOT (\*)

Camera Specific	ations	
Image Sensor		Progressive scan 1/3" CMOS, 4MP
Maximum Resolution		2592 x 1520
Field of View (H)		100.4°
Minimum Illumination		0.005 lux @ F1.6, AGC ON, 0 lux (IR LED on)
Day/Night		Smart IR
White Balance		Auto, Indoor, Outdoor, Manual
Compensation Electronic Shutter Speed		True WDR (120dB), BLC, HLC
		1/30 - 1/100000 sec.
DNR		3D DNR
Video Specificat	ions	
Main Resolution		520 / 2560x1440 / 2304x1296 / 080 / 1280x720 @ 30fps

	1980x1080 / 1280x/20 @ 30fps
Compression	H.265, H.264 (HP/MP/BP), MJPEG
Video Settings	Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Day/Night mode, Infrared settings, Exposure, Gain, Corridor Pattern, Image flip/mirror
Bitrate Control	VBR, CBR (64Kbps ~ 8Mbps)
Multiple Streaming	3 streams

UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP,

User ID & Password protection, IP/Mac address filtering, digest authentication Max. 10 simultaneous users, Actual number of users may vary depending

	Audio Specifications				
	Audio Codec		G.711A / G.711U		
	Interfaces				
	Ethernet		10/100 Mbps		
	Power		DC jack		
	Microphone Input		Mono 3.5mm + built-in mic		
	Audio Output		No		
	Card Slot		MicroSD, up to 128GB (not included)		
	Alarm		No		
	Reset		Yes		
	System Specifications				
	PoE	Standard (IEEE 802.3af)			
	Analytics	Motion, missing object, abandoned object, intrusion, vehicle, human, tampering, scene change, and face detection			
	Alarm Triggers	Analytics, SD card error			
	Alarm Events	FTP upload, email upload			
	Image Settings	Watermark, IP address filtering, video mask, password protection			
	Operating & Unit Specifications				
	Power		PoE, 12VDC (power supply not included)		
	Power Consumption		<7.5W		
	Operating Temperature		-40°F ~ 140°F		

	rower	FOL, 12 VDC (power supply not included)
	Power Consumption	< 7.5W
	Operating Temperature	-40°F ~ 140°F
	Operating Humidity	Less than 95 % (non-condensing)
	Unit Dimensions	3.7" (φ) × 3.25" (H)
	Unit Weight	1 lb.
	Certifications	FCC, RoHS

Web Browser Support	Windows (Internet Explorer 8 and up)
PC Application	SecureGuard® VMS, SecureGuard® CMS
Mobile	SecureGuard^ Client, Speco Blue (iPhone $^{\circ}$ and Android $^{\scriptscriptstyle{\rm M}}$ )

## Other Platforms Apple TV, Amazon Fire TV

**Network Specifications** 

**Client Specifications** 

HTTP. HTTPS

on bandwidth

Speco DDNS (free of charge)

Protocols

Security

User Access

**DDNS** support



ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 8/3/20

Apps available from the follow

App Store

amazon appstore Onvir 800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

## speco technologies