# **Product data sheet**



APC NetShelter Rack PDU Advanced, Switched, 3Phase, 17.3kW, 208V 60A, 42 Outlets, 460P9

APDU10452SW

### Overview

Lead time Usually in Stock

#### Main

| Color                     | Black          |
|---------------------------|----------------|
| Product or Component Type | PDU            |
| PDU Type                  | Switched       |
| Cord length               | 5.9 ft (1.8 m) |

## Complementary

| Input Voltage               | 208 V 3 phase                   |  |
|-----------------------------|---------------------------------|--|
| Height                      | 71.9 in (182.6 cm)              |  |
| Width                       | 2.2 in (5.6 cm)                 |  |
| Output Voltage              | 208 V                           |  |
| Depth                       | 3.0 in (7.5 cm)                 |  |
| Net Weight                  | 24.5 lb(US) (11.1 kg)           |  |
| Mounting Location           | Side                            |  |
| Mounting preference         | No preference                   |  |
| Input Plug Type             | IEC 60309 60 A 3P+PE            |  |
| Mounting Mode               | Rack-mounted                    |  |
| Rack units                  | 0U                              |  |
| Mounting position           | Vertical                        |  |
| Communication Port Protocol | 1000BASE-T<br>10/100BASE-T      |  |
| Line Rated Current          | 48 A                            |  |
| Acceptable Input Voltage    | 200240 V                        |  |
| Input current limits        | 60 A                            |  |
| Load Capacity               | 17300 VA                        |  |
| Input Frequency             | 50/60 Hz                        |  |
| Outlet type and quantity    | 21 C13/C15/C19/C21<br>21C13/C15 |  |

#### **Environment**

**Product Certifications** TAA compliance

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Standards                             | UL 62368-1<br>CSA C22.2 No 62368-1<br>FCC part 15 Subpart B |  |
|---------------------------------------|---|--|
| IP Degree of Protection               | IP44  |  |
| Ambient Air Temperature for Operation | 23140 °F (-560 °C)  |  |
| Relative Humidity                     | 595 %   |  |
| Operating altitude                    | 010000 ft   |  |
| Ambient Air Temperature for Storage   | -13149 °F (-2565 °C)  |  |
| Storage Relative Humidity             | 595 %   |  |
| Storage altitude                      | 050000 ft (0.000000000015240.0000000000 m)                  |  |

## Ordering and shipping details

| GTIN              | 731304439868 |
|-------------------|--------------|
| Country of origin | US           |

## **Packing Units**

| Unit Type of Package 1       | PCE                    |
|------------------------------|------------------------|
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 78.0 in (198 cm)       |
| Package 1 Width              | 5.2 in (13.2 cm)       |
| Package 1 Length             | 10.3 in (26.2 cm)      |
| Package 1 Weight             | 31.09 lb(US) (14.1 kg) |

## **Contractual warranty**

Warranty 3 years repair or replace



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

### **Certifications & Standards**

| Reach Regulation         | REACh Declaration  |
|--------------------------|--|
| Eu Rohs Directive        | Compliant EU RoHS Declaration  |
| China Rohs Regulation    | China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)                                    |
| Environmental Disclosure | Product Environmental Profile  |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile      | End of Life Information  |