

Ultra High Bright SSL Laser projector delivering 22,000 lumens, rich connectivity, edge-blending, and very low maintenance operating time

Features

- Bright 22,000 ANSI lumens with a native WUXGA (1920 x 1200) resolution for impeccable colors and outstanding details
- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels and vibrant, colorful images
- Solid-state, laser-phosphor light source for reliable projection and performance
- Environmentally friendly lamp-less design that is mercury-free and energy efficient
- Almost maintenance-free with up to 20,000 hours of operating time
- Advanced video processor for fluid video streaming and 10-bit programmable RGB color adjustments
- Laser light source produces rich colors for an incredible cinematic experience
- Fine tune and optimize an image with advanced calibrations, including gamma and color management settings
- Built-in hardware edge blending and warping functionality
- Powered zoom, focus and lens shift (horizontal/vertical) for easy adjustment and positioning flexibility
- Picture-in-Picture (PIP) for simultaneous image projection from two active sources
- Full suite of display connectivity inputs and outputs including: HDMI v1.4, DVI-D, Component (5 BNC), VGA-In, 3G-SDI-In/Out, VGA-Out, HDBaseT™
- HDBaseT™ interface with support for distribution of digital video content over standard CAT5e/6 LAN cable
- Portrait mode projection allows the projector to be easily setup and installed in a 90° installation
- 360° operation and projection design for set up in all angles
- Instantaneous power-on & off, so no need for system pre-heating and postcooling
- Airtight sealed engine and filter-less design for improved performance against dust and fibers
- Frame sequential and dual channel 3D supported
- Complete range of motorized interchangeable lens in sizes from 0.9 to 7:1 (optional)
- Optimized system layout with high efficiency cooling system
- Heavy duty steel chassis for extra strength and integrity
- 24/7 continuous operation with no downtime
- Network ready for integration and system administration via RJ45

Photo



Specifications	
Display Type	Single Chip 0.96" DLP Technology by TI
Brightness	22,000 ANSI Lumen ¹ Note: 200-240V is required for full output (NEMA 6-15)
Native Resolution	WUXGA (1920 x 1200), 16:10 format
Contrast Ratio	10,000:1 or 30,000:1 (with DB On)
Laser Life/Type	20,000 + hours (Laser Phosphor Light Engine)
Aspect Ratio	16:10 Native
Image Size (Diagonal)*	40" – 500" (See page 2 for specification)
Keystone Correction	Vertical ±40°, Horizontal ±60° (Adjustable Range of single direction)
Horizontal Frequency	15, 31 - 90Hz
Vertical Scan Rate	24 - 30Hz, 47 - 85Hz
Projector Lens *	5 lens options (See page 2 for specification)
Lens Shift Range *	Vertical: ±50%, Horizontal: ±15%
Offset*	Motorize Lens Shift (See page 2 for specification)
Edge Blending	Yes (Built-In)
Warping	Yes (Built-In)
Computer Compatibility	VGA, SVGA, XGA, WXGA, SXGA, SXGA+, UXGA, 1080P, WUXGA@60hz, Mac
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i, 1080p)
I/O Connection Ports	HDMI v1.4 (x2), HDCP v1.4 Compliant
	HDBaseT™ / LAN Control (Shared) RJ45
	DVI-D Component/RGBHV (5 BNC)
	3G-SDI-In/Out RS-232-In/Out (DB-9)
	VGA-In/Out Wire Remote (3.5mm Jack)
	3D Sync IN/Out 12V Trigger (x2) (3.5mm Jack)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Anti-Theft Lens Screw
Dimensions (WxDxH)	26.8" x 20.8" x 9.7" (681x 530 x 248mm)
Weight	115lbs (52.3Kg)
Available ID Colors	Black (DU9900Z-BK)
Noise Level	45dB / 39dB (Eco Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	Normal Mode 2,100 Watts 100V- 240V@100Vac
	Network Standby Less than 6W
	Eco Standby Less than 0.5W
Environment Condition	Operating 0° to 40°C, (0 to 104°F), humidity 10 to 85% non-condensation
	Storage -10° to 60°C (14 - 140°F), humidity 5 - 95% non-condensation
Standard Accessories	AC Power Cord, Remote Control, Lens Cap, Anti-Theft Lens Screws, Documentation Kit
Optional Accessories	Interchangeable Lens Options (x5)
UPC Code (Projector)	813097025289

¹Brightness specification is based on 240V AC

Vivitek™, Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



DU9900Z Series Projector Lenses

High-performance lenses for large venue installations

Features

- Five high-performance lenses designed for a variety of large venue applications
- Wide throw ratio range starting from 0.9 up to a maximum 7.0:1 (Depends on resolution)
- Available in a variety of zoom ratios including 1.3x, 1.33x, 1.67x, 1.75x and 2.0x
- Simple lens insertion and removal
- Support for powered zoom, focus and lens shift features for easy adjustment and movement
- Light weight, yet heavy duty construction
- Sealed structure for dust and moisture resistance
- Compatible with Vivitek DU9800Z projector

Specifications

Image					
Model Number	D98-0912	D98-1215	D98-1520	D98-2040	D98-4070
Part Number	3797976800-SVK	3797859900-SVK	3797886100-SVK	3797893200-SVK	3797858100-SB
Lens Type	Ultra-Wide Angle Lens	Short Throw Lens	Standard Lens	Long Throw Lens	Ultra-Long Throw Lens
Throw Ratio	0.9 - 1.2:1	1.2 - 1.56:1	1.5 - 2.0:1	2.0 - 4.0:1	4.0 - 7.0:1
Zoom Ratio	1.33x	1.3x	1.33x	2.0x	1.75x
fValue (Focal Length)	19.34 – 25.76mm	25.69mm - 33.22mm	31.9mm - 42.2mm	42.6mm – 84.8mm	83.93mm - 146.85mm
F Number	2.2 – 2.53	2.18 - 2.66	2.17 – 2.65	2.17 - 2.64	2.2 - 2.57
Image Size (Diagonal)	50" – 500"	40" – 500"	40" – 500"	40" – 500"	40" – 500"
Projection Distance (Approximate)	0.92 -13.46m	0.95 – 17.47m	1.24 – 21.84m	2.65 - 41.77m	4.38 – 74.51m
Lens Shift Range	Vertical: ±45%, Horizontal: ±15%	Vertical: ±50% Horizontal: ±15%	Vertical: ±50%, Horizontal: ±15%	Vertical: ±50%, Horizontal: ±15%	Vertical: ±50%, Horizontal: ±15%
Focus/Zoom Adjustment	Motorized	Motorized	Motorized	Motorized	Motorized
Available Color	Black	Black	Black	Black	Black
Accessories	Lens Hood, Cap	Lens Hood, Cap	Lens Hood, Cap	Lens Hood, Cap	Lens Hood, Cap
Dimensions (Diameter x Length)	136 x 298.7mm (5.4"x 11.8")	120 x 228.5mm (4.7" x 9")	92 x 217.92mm (4.7" x 8.6")	112 x 251mm (3.7" x 9.88")	77 x 247mm (3.0" x 9.7")
Weight	2,676g (5.9lbs)	2,010g (4.43lbs)	2,010g (4.43lbs)	2,663g (5.87lbs)	1,930g (4.25lbs)

©2020 VIVITEK. VIVITEK IS A TRADEMARK OF DELTA ELECTRONICS, INC., OTHER TRADEMARKS ARE THE PROPERTIES OF THEIR RESPECTIVE OWNERS. VALUES, WEIGHTS AND DIMENSIONS SHOWN ARE APPROXIMATE. ERRORS AND OMISSIONS ACCEPTED