



EWS7952FP-FIT



# EnGenius Fit Layer 2 Plus Managed EWS7952FP-FIT 48-Port Gigabit PoE+ Switch with 740W Budget, 4 SFP Uplink Ports

Simple • Secure • Smart



The EnGenius Fit Managed Switch EWS7952FP-FIT is a 48-port Gigabit PoE+ Layer 2 plus switch with a 740W PoE budget and 4 SFP uplink ports.

Manage your network onsite or on-the-go through our **FitXpress** cloud-based mobile app or web portal. Additionally, **FitController** gives you greater control of your network using plug-n-play hardware with embedded network management software. Admins can easily view detailed analytics from a single pane of glass as well as monitor and troubleshoot issues instantly. With its business-class features, the EnGenius Fit managed switch provides secure, reliable, and high-performance switching while reducing capital and operating expenses for cost-conscious small businesses.

## Features & Benefits

- 48 10/100/1000 Base-T GbE Ports.
- Full-featured Layer 2 plus switching.
- 802.3af/at PoE ready on all ports with 740W PoE budget.
- 104 Gbps switching capacity.
- Setup in minutes with app-based step by step instructions.
- Quick-scan device register, remote monitoring and troubleshooting.
- Real-time system metrics, analytics and remote configurations.
- Manage your network onsite or on-the-go through our **FitXpress** cloud-based mobile app or web portal.
- **FitController** gives you greater control of your network using plug-n-play hardware with embedded network management software.
- Monitor a site or multiple sites with no recurring cost or licensing fee.
- Security - access control list/port security; 802.1x authentication.
- IGMP & MLD snooping provides advanced multicast filtering & network efficiency.
- 802.3ad Link Aggregation (LACP), Spanning Tree (STP), Rapid Spanning Tree (RSTP) & Multiple Spanning Tree (MSTP).
- Voice VLAN for fast, reliable deployment of VoIP services.
- Advanced QoS with IPv4/IPv6 ingress traffic filtering (ACLs) & prioritization.
- Standards-based technology ensures interoperability with existing standards-based network devices.
- Dual firmware images improve reliability & network uptime.

# Technical Specifications

## EWS7952FP-FIT

### Port Standards

802.3 10Base-T Ethernet

802.3u 100Base-TX Ethernet

802.3ab 1000Base-T Ethernet

802.3x Full-Duplex Flow Control

### Network Ports

48 10/100/1000 Mbps Ports

4 10/100/1000 Mbps SFP Ports

### Switching Capacity

104Gbps

### PoE Capable Ports

1-48 (802.3af/at)

All Gigabit Ethernet ports can output up to 30 Watts

### Total PoE Budget

740W

### SDRAM

256MB

### Flash Memory

32MB

### Packet Buffer Memory

1.5MB

### Address Database Size

8,000 MAC Addresses

## PHYSICAL INTERFACE

### LED Indicators

Power LED

Fault LED

PoE Max LED

LAN Mode LED

PoE Mode LED

### Ports

Link/Activity/Speed (per Ethernet port)

Link/Activity/Speed (per SFP slot)

### SFP Ports

Link/Act LED

### Reset Button

## SOFTWARE FEATURES

### Multiple IP Interface

20 IPv6 address

### ARP Table

Max. 192 ARP entries

Static ARP

Static 192 ARP entries

### IPv4 Static Route

Max. 59 entries

### IPv6 Static Route

Max. 5 entries

## SOFTWARE FEATURES (L2 FEATURE)

### MAC Address Table

8K

### Jumbo Frame

9K

### Multicast Group

Max 256 groups

### Port Security

Max. 256 Entries

### SSL Certificate

Certificate/Key Update

### L2 Features

802.1Q VLAN tagging

VLAN Table

Port-based VLAN

Voice VLAN

GARP VLAN Registration Protocol

802.1d Spanning tree:

RSTP

CIST

MSTP

802.3ad Link Aggregation

Loopback Detection

### L3 Feature

IGMP Snooping

MLD Snooping

DHCP Snooping

DHCP Relay

Static Route

### Port Settings

Multicast Filtering

EEE

Port Isolation

Port Mirror

Jumbo Frames

LLDP

---

## Security

---

802.1X Radius Authentication Protocol

---

Access:

---

Web:

HTTP Service  
HTTPs Service

---

Command Line Interface (CLI):

Telnet Service  
SSH Service

---

## Port Security

---

Radius Server

---

DoS Prevention

---

System Settings

---

IP Settings:

IPv4 Management  
IPv6 Management  
IPv4 Network

---

ARP Table

---

ARP Statistics

---

Simple Network Time Protocol (SNTP)

---

## Analyze

---

Log:

Local Logging  
Remote Logging

---

## Diagnostic

---

Cable Diagnostics

---

Ping Test

---

IPv6 Ping Test

---

Trace Route

---

Connection Diagnostic

---

## Access Control List (ACL)

---

MAC Based ACL

---

MAC ACE

---

IPv4 ACL

---

IPv4 ACE

---

IPv6 ACL

---

IPv6 ACE

---

ACL (Port) Binding

---

## SNMP

---

SNMP v1/v2c/v3 Support

---

## RMON

---

RMON 1,2,3,9

---

## QoS

---

CoS Mapping

---

DSCP Mapping

---

Port CoS

---

Bandwidth Control

---

Storm control

---

Advanced Mode:

Class Mapping

---

---

## MIB/RFC Standards

---

RFC1213

---

RFC1493

---

RFC1757

---

RFC2674

---

RFC2863

---

## ENVIRONMENT & MECHANICAL

---

### Temperature Range

---

Operating: 32 to 122°F/0 to 50°C

Storage: -40 to 158°F/-40 to 70 °C

---

### Humidity (Non-Condensing)

---

5% - 95%

---

## DIMENSIONS & WEIGHTS

---

### Device

---

Weight: 14.15 lbs. (6.41kg)

---

Width: 17.32" (440 mm)

---

Length: 12.20" (310 mm)

---

Height: 1.73" (44 mm)

---

### Packaging

---

Weight: 17.28 lbs. (7.83 kg)

---

Width: 21.57" (548 mm)

---

Length: 16.88" (429 mm)

---

Height: 4.13" (105 mm)

---

### Package Contents

---

1x Fit L2+ Managed 48 Ports EWS7952FP-FIT PoE+ Gigabit Switch

---

1 x Power Cord

---

1 x RJ45 Console Cable

---

1 x Rack Mount Kit

---

Quick Start Guide QR Code

---

FitXpress Cloud-Based Mobile App QR Code

---

### Certifications

---

CE, FCC, IC

---

### Warranty

---

1 Year

---

# Product Images

