



# **HSM SECURIO B35 - 1/4"**


## **HSM SECURIO B35 document shredder**

For more data security in the workplace. The excellent document shredder with an intake width of 400 mm for professional data destruction in an open-plan office for up to eight people.

# **Technical data**

Order number:	1921113	Intake width:	15.75"
EAN	4026631047333	Container volume /	34.3 gal
Cutting type:	strip cut	collecting:	
Cutting size:	1/4"	Collection volume in sheets (80 g):	855
Security level (DIN 66399):	E-2 O-2 P-2 T-2	Noise level (idle operation):	ca. 56 dB(A)
Cutting capacity in sheets 80g/m²:	35 - 37	Width x Depth x Height:	24.41" x 20.67" x 34.25"
•		Weight:	106.04 lb
Power consumption:	700 W		D 6: 1
Voltage / Frequency:	110-120 V / 60 Hz	Shredder material:	Paper, Staples and paper clips, Credit card, CD/DVD

# **Product information**



The induction-hardened, solid steel cutting rollers guarantee durability.



Reusable cardboard box as bin for shredded material.



The full bin is indicated via the display and the machine switches off automatically.





#### For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



#### **Energy-saving**

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



## High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



### **Automatic start/stop**

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



## Anti-paper jam function

The paper feed with overload protection reduces paper jams and sustains the high throughput of paper.



## **Convenient emptying**

Robust wooden cabinet with castors. After opening the door, the reusable collecting bag can be easily removed and emptied.















Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).









