



Powering Business Worldwide

Eaton Internal Replacement Battery Cartridge (RBC) for Select 1500VA UPS Systems

MODEL NUMBER: 744-A4801



UPS backup battery cartridge replaces the expired or aging internal battery in your Eaton 5PX G2 UPS system.

Features

UPS Replacement Battery Cartridge for Select Eaton 5PX G2 UPS Systems

This UPS backup battery replacement is compatible with Eaton's 1500VA 5PX G2 UPS systems along with Eaton Tripp Lite series SmartPro 1.44kVA & 1.5kVA UPS systems. Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime.

Comes Pre-Wired for Quick, Easy Installation

The sealed lead acid (SLA) 744-A4801 internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 744-A4801 has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your 1500VA 5PX G2 or Eaton Tripp Lite series SmartPro UPS system.

Specifications

OVERVIEW	
UPC Code	037332282316
INPUT	
Input Phase	Single-Phase
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)
Battery Replacement Description	Re-use existing wiring harness

Highlights

- Replacement battery backup for Eaton 1500VA 5PX G2 UPS systems and select Tripp Lite Series SmartPro 1.44kVA and 1.5kVA models
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery cartridge requires no regular maintenance
- Ships pre-wired and ready for immediate installation to prevent downtime

System Requirements

- Compatible with Eaton's 5PX1500RTNG2 and 5PX1500HRTG2 (5PX G2) UPS systems
- Also compatible with Tripp Lite series SmartPro SMART1500RMXL2U, SMART1500RMXLN, SMX1500XLRT2U, SMX1500XLRT2UN (SmartPro RM G2) UPS systems

Package Includes

744-A4801 Internal Replacement Battery Cartridge



Powering Business Worldwide

Hot Swap Battery	Yes
PHYSICAL	
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000
Unit Weight (lbs.)	5.44
Unit Weight (kg)	2.47
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
APPLICATIONS	
Used With	5PX1500RTG2, 5PX1500RTNG2, 5PX1500HRTG2, SMART1500RMXL2U, SMART1500RMXLN, SMX1500XLRT2U, SMX1500XLRT2UN
STANDARDS & COMPLIANCE	
Product Certifications	UL Listed; cUL Listed
Product Compliance	FCC (USA); CE (Europe)

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.