


Product datasheet

Specifications

Low temp kit (-35C)



ACAC10040

Overview

Lead Time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage 200...240 V

Provided Equipment User manual

Physical

Height 35.1 cm

Width 23.7 cm

Depth 27.4 cm

Net Weight 9 kg

Mounting Preference No preference

Mounting Mode Not rack-mountable

Input

Network Frequency 50 Hz

Packing Units

Unit Type Of Package 1 PCE

Number Of Units In Package 1 1

Package 1 Height 40 cm

Package 1 Width 38 cm

Package 1 Length 40 cm

Package 1 Weight 9.86 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive

Under investigation

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
