

# HPE Aruba Networking 750 Series Campus Access Points



## What's new

- AI-powered Wi-Fi 7 access points ideal for the most demanding enterprise, healthcare, LPV, education, retail, and industrial IoT deployments.
- Three 4x4 MIMO radios provide comprehensive triband coverage across 2.4 GHz, 5 GHz, and 6 GHz for up to 18.7 Gbps maximum aggregate data rate.
- High availability with dual 10 Gbps wired ports for redundant Ethernet and power, as well as the ability to combine (sum) power from both ports.
- High density IoT support with two integrated [1] Bluetooth 5.4 and

## Overview

HPE Aruba Networking 750 Series Campus Access Points are our flagship Wi-Fi 7 Access Points that deliver impressive wireless performance, strengthen network security, provide precise location-based services, and offer an IoT platform with enterprise-grade security, enabling enterprises to fully realize the value of their wireless investment and unlock operational efficiencies.

This high-performance access point is designed with three 4x4 MIMO radios (2.4 GHz, 5 GHz, and 6 GHz), dual 10 Gbps Ethernet ports, dual IoT radios, built-in GNSS receiver, and patented Ultra Tri-band (UTB) filtering for high capacity, fast, and resilient connectivity with enhanced security. HPE Aruba Networking Wireless Operating System (AOS-10) and HPE Aruba Networking Central provide intelligent automation, AI insights, and unified infrastructure management to help drive efficient IT operations. The 750 Series includes a limited lifetime warranty.

802.15.4 radios for Zigbee support and two USB port extensions.

- Built-in GNSS receiver, barometric pressure sensor, and intelligent software enable Access Points to self locate and act as reference points for accurate indoor location measurements.
- Patented Ultra Tri-band (UTB) filtering enhances use of 5 GHz and 6 GHz bands.

## Features

### Flagship Wi-Fi 7 Performance

Based on the 802.11be standard, the HPE Aruba Networking 750 Series Campus Access Points are designed to take advantage of the 6 GHz band through three dedicated radios, which translates into far greater speeds, wider channels for multi-gigabit traffic, and less interference.

With three 4x4 MIMO radios (2.4 GHz, 5 GHz, and 6 GHz), it delivers up to 18.7 Gbps maximum tri-band aggregate data rate and is capable of up to 28.8 Gbps maximum aggregate data rate using optional dual 5 GHz and 6 GHz radio modes.

Featuring high availability with two 10 GbE ports for hitless failover for both data and power, allowing these dual ports to provide business continuity for mission-critical applications with flexibility to support speeds of 1, 2.5, 5, or 10 Gbps (or 100 Mbps).

Enhanced wireless experience with HPE Aruba Networking ClientMatch technology removes sticky client issues by steering a client to the Access Point where it receives the strongest radio signal.

Patented Ultra Tri band filtering enables enterprises to take advantage of the high end of 5 GHz with the lower end of 6 GHz without creating coverage gaps or islands.

### Simplified Access with Enhanced Security

The HPE Aruba Networking 750 Series Campus Access Points offer enhanced security with Dynamic Segmentation to remove the time-consuming and error-prone task of managing complex and static VLANs, ACLs, and subnets by dynamically assigning policies and keeping traffic protected and separated.

MACsec-capable 10 GbE port extends wired Ethernet protection to the access point.

It offers stronger encryption and authentication with WPA3, protected credentials/keys storage for guest access with Enhanced Open, and user and IoT access policy enforcement firewalls.

The APs simplify policy enforcement by using the Policy Enforcement Firewall (PEF) to encapsulate all traffic from the access point to the gateway (or mobility controller) for end-to-end encryption and inspection.

For enhanced device assurance, HPE Aruba Networking Access Points include an installed Trusted Platform Module (TPM) for protected storage of credentials, keys, and boot code.

### AP as an IoT Platform

The HPE Aruba Networking 750 Series Campus Access Point can serve as flexible IoT platforms that bolsters network security and provide coverage for a broad range of IoT devices without the need for network overlays.

It provides two built-in Bluetooth 5.4 and 802.15.4 radios for Zigbee support to simplify deploying and managing IoT-based location services, asset tracking services, security solutions, and IoT sensors. Two USB port extensions provide connectivity to a range of IoT devices.

Advanced IoT Coexistence (AIC) feature uses built-in filtering to allow Wi-Fi and BLE/Zigbee radios to operate at greater capacity without the impact of interference.

HPE Aruba Networking Central IoT Operations unifies visibility of IT and OT infrastructure within the network health dashboard by extending network monitoring and insights to BLE, Zigbee, and other non-IP IoT devices to help non-Wi-Fi device onboarding and data collection.

HPE Aruba Networking Central Client Insights uses deep packet inspection to provide additional context and behavioral information that help verify devices are receiving proper policy enforcement and continuously monitor for rogue devices.

### **Energy Saving and Self-locating**

The HPE Aruba Networking 750 Series Campus Access Points help organizations reduce energy consumption and deliver precision indoor location services with the Access Points that serve as reference points for client devices and other technologies using fine time measurement.

It offers precision locationing with the support of FTM 802.11az for sub-1 meter accuracy and built-in GNSS receivers for high-accuracy indoor location measurements.

Built-in barometric sensor for altitude locationing within multi-story buildings that provides floor-level mappings.

AI-powered dynamic power save mode enables the HPE Aruba Networking 750 Series Campus Access Points to automatically wake up at a schedule when connectivity demand arises, reducing power demands and lowering the energy footprint to align with the organization sustainability initiatives.

The target wake time (TWT) establishes a schedule for when clients need to communicate with an AP to help improve client power savings and reduce airtime contention. Intelligent Power Monitoring provides energy consumption insights as APs continuously monitor and report hardware energy usage.

**Wi-Fi antenna**

AP-754: Two sets of four (female) RP-SMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worst-case internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.

AP-755: Integrated down tilt omni-directional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual-5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual-6 GHz mode). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.

**Certifications**

Bluetooth SIG  
 Ethernet Alliance (PoE, PD device, Class 6)  
 UL2043 plenum rating  
 Wi-Fi Alliance (WFA)  
 Wi-Fi CERTIFIED a, b, g, n, ac, 6, 7  
 WPA, WPA2 and WPA3- Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)  
 WMM, WMM-PS, W-Fi Agile Multiband

**Regulatory**

FCC/ISED;  
 CE Marked;  
 RED Directive 2014/53/EU;  
 EMC Directive 2014/30/EU;  
 Low Voltage Directive 2014/35/EU;  
 UL/IEC/EN 60950;  
 IEC/EN 62368-1;  
 EN 60601-1-1;  
 EN60601-1-2  
 For more country-specific regulatory information and approvals, please see your HPE Aruba Networking representative.

**Warranty**

Limited lifetime warranty. See the warranty duration.

**Connectivity, standard**

Wi-Fi 7 (802.11be)

**Ports**

E0, E1: Two Ethernet wired network ports (RJ-45);  
 U0, U1: Two USB 2.0 host interface (Type A connector);  
 Serial console interface (proprietary, micro-B USB physical jack);  
 Kensington security slot;

**Mounting**

A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.

**Power consumption**

Maximum (worst case) power consumption (without/with USB devices attached):  
 DC powered: 35W/46W  
 PoE powered: 40W/51W  
 This assumes that up to 10W is supplied to the attached USB device(s)

Maximum (worst-case) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE)  
 Maximum (worst-case) power consumption in deep-sleep mode: 2.4W (DC) or 3.5W (PoE)

**Radio coverage**

AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO

[1] Bluetooth is a trademark owned by its proprietor and used by Hewlett Packard Enterprise under license. All third-party marks are property of their respective owners.

## SKU comparison

	HPE Aruba Networking AP-754 (EG) Tri Radio 4x4 Wi-Fi 7 External Antennas Campus Access Point (S1G71A)	HPE Aruba Networking AP-754 (EG) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G76A)	HPE Aruba Networking AP-754 (IL) Tri Radio 4x4 Wi-Fi 7 External Antennas Campus Access Point (S1G72A)
<b>Differentiator</b>	Available in Egypt only	Available in Egypt only	Available in Israel only
<b>Wi-Fi antenna</b>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>
<b>Certifications</b>	Bluetooth SIG Ethernet Alliance (PoE, PD device, Class 6) UL2043 plenum rating WiFi Alliance (WFA) WiFi CERTIFIED a, b, g, n, ac, 6, 7 WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE) WMM, WMMPS, WFi Agile Multiband	Bluetooth SIG Ethernet Alliance (PoE, PD device, Class 6) UL2043 plenum rating WiFi Alliance (WFA) WiFi CERTIFIED a, b, g, n, ac, 6, 7 WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE) WMM, WMMPS, WFi Agile Multiband	Bluetooth SIG Ethernet Alliance (PoE, PD device, Class 6) UL2043 plenum rating WiFi Alliance (WFA) WiFi CERTIFIED a, b, g, n, ac, 6, 7 WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE) WMM, WMMPS, WFi Agile Multiband
<b>Regulatory</b>	FCC/ISED; CE Marked; RED Directive 2014/53/EU; EMC Directive 2014/30/EU; Low Voltage Directive 2014/35/EU; UL/IEC/EN 60950; IEC/EN 623681; EN 6060111; EN6060112 For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.	FCC/ISED; CE Marked; RED Directive 2014/53/EU; EMC Directive 2014/30/EU; Low Voltage Directive 2014/35/EU; UL/IEC/EN 60950; IEC/EN 623681; EN 6060111; EN6060112 For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.	FCC/ISED; CE Marked; RED Directive 2014/53/EU; EMC Directive 2014/30/EU; Low Voltage Directive 2014/35/EU; UL/IEC/EN 60950; IEC/EN 623681; EN 6060111; EN6060112 For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.

	HPE Aruba Networking AP-754 (EG) Tri Radio 4x4 Wi-Fi 7 External Antennas Campus Access Point (S1G71A)	HPE Aruba Networking AP-754 (EG) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G76A)	HPE Aruba Networking AP-754 (IL) Tri Radio 4x4 Wi-Fi 7 External Antennas Campus Access Point (S1G72A)
<b>Connectivity, standard</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Ports</b>	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;
<b>Mounting</b>	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.
<b>Power consumption</b>	Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)  Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)	Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)  Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)	Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)  Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)
<b>Radio coverage</b>	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO

	HPE Aruba Networking AP-754 (IL) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G77A)	HPE Aruba Networking AP-754 (JP) Tri Radio 4x4 Wi-Fi 7 External Antennas Campus Access Point (S1G73A)	HPE Aruba Networking AP-754 (JP) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G78A)
<b>Differentiator</b>	Available in Israel only	Available in Japan only	Available in Japan only
<b>Wi-Fi antenna</b>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>
<b>Certifications</b>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>
<b>Regulatory</b>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Connectivity, standard</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)

	HPE Aruba Networking AP-754 (IL) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G77A)	HPE Aruba Networking AP-754 (JP) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G73A)	HPE Aruba Networking AP-754 (JP) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G78A)
<b>Ports</b>	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;
<b>Mounting</b>	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.
<b>Power consumption</b>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>
<b>Radio coverage</b>	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO

	HPE Aruba Networking AP-754 (RW) Tri Radio 4x4 Wi-Fi 7 External Antennas Campus Access Point (S1G74A)	HPE Aruba Networking AP-754 (RW) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G79A)	HPE Aruba Networking AP-754 (US) Tri Radio 4x4 Wi-Fi 7 External Antennas Campus Access Point (S1G75A)
<b>Differentiator</b>	Available everywhere except US, Israel, Japan and Egypt	Available everywhere except US, Israel, Japan and Egypt	Available in US only
<b>Wi-Fi antenna</b>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>
<b>Certifications</b>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>
<b>Regulatory</b>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Connectivity, standard</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)

	HPE Aruba Networking AP-754 (RW) Tri Radio 4x4 Wi-Fi 7 External Antennas Campus Access Point (S1G74A)	HPE Aruba Networking AP-754 (RW) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G79A)	HPE Aruba Networking AP-754 (US) Tri Radio 4x4 Wi-Fi 7 External Antennas Campus Access Point (S1G75A)
<b>Ports</b>	E0, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	E0, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	E0, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;
<b>Mounting</b>	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.
<b>Power consumption</b>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>
<b>Radio coverage</b>	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO

	HPE Aruba Networking AP-754 (US) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G80A)	HPE Aruba Networking AP-755 (EG) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S1G81A)	HPE Aruba Networking AP-755 (EG) Tri Radio 4x4 Wi-Fi 7 Internal Antennas TAA Campus Access Point (S1G86A)
<b>Differentiator</b>	Available in US only	Available in Egypt only	Available in Egypt only
<b>Wi-Fi antenna</b>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>
<b>Certifications</b>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>
<b>Regulatory</b>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Connectivity, standard</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)

	HPE Aruba Networking AP-754 (US) Tri Radio 4x4 Wi-Fi 7 External Antennas TAA Campus Access Point (S1G80A)	HPE Aruba Networking AP-755 (EG) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S1G81A)	HPE Aruba Networking AP-755 (EG) Tri Radio 4x4 Wi-Fi 7 Internal Antennas TAA Campus Access Point (S1G86A)
<b>Ports</b>	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;
<b>Mounting</b>	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.
<b>Power consumption</b>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>
<b>Radio coverage</b>	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO

	HPE Aruba Networking AP-755 (ID) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S5E16A)	HPE Aruba Networking AP-755 (IL) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S1G82A)	HPE Aruba Networking AP-755 (IL) Tri Radio 4x4 Wi-Fi 7 Internal Antennas TAA Campus Access Point (S1G87A)
<b>Differentiator</b>	Available in Indonesia only	Available in Israel only	Available in Israel only
<b>Wi-Fi antenna</b>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>
<b>Certifications</b>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>
<b>Regulatory</b>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Connectivity, standard</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)

	HPE Aruba Networking AP-755 (ID) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S5E16A)	HPE Aruba Networking AP-755 (IL) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S1G82A)	HPE Aruba Networking AP-755 (IL) Tri Radio 4x4 Wi-Fi 7 Internal Antennas TAA Campus Access Point (S1G87A)
<b>Ports</b>	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;
<b>Mounting</b>	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.
<b>Power consumption</b>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>
<b>Radio coverage</b>	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO

	HPE Aruba Networking AP-755 (JP) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S1G83A)	HPE Aruba Networking AP-755 (JP) Tri Radio 4x4 Wi-Fi 7 Internal Antennas TAA Campus Access Point (S1G88A)	HPE Aruba Networking AP-755 (RW) Tri Radio 4x4 Wi-Fi 7 Internal Antennas 5-pack Campus Access Point (SOH10A)
<b>Differentiator</b>	Available in Japan only	Available in Japan only	Available everywhere except US, Israel, Japan and Egypt
<b>Wi-Fi antenna</b>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>
<b>Certifications</b>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>
<b>Regulatory</b>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> <li>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</li> </ul>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> <li>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</li> </ul>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> <li>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</li> </ul>
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Connectivity, standard</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)

	HPE Aruba Networking AP-755 (JP) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S1G83A)	HPE Aruba Networking AP-755 (JP) Tri Radio 4x4 Wi-Fi 7 Internal Antennas TAA Campus Access Point (S1G88A)	HPE Aruba Networking AP-755 (RW) Tri Radio 4x4 Wi-Fi 7 Internal Antennas 5-pack Campus Access Point (SOH10A)
<b>Ports</b>	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;
<b>Mounting</b>	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.
<b>Power consumption</b>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>
<b>Radio coverage</b>	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO

	HPE Aruba Networking AP-755 (RW) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S1G84A)	HPE Aruba Networking AP-755 (RW) Tri Radio 4x4 Wi-Fi 7 Internal Antennas TAA Campus Access Point (S1G89A)	HPE Aruba Networking AP-755 (US) Tri Radio 4x4 Wi-Fi 7 Internal Antennas 5-pack Campus Access Point (SOH11A)
<b>Differentiator</b>	Available everywhere except US, Israel, Japan and Egypt	Available everywhere except US, Israel, Japan and Egypt	Available in US only
<b>Wi-Fi antenna</b>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Builtin antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>
<b>Certifications</b>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>	<ul style="list-style-type: none"> <li>Bluetooth SIG</li> <li>Ethernet Alliance (PoE, PD device, Class 6)</li> <li>UL2043 plenum rating</li> <li>WiFi Alliance (WFA)</li> <li>WiFi CERTIFIED a, b, g, n, ac, 6, 7</li> <li>WPA, WPA2 and WPA3-Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)</li> <li>WMM, WMMPS, WFi Agile Multiband</li> </ul>
<b>Regulatory</b>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<ul style="list-style-type: none"> <li>FCC/ISED;</li> <li>CE Marked;</li> <li>RED Directive 2014/53/EU;</li> <li>EMC Directive 2014/30/EU;</li> <li>Low Voltage Directive 2014/35/EU;</li> <li>UL/IEC/EN 60950;</li> <li>IEC/EN 623681;</li> <li>EN 6060111;</li> <li>EN6060112</li> </ul> <p>For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Connectivity, standard</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)

	HPE Aruba Networking AP-755 (RW) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S1G84A)	HPE Aruba Networking AP-755 (RW) Tri Radio 4x4 Wi-Fi 7 Internal Antennas TAA Campus Access Point (S1G89A)	HPE Aruba Networking AP-755 (US) Tri Radio 4x4 Wi-Fi 7 Internal Antennas 5-pack Campus Access Point (SOH11A)
<b>Ports</b>	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;	EO, E1: Two Ethernet wired network ports (RJ45); U0, U1: Two USB 2.0 host interface (Type A connector); Serial console interface (proprietary, microB USB physical jack); Kensington security slot;
<b>Mounting</b>	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.
<b>Power consumption</b>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>	<p>Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 35W/46W PoE powered: 40W/51W This assumes that up to 10W is supplied to the attached USB device(s)</p> <p>Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE) Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)</p>
<b>Radio coverage</b>	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO

**HPE Aruba Networking AP-755 (US) Tri Radio 4x4 Wi-Fi 7 Internal Antennas Campus Access Point (S1G85A)**

**HPE Aruba Networking AP-755 (US) Tri Radio 4x4 Wi-Fi 7 Internal Antennas TAA Campus Access Point (S1G90A)**

<b>Differentiator</b>	Available in US only	Available in US only
<b>Wi-Fi antenna</b>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>	<p>AP754: Two sets of four (female) RPSMA connectors for external antennas (A0 through A3 corresponding with radio chains 0 through 3 for the 2.4 GHz and 5 GHz radios, and B0 through B3 corresponding with radio chains 0 through 3 for the 6 GHz radio). Worstcase internal loss between radio interface and external antenna connectors: 1.1 dB in 2.4 GHz, 1.8 dB in 5 GHz, and 2.8 dB in 6 GHz.</p> <p>AP755: Integrated down tilt omnidirectional antennas for 4x4 MIMO with peak antenna gain of 5.3 dBi in 2.4 GHz, 6.0 dBi in 5 GHz (5.8 dBi in dual5 GHz mode) and 6.0 dBi in 6 GHz (5.9 dBi in dual6 GHz mode). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The down tilt angle for maximum gain is roughly 30 to 40 degrees.</p>
<b>Certifications</b>	<p>Bluetooth SIG            Ethernet Alliance (PoE, PD device, Class 6)            UL2043 plenum rating            WiFi Alliance (WFA)            WiFi CERTIFIED a, b, g, n, ac, 6, 7            WPA, WPA2 and WPA3- Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)            WMM, WMMPS, WFi Agile Multiband</p>	<p>Bluetooth SIG            Ethernet Alliance (PoE, PD device, Class 6)            UL2043 plenum rating            WiFi Alliance (WFA)            WiFi CERTIFIED a, b, g, n, ac, 6, 7            WPA, WPA2 and WPA3- Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)            WMM, WMMPS, WFi Agile Multiband</p>
<b>Regulatory</b>	<p>FCC/ISED;            CE Marked;            RED Directive 2014/53/EU;            EMC Directive 2014/30/EU;            Low Voltage Directive 2014/35/EU;            UL/IEC/EN 60950;            IEC/EN 623681;            EN 6060111;            EN6060112            For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>	<p>FCC/ISED;            CE Marked;            RED Directive 2014/53/EU;            EMC Directive 2014/30/EU;            Low Voltage Directive 2014/35/EU;            UL/IEC/EN 60950;            IEC/EN 623681;            EN 6060111;            EN6060112            For more countryspecific regulatory information and approvals, please see your HPE Aruba Networking representative.</p>
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Connectivity, standard</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Ports</b>	<p>E0, E1: Two Ethernet wired network ports (RJ45);            U0, U1: Two USB 2.0 host interface (Type A connector);            Serial console interface (proprietary, microB USB physical jack);            Kensington security slot;</p>	<p>E0, E1: Two Ethernet wired network ports (RJ45);            U0, U1: Two USB 2.0 host interface (Type A connector);            Serial console interface (proprietary, microB USB physical jack);            Kensington security slot;</p>
<b>Mounting</b>	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.

**HPE Aruba Networking AP-755 (US) Tri  
Radio 4x4 Wi-Fi 7 Internal Antennas  
Campus Access Point (S1G85A)**

**HPE Aruba Networking AP-755 (US) Tri  
Radio 4x4 Wi-Fi 7 Internal Antennas TAA  
Campus Access Point (S1G90A)**

**Power consumption**

Maximum (worst case) power consumption (without/with USB devices attached):  
DC powered: 35W/46W  
PoE powered: 40W/51W  
This assumes that up to 10W is supplied to the attached USB device(s)

Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE)  
Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)

Maximum (worst case) power consumption (without/with USB devices attached):  
DC powered: 35W/46W  
PoE powered: 40W/51W  
This assumes that up to 10W is supplied to the attached USB device(s)

Maximum (worstcase) power consumption in idle mode: 14W/25W (DC) or 12W/23W (PoE)  
Maximum (worstcase) power consumption in deepsleep mode: 2.4W (DC) or 3.5W (PoE)

**Radio coverage**

AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO

AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 4x4 MIMO

# HPE Aruba Networking Services

HPE Aruba Networking services simplify and accelerate the network technology lifecycle, enabling your network to scale with better predictability and cost-effectiveness. Whether you operate your own network and need to improve your IT efficiencies, or you want to offload some of the burden, we have the services you need to reach your goals.

Learn more about what HPE Services - Aruba Networking has to offer at: [hpe.com/edge/services](https://hpe.com/edge/services)

## Support Services

Our support portfolio provides the essential support elements as well as proactive and preventive features to help you improve your team's productivity and get the most from your network. Our support customers benefit from faster issue resolution, simplified operations and efficiencies, and reduced network issues.

## Professional Services

With deep intellectual capital and purpose-built tools, our team delivers a range of standard and custom professional services designed to accelerate your value from HPE Aruba Networking technology.

### Project based services include:

- Planning, audit, and assessment
- Architecture review and design
- Deployment, migration, and knowledge transfer

### Annual subscription services include:

- Network optimization
- Intelligent Operations
- Customer Experience Management

Our [Education Services](#) allow your team to come up to speed quickly.

## HPE GreenLake for Networking

Our NaaS solution, is part of the HPE GreenLake services family, and simplifies network operations, accelerates equipment handling, and increases the value of your HPE Aruba Networking solution. If you need expert guidance and automation-based operations for your team, please explore our NaaS approach through HPE GreenLake for Networking.

[For additional technical information, available models and options, please reference the QuickSpecs](#)

Visit [HPE.com](https://www.hpe.com)

[Chat now](#)

© Copyright 2025 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Image may differ from the actual product.

[PSN1014840332HKEN](#), December, 2025.

HEWLETT PACKARD ENTERPRISE

[hpe.com](https://www.hpe.com)

