





SPECIFICATIONS

Active Display Area (mm) 521.395 (H) x 293.284 (V) Curvature Curve 1500R Panel Type VA Panel Resolution 1920 x 1080 (FHD) Pixel Pitch (H x V) 0.27156 (H) x 0.27156 (V) Aspect Ratio 16:9 Brightness (nits) SDR: 300 cd/m² Contrast Ratio 3000:1 DCR 100000000:1 Signal Frequency 98.496 ~ 392.4 KHz(H) / 48~180 Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (MPRT) DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync HDR Ready Video ports Video ports 1x HDMI™ 2.0b (FHD@180Hz) Video ports 1x HDMI™ 2.0b (FHD@180Hz) Video ports N/A Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 89.9% / 91.5% / 115.8% (CIE1976 Standard) Surface Treatment Anti-glare Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Yes P	Panel Size	23.6"
Panel Type VA Panel Resolution 1920 x 1080 (FHD) Pixel Pitch (H x V) 0.27156 (H) x 0.27156 (V) Aspect Ratio 16:9 Brightness (nits) SDR: 300 cd/m² Contrast Ratio 3000:1 DCR 100000000:1 Signal Frequency 98.496 ~ 392.4 KHz(H) / 48~180 Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (MPRT) DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync HDR Ready 1x HDMI™ 2.0b (FHD@180Hz) Video ports 1x HDMI™ 2.0b (FHD@180Hz) 1x DisplayPort 1.2a N/A Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 89.9% / 91.5% / 115.8% (CIE1976 Standard) Surface Treatment Anti-glare Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Yes Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Fivot) N/A Adjus	Active Display Area (mm)	521.395 (H) x 293.284 (V)
Panel Resolution 1920 x 1080 (FHD) Pixel Pitch (H x V) 0.27156 (H) x 0.27156 (V) Aspect Ratio 16:9 Brightness (nits) SDR: 300 cd/m² Contrast Ratio 3000:1 DCR 100000000:1 Signal Frequency 98.496 ~ 392.4 KHz(H) / 48~180 Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (MPRT) DYNAMIC REFRESH RATE Adaptive-Sync HDR Ready 1x HDMI™ 2.0b (FHD@180Hz) Video ports 1x HDMI™ 2.0b (FHD@180Hz) 1x DisplayPort 1.2a N/A Audio ports 1x Headphone-out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 89.9% / 91.5% / 115.8% (CIE1976 Standard) Surface Treatment Anti-glare Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Fivot) N/A Adjustment (Height) N/A <t< th=""><th>Curvature</th><th>Curve 1500R</th></t<>	Curvature	Curve 1500R
Pixel Pitch (H x V) 0.27156 (H) x 0.27156 (V) Aspect Ratio 16:9 Brightness (nits) SDR: 300 cd/m² Contrast Ratio 3000:1 DCR 100000000:1 Signal Frequency 98.496 ~ 392.4 KHz(H) / 48~180 Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (MPRT) DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync HDR Ready 1x HDMI™ 2.0b (FHD@180Hz) 1x DisplayPort 1.2a Video ports 1x HDMI™ 2.0b (FHD@180Hz) 1x DisplayPort 1.2a USB ports N/A Audio ports 1x Headphone-out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 89.9% / 91.5% / 115.8% (CIE1976 Standard) Surface Treatment Anti-glare Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Yes Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Fivot) N/A Adjustment (Height) N/A	Panel Type	VA
Aspect Ratio 16:9	Panel Resolution	1920 x 1080 (FHD)
SDR: 300 cd/m²	Pixel Pitch (H x V)	0.27156 (H) x 0.27156 (V)
DCR	Aspect Ratio	16:9
DCR 100000000:1 Signal Frequency 98.496 ~ 392.4 KHz(H) / 48~180 Hz(V) ACTIVATED RANGE 48~180Hz Refresh Rate 180Hz Response time 1ms (MPRT) DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync HDR Ready 1x HDMI™ 2.0b (FHD@180Hz) 1x DisplayPort 1.2a Video ports 1x Headphone-out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 89.9% / 91.5% / 115.8% (CIE1976 Standard) Surface Treatment Anti-glare Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Yes Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5°~20° Adjustment (Pivot) N/A Adjustment (Height) N/A Kensington Lock Yes	Brightness (nits)	SDR: 300 cd/m ²
Signal Frequency #2(V) ACTIVATED RANGE Refresh Rate Response time DYNAMIC REFRESH RATE TECHNOLOGY HDR Support Video ports ### 180Hz ### 2.0b (FHD@180Hz) ### 178° (W) ### 2.0b (FHD@180Hz) ### 178° (W) ### 39.9% / 91.5% / 115.8% (CIE1976 ### 55andard) Surface Treatment ### 2.0b (FHD@180Hz) ### 178° (W) ### 4.0be RGB / DCI-P3 / sRGB ### 39.9% / 91.5% / 115.8% (CIE1976 ### 55andard) Surface Treatment ### Anti-glare ### Display Colors ### 1.07b, 10 bits (8 bits + FRC) ### SPEAKER ### N/A ### Frameless Design ### Yes ### Power Input ### 100~240V, 50/60Hz ### Adjustment (Tilt) ### 4.5°~20° ### Adjustment (Pivot) ### Adjustment (Pivot) ### Adjustment (Pivot) ### Adjustment (Pivot) ### N/A ### MACHANGE ### 180	Contrast Ratio	3000:1
ACTIVATED RANGE Refresh Rate Response time DYNAMIC REFRESH RATE TECHNOLOGY HDR Support Video ports USB ports N/A Audio ports Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors Display Colors Power Type Power Input Adjustment (Firot) Adjustment (Pivot) Adjustment (Pivot) Response Image Image Image Image Image Image Alabetz Al	DCR	100000000:1
Refresh Rate Response time Ims (MPRT) DYNAMIC REFRESH RATE TECHNOLOGY HDR Support HDR Ready Video ports Ix HDMI™ 2.0b (FHD@180Hz) 1x DisplayPort 1.2a USB ports N/A Audio ports Ix Headphone-out Viewing Angle I78° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors I.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Power Type Internal Power Board Power Input I00~240V, 50/60Hz Adjustment (Tilt) Adjustment (Pivot) N/A Adjustment (Pivot) N/A Adjustment (Height) N/A Kensington Lock Yes	Signal Frequency	
Response time DYNAMIC REFRESH RATE TECHNOLOGY HDR Support Video ports 1x HDMI™ 2.0b (FHD@180Hz) 1x DisplayPort 1.2a USB ports N/A	ACTIVATED RANGE	48~180Hz
DYNAMIC REFRESH RATE TECHNOLOGY HDR Support HDR Ready 1x HDMI™ 2.0b (FHD@180Hz) 1x DisplayPort 1.2a USB ports N/A Audio ports 1x Headphone-out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER Power Type Internal Power Board Power Input Adjustment (Tilt) Adjustment (Swivel) Adjustment (Pivot) Adjustment (Height) Kensington Lock Yes	Refresh Rate	180Hz
TECHNOLOGY HDR Support HDR Ready Video ports 1x HDMI™ 2.0b (FHD@180Hz) 1x DisplayPort 1.2a USB ports N/A Audio ports 1x Headphone-out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Yes Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) Adjustment (Swivel) Adjustment (Pivot) N/A Kensington Lock Yes	Response time	1ms (MPRT)
Video ports 1x HDMI™ 2.0b (FHD@180Hz) 1x DisplayPort 1.2a USB ports N/A Audio ports 1x Headphone-out Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 89.9% / 91.5% / 115.8% (CIE1976 Standard) Surface Treatment Anti-glare Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Yes Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5°~20° Adjustment (Swivel) N/A Adjustment (Pivot) N/A Adjustment (Height) N/A Kensington Lock Yes		Adaptive-Sync
USB ports N/A Audio ports Ix Headphone-out Viewing Angle Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors SPEAKER Power Type Internal Power Board Power Input Adjustment (Tilt) Adjustment (Pivot) Adjustment (Height) Kensington Lock N/A Ix Headphone-out 1x Headphone-out 105.8% (CIE1976 Standard) Standard) Standard) 105.8% (CIE1976 Standard) Standard) 107b, 10 bits (8 bits + FRC) Internal Power Board 100~240V, 50/60Hz Adjustment (Tilt) Adjustment (Fivot) N/A N/A Kensington Lock Yes	HDR Support	HDR Ready
Audio ports Viewing Angle 178° (H) / 178° (V) 89.9% / 91.5% / 115.8% (CIE1976 Standard) Surface Treatment Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) Adjustment (Swivel) Adjustment (Pivot) Adjustment (Height) Kensington Lock Yes	Video ports	, , ,
Viewing Angle 178° (H) / 178° (V) Adobe RGB / DCI-P3 / sRGB 89.9% / 91.5% / 115.8% (CIE1976 Standard) Surface Treatment Anti-glare Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Yes Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5°~20° Adjustment (Swivel) N/A Adjustment (Pivot) N/A Adjustment (Height) N/A Kensington Lock Yes	USB ports	N/A
Adobe RGB / DCI-P3 / sRGB Surface Treatment Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Yes Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) Adjustment (Swivel) Adjustment (Pivot) N/A Adjustment (Height) Kensington Lock Yes	Audio ports	1x Headphone-out
Standard) Surface Treatment Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) Adjustment (Swivel) Adjustment (Pivot) Adjustment (Height) Kensington Lock Standard) Standard) Standard) Standard) 1.07b, 10 bits (8 bits + FRC) N/A N/A N/A N/A Standard) N/A N/A N/A N/A Ves	Viewing Angle	178° (H) / 178° (V)
Display Colors 1.07b, 10 bits (8 bits + FRC) SPEAKER N/A Frameless Design Yes Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) Adjustment (Swivel) Adjustment (Pivot) Adjustment (Height) Kensington Lock Yes	Adobe RGB / DCI-P3 / sRGB	•
SPEAKER N/A Frameless Design Yes Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) Adjustment (Swivel) Adjustment (Pivot) Adjustment (Height) N/A Kensington Lock Yes	Surface Treatment	Anti-glare
Frameless Design Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) Adjustment (Swivel) Adjustment (Pivot) Adjustment (Height) Kensington Lock Yes	Display Colors	1.07b, 10 bits (8 bits + FRC)
Power Type Internal Power Board Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5°~20° Adjustment (Swivel) N/A Adjustment (Pivot) N/A Adjustment (Height) N/A Kensington Lock Yes	SPEAKER	N/A
Power Input 100~240V, 50/60Hz Adjustment (Tilt) -5°~20° Adjustment (Swivel) N/A Adjustment (Pivot) N/A Adjustment (Height) N/A Kensington Lock Yes	Frameless Design	Yes
Adjustment (Tilt) -5°~20° Adjustment (Swivel) N/A Adjustment (Pivot) N/A Adjustment (Height) N/A Kensington Lock Yes	Power Type	Internal Power Board
Adjustment (Swivel) Adjustment (Pivot) Adjustment (Height) N/A Kensington Lock N/A Yes	Power Input	100~240V, 50/60Hz
Adjustment (Pivot) Adjustment (Height) Kensington Lock N/A Yes	Adjustment (Tilt)	-5°~20°
Adjustment (Height) N/A Kensington Lock Yes	Adjustment (Swivel)	N/A
Kensington Lock Yes	Adjustment (Pivot)	N/A
	Adjustment (Height)	N/A
VESA Mounting 100 x 100 mm	Kensington Lock	Yes
	VESA Mounting	100 x 100 mm

FEATURES



1500R Curved Gaming

Immerse in a captivating experience with a 1500R curvature rate.



180Hz High Refresh Rate

Experience smooth gaming with a blazing fast 180Hz refresh rate, that gives you the upperhand in fast moving games.



1ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 1ms(MPRT) response time.



HDR Ready

Enhance eye-catching details through adjustments in contrast and shadows.



AI Vision

Smart black tuner to brighten your day by bringing out the fine details in dark areas.

Dimension with Stand (W x D x H)	539 x 220.1 x 394.5 mm (21.2 x 8.6 x 15.5 inch)
Dimension without Stand (W \times D \times H)	539 x 70.2 x 319.7 mm (21.2 x 2.76 x 12.5 inch)
Weight (NW / GW)	3 kg (6.6 lbs) / 4.8 kg (10.5 lbs)
Carton Dimension (W X D X H)	640 x 140 x 410 mm (25 x 5.5 x 16.1 inch)
Accessories	1x HDMI™ Cable (2.0), 1x Power Cord (C13), 1x Quick Guide
Note	HDMI™: 1920 x 1080 (Up to 180Hz) DisplayPort: 1920 x 1080 (Up to 180Hz) Support: HDMI™ CEC; Non Support: KVM, PIP/PBP

CONNECTIONS



- 1. 5-Way Navigator
- 2. HDMI™ 2.0b (FHD@180Hz)
- 3. DisplayPort 1.2a
- 4. Headphone-out
- 5. AC-in
- 6. Kensington Lock