# Power Cord, C19 to CEE/7 Schuko, 2.5m

AP9875

Product availability: Stock - Normally stocked in distribution facility

#### **Overview**

Lead time Usually in Stock

#### Main

Product or Component Type	Power cord	
Input Connection Type	Schuko CEE 7 / EU1-16P	
Number of rack unit	0U	
Cable length	8.2 ft (2.5 m)	
Number of cables	1	

#### **Physical**

Color	Black	
Net Weight	0.49 lb(US) (0.22 kg)	
Mounting preference	No preference	
Mounting Mode	Not rack-mountable	

#### Input

Input Frequency	50/60 Hz
Permissible voltage	90250 V
Max line current	16 A
Input current limits	16 A

#### **Output**

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Protection Type	Without circuit breaker

#### Conformance

Product Certifications VDE

#### **Environmental**

Ambient air temperature for operation	32113 °F (045 °C)	
Relative Humidity	095 %	
Operating altitude	010000 ft	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature for Storage	-13149 °F (-2565 °C)	
Storage Relative Humidity	y 095 %	
Storage altitude	050000 ft (0.000000000015240.0000000000 m)	

# Ordering and shipping details

Category	11309-APC RESALE PRODUCTS	
Discount Schedule	APC1	
GTIN	731304189404	
Returnability	No	
Country of origin	CN	

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.01 in (5.1 cm)	
Package 1 Width	4.02 in (10.2 cm)	
Package 1 Length	7.99 in (20.3 cm)	
Package 1 Weight	0.659 lb(US) (0.299 kg)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	10	
Package 2 Height	10.04 in (25.5 cm)	
Package 2 Width	13.07 in (33.2 cm)	
Package 2 Length	21.10 in (53.6 cm)	
Package 2 Weight	9.9 lb(US) (4.5 kg)	
Unit Type of Package 3	PAL	
Number of Units in Package 3	10	
Package 3 Height	56.69 in (143.99 cm)	
Package 3 Width	39.37 in (100 cm)	
Package 3 Length	47.24 in (120 cm)	
Package 3 Weight	9.9 lb(US) (4.5 kg)	

### **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	70
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	Yes