

Product data sheet

Specifications



APC Smart-UPS RT192V RM Battery Pack 2 Rows

SURT192RMXLBP2

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or Component Type	External battery pack
Number of rack unit	6U
Battery Type	Lead-Acid battery
Provided Equipment	All required connectors Rack Mounting brackets User Manual
Range of Product	Smart-UPS Battery Systems

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	19 inch Battery tray
Battery Voltage	192V
RBC Quantity	4
Replacement battery	APCRBC140

Physical

Color	Black
Height	10.4 in (263 mm)
Width	17.008 in (432 mm)
Depth	29.09 in (739 mm)
Net Weight	400.84 lb(US) (181.82 kg)
Mounting Mode	Rack-mounted

Output

Battery Capacity	19 Ah
------------------	-------

Conformance

Standards	OSHPD
-----------	-------

Environmental

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0...15240 m)
Storage Relative Humidity	0...95 % non-condensing

Ordering and shipping details

GTIN	731304255734
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	17.008 in (43.2 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	39.5 in (100.3 cm)
Package weight(Lbs)	486.009 lb(US) (220.45 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	4
Package 2 Height	39.9 in (101.4 cm)
Package 2 Width	39.4 in (100 cm)
Package 2 Length	47.2 in (120 cm)
Package 2 Weight	1939.999 lb(US) (879.968 kg)

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 009 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	816 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	55 kg CO2 eq.
Carbon footprint of the installation phase [A5]	62 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	769 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	77 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	A64c500c-f72a-458b-8faa-8175a94429fe
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	48
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Alternative



