

Product data sheet

Specifications



APC Symmetra RM 6kVA Scalable to 6kVA N+1 208/240V w/ 208 to 120V Step-Down Transformer (4) L5-20R

SYH6K6RMT-TF3

⚠ To be discontinued

⚠ Discontinued on: Dec 31, 2024

⚠ To be end-of-service on: Dec 31, 2034

Overview

Lead time	Usually in Stock
Main	
Main Input Voltage	208 V
Product or Component Type	Uninterruptible power supply (UPS)
Main Output Voltage	120 V 208 V
Kw Rating	4200 W
Rated power in VA	6000 VA
Input Connection Type	NEMA L6-30P 30 A
output connection type	4 NEMA L5-20R 2 NEMA L6-20R
Number of rack unit	10U
Cable length	10 ft (3.05 m)
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	User Manual Rack Mounting brackets Rack Mounting support rails CD with software
Range of Product	Symmetra

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Included Battery Modules	3
Battery Slots Empty	0
Typical recharge time	3 h
Additional information	Configurable for 208 or 240 nominal output voltage
Battery Charge Power (Watts)	610 W rated
Battery life	3...5 year(s)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Extendable Run Time	1
---------------------	---

General

product web sub-family	2kVA power increments
Number of power module	4
Number preinstalled power module	3
Number of power module free slots	0
Number of power module filled slots	0
Redundant	Yes

Physical

color	Black
Height	17.52 in (44.5 cm)
Width	19.02 in (48.3 cm)
Depth	28.74 in (73 cm)
Net Weight	389.82 lb(US) (176.82 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	No

Input

Input Frequency	60 Hz +/- 3 Hz
Number of input connectors	1 Hard Wire 3-wire (2PH + G)
Efficiency at full load	155...276 V
Input Power Factor at Full Load	0.98

Output

Max Configurable Power (Watts)	4200 W
Harmonic distortion	Less than 5 % at full load
Output Frequency (sync to mains)	57...63 Hz for 60 Hz nominal sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal not synced
Crest factor	Up to 5 : 1
Topology	Double Conversion Online
Wave type	Sine wave
Bypass type	Internal Bypass (Automatic and Manual)
Efficiency at full load	85 % full load)
Maximum configurable power in VA	6000 VA

Conformance

Product Certifications	CSA
------------------------	-----

Standards	FCC Part 15 class A UL 1778
-----------	--------------------------------

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Acoustic level	60 dBA
Online Thermal Dissipation	2529 Btu/h

Communications & Management

Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 2 with environmental monitoring
control panel	Multi-function LCD status and control console
Emergency Power Off (EPO)	Yes

Ordering and shipping details

GTIN	731304740292
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.00 in (50.8 cm)
Package 1 Width	30.98 in (78.7 cm)
Package 1 Length	22.99 in (58.4 cm)
Package 1 Weight	437.93 lb(US) (198.64 kg)

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	18638
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No