

APC NetShelter Basic Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x12 C13 outlets, C20 cord

AP9565

Overview

Presentation	Reliable rack power distribution designed to increase manageability and efficiency in the data center The output and input connections are (12)C13 Real-time remote monitoring of connected loads User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.
Lead time	Usually in Stock

Main

Color	Black	
Product or Component Type	PDU	
PDU Type	Basic	
Cord length	8.2 ft (2.5 m)	
Number of cables	1	
Provided Equipment	Installation guide Rack Mounting brackets	

Complementary

Input Voltage	200 V	
	208 V	
	230 V	
Height	1.73 in (4.4 cm)	
Width	17.60 in (44.7 cm)	
Output Voltage	208 V	
	230 V	
Depth	2.24 in (5.7 cm)	
Net Weight	4.52 lb(US) (2.05 kg)	
Mounting Location	Front	
	Rear	
Mounting preference	No preference	
Input Plug Type	IEC 60320 C20	
Mounting Mode	Rack-mounted	
Rack units	1U	
Mounting position	Horizontal	
Input current limits	16 A	
Load Capacity	3680 VA	
Input Frequency	50/60 Hz	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Outlet type and quantity 12 IEC 60320 C13

Environment

Product Certifications	cUL Listed CE Queensland Australia UL Listed VDE	
Standards	UL 60950	
Ambient air temperature for operation	32113 °F (045 °C)	
Relative Humidity	095 %	
Operating altitude	010000 ft	
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)	
Storage Relative Humidity	095 %	
Storage altitude	050000 ft (0.000000000015240.0000000000 m)	

Ordering and shipping details

GTIN 731304213055

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.76 in (7 cm)	
Package 1 Width	18.27 in (46.4 cm)	
Package 1 Length	9.02 in (22.9 cm)	
Package 1 Weight	8.007 lb(US) (3.632 kg)	

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	55
Environmental Disclosure	Product Environmental Profile

Use Better

EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
₩ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	Yes