

# Product data sheet

Specifications



## APC Back-UPS Pro External Battery Pack

BR24BPG

**Product availability: Non-Stock - Not normally stocked in distribution facility**

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	120 V
Product or Component Type	External battery pack
Number of cables	1
Battery Type	Lead-Acid battery
Provided Equipment	User Manual
Range of Product	Back-UPS Pro

### Batteries & Runtime

Device mounting	Stand alone battery stack
Battery Life	4...6 year(s)
Battery Voltage	24 V
Battery Capacity	18 Ah
Included Battery Modules	2
Battery Slots Empty	0
RBC Quantity	1
Battery Volt-Amp-Hour Capacity	372 VAh

### Physical

Color	Black
Height	11.9 in (301 mm)
Width	4.4 in (112 mm)
Depth	15.04 in (382 mm)
Net Weight	29.5 lb(US) (13.4 kg)
USB compatible	No

### Conformance

Product Certifications TÜV

### Environmental

Relative Humidity 0...95 %

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Storage Relative Humidity</b>	0...95 %
<b>Ambient Air Temperature for Storage</b>	5...113 °F (-15...45 °C)
<b>Ambient Air Temperature for Operation</b>	32...104 °F (0...40 °C)
<b>Operating altitude</b>	0...30000 ft
<b>Storage altitude</b>	0...50000 ft (0...15240 m)

## Ordering and shipping details

<b>Category</b>	11309-APC RESALE PRODUCTS
<b>Discount Schedule</b>	APC1
<b>GTIN</b>	731304268789
<b>Returnability</b>	No

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	15.748 in (40.000 cm)
<b>Package 1 Width</b>	9.449 in (24.000 cm)
<b>Package 1 Length</b>	19.331 in (49.100 cm)
<b>Package weight(Lbs)</b>	32.119 lb(US) (14.569 kg)
<b>Unit Type of Package 2</b>	P06
<b>Number of Units in Package 2</b>	3
<b>Package 2 Height</b>	20.472 in (52.000 cm)
<b>Package 2 Width</b>	23.622 in (60.000 cm)
<b>Package 2 Length</b>	31.496 in (80.000 cm)
<b>Package 2 Weight</b>	111.790 lb(US) (50.707 kg)
<b>SCC14</b>	10731304268786

## Contractual warranty

<b>Warranty (in months)</b>	36 UPS 12 Battery
-----------------------------	-------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	67 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	54 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	4 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	51 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	5 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	1068e1eb-6a97-4f67-a95e-95f440cdd7dd
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	48
Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	User replaceable
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

---

