

Product data sheet

Specifications



APC NetShelter Soundproof, 38U, Server Rack Enclosure, 120V, Maple [TAA]

AR4038LA

Overview

Lead time Usually Ships within 2 Weeks

Main

Product or Component Type Rack enclosure

Main Input Voltage 100...120 V

Input Connection Type NEMA 5-15P

output connection type 10 NEMA 5-15R

Number of rack unit 38U

Cable length 11.98 ft (3.65 m)

Number of cables 1

Provided equipment Casters

Physical

Height 76.4 in (1940 mm)

Width 29.5 in (750 mm)

Depth 44.5 in (1130.4 mm)

Net Weight 571.0 lb(US) (259 kg)

Color Maple

Mounting preference No preference

Mounting Mode Not rack-mountable

Mounting position Horizontal

Maximum Mounting Depth 32.7 in (830 mm)

Minimum Mounting Depth 27.2 in (690 mm)

Rack Width 19"

Permanent permissible load 3306.9 lb(US) (1500 kg) static
1653.5 lb(US) (750 kg) dynamic

Input

Input Frequency 50/60 Hz

Output

PDU Type Basic

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Conformance

Standards EIA-310D

Ordering and shipping details

GTIN 731304621799

Packing Units

| | |
|------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 80.7 in (205.1 cm) |
| Package 1 Width | 32.3 in (82 cm) |
| Package 1 Length | 47.2 in (120 cm) |
| Package weight(Lbs) | 668.001 lb(US) (303 kg) |

Compliance

Compliance TAA Compliant

Contractual warranty

Warranty (in months) 24



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|------------------|
| Total lifecycle Carbon footprint | 1 063 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 1 015 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 26 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 0 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 23 kg CO2 eq. |

Use Better



Materials and Substances

| | |
|--|----|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|-------------------------------|---|
| Recyclability potential, in % | 95 |
| Circularity Profile | End of Life Information |
| Take-back | No |

Image of product / Alternate images

Alternative







