

Dry contact, Management Options, Dry Contact I/O Card, monitor external UPS environmental sensors, output relays, and input contacts

AP9613

① To be discontinued

- ! To be discontinued on: Mar 31, 2025
- ! To be end-of-service on: Mar 31, 2026

Overview

Presentation	UPS management SmartSlot Card with Dry Contact (relay) support to monitor external triggers and initiate actions on external devices.	
Lead time	Usually in Stock	

Main

Product or Component Type	Dry contact
Number of rack unit	OU
Provided Equipment	User Manual USB cable
Range of Product	Management Ontions and Cables

Physical

Color	Black	
Height	1.50 in (3.8 cm)	
Width	4.76 in (12.1 cm)	
Depth	4.49 in (11.4 cm)	
Net Weight	0.46 lb(US) (0.21 kg)	
Mounting preference	No preference	
Mounting Mode	Not rack-mountable	

Conformance

Standards	EN 55022 Class A	
	EN 55024	
	EN 61000-3-2	
	EN 61000-3-3	
	EN 61000-4-2	
	EN 61000-4-3	
	EN 61000-4-4	
	EN 61000-4-6	
	FCC Part 15 class A	

Environmental

Ambient air temperature for	32104 °F (040 °C)	
operation	(, , , , , , , , , , , , , , , , , , ,	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Relative Humidity	095 %	
Operating altitude	010000 ft	
Ambient Air Temperature for Storage	5149 °F (-1565 °C)	
Storage Relative Humidity	095 %	
Storage altitude	0 50000 ft (0 000000000 15240 000000000 m)	

Ordering and shipping details

Category	09305 - INDUSTRIAL UPS	
GTIN	731304293842	
Returnability	No	
Country of origin	PH	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.85 in (4.700 cm)	
Package 1 Width	6.50 in (16.500 cm)	
Package 1 Length	9.21 in (23.400 cm)	
Package 1 Weight	14.109 oz (400.000 g)	
Unit Type of Package 2	S03	
Number of Units in Package 2	6	
Package 2 Height	11.81 in (30.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	7.013 lb(US) (3.181 kg)	

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	282
Environmental Disclosure	Product Environmental Profile

Use Better

S Materials and Substances		
EU RoHS Directive	Compliant with Exemptions	
REACh Regulation	REACh Declaration	
᠃ Energy efficiency		
Optimized Energy Efficiency	Energy efficient product	

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	Yes