

Emergency Power Off (EPO)

EPW9

Product availability: Stock - Normally stocked in distribution facility

Overview

Presentation	Provides a single point of emergency equipment shutdown for up to eight APC InfraStruXure devices and one third-party device.
Lead time	Usually in Stock

Main

Number of cables	1	
Provided Equipment	User Manual	

Physical

Color	Black
Height	8.90 in (22.6 cm)
Width	9.88 in (25.1 cm)
Depth	2.60 in (6.6 cm)
Net Weight	6.4 lb(US) (2.9 kg)
Mounting Mode	Not rack-mountable

Conformance

Product Certifications	cUL Listed
	UL Listed

Environmental

Ambient air temperature for operation	23113 °F (-545 °C)	
Relative Humidity	595 %	
Operating altitude	010000 ft	
Ambient Air Temperature for Storage	23113 °F (-545 °C)	
Storage Relative Humidity	595 %	
Storage altitude	010000 ft (0.00000000003048.0000000000 m)	

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA	
Discount Schedule	BMS1	
GTIN	731304213239	
Returnability	No	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin PH

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	12.01 in (30.5 cm)	
Package 1 Width	5.00 in (12.7 cm)	
Package 1 Length	12.01 in (30.5 cm)	
Package 1 Weight	6.92 lb(US) (3.14 kg)	

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

Use Better

EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Use Again	
○ Repack and remanufacture	
	The product must be disposed on European Union markets following specific waste collection and never end