

# Product data sheet

Specifications



## APC NetShelter Switched Rack PDU, 0U, 20A, 100-120V, 24 NEMA 5-20R outlets

AP8930

**Product availability: Stock - Normally stocked in distribution facility**

## Overview

<b>Presentation</b>	APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
---------------------	---

<b>Lead time</b>	Usually in Stock
------------------	------------------

## Main

<b>Color</b>	Black
<b>Product or Component Type</b>	PDU
<b>PDU Type</b>	Switched
<b>Cord length</b>	9.5 ft (2.9 m)
<b>Number of cables</b>	1
<b>Provided Equipment</b>	Installation guide Rack Mounting brackets Serial configuration cable Safety guide

## Complementary

<b>Input Voltage</b>	120 V
<b>Height</b>	70.5 in (1791 mm)
<b>Width</b>	2.2 in (55 mm)
<b>Output Voltage</b>	120 V
<b>Depth</b>	1.8 in (46 mm)
<b>Net Weight</b>	14.37 lb(US) (6.52 kg)
<b>Mounting Location</b>	Side
<b>Mounting preference</b>	No preference
<b>Input Plug Type</b>	NEMA L5-20P
<b>Mounting Mode</b>	Rack-mounted
<b>Rack units</b>	0U
<b>Mounting position</b>	Vertical

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Line Rated Current	16 A
Acceptable Input Voltage	100...120 V
Input current limits	20 A
Load Capacity	1920 VA
Input Frequency	50/60 Hz
Outlet type and quantity	24 NEMA 5-20R

## Environment

Product Certifications	cUL Listed UL Listed
Standards	FCC Part 15 class A ICES-003 UL 60950-1
Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0...15240 m)

## Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304307518
Returnability	No
Country of origin	IN

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	79.0 in (200.6 cm)
Package 1 Width	4.26 in (10.83 cm)
Package 1 Length	6.48 in (16.47 cm)
Package weight(Lbs)	19.0 lb(US) (8.6 kg)

## Contractual warranty

Warranty (in months)	24
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	1 555 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	48 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 502 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>
Halogen content performance	Product contains halogen above thresholds

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	71
Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	Yes
Take-back	Nej