

Product data sheet

Specifications



APC Smart-UPS SRT Step-Down Transformer, 10kVA, rackmount, 4U, 2x NEMA L5-20R & 2x NEMA L14-30R outlets

SRT10KRMTF

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	208 V
Product or Component Type	Transformer
Main Output Voltage	120 V 208 V 240 V
Output connector type	Hard Wire 3-wire (2PH + G) for 2 zone(s) Hard Wire 4-wire (2PH+N+G) for 1 zone(s)
Provided Equipment	Mounting Hardware Rack Mounting brackets Safety guide User Manual Warranty card
Range of Product	Smart-UPS Accessories

Physical

Color	Black
Height	6.9 in (174 mm)
Width	17.008 in (432 mm)
Depth	29.5 in (749 mm)
Net Weight	220.00 lb(US) (99.79 kg)
Mounting preference	Lower
Mounting Mode	Rack-mounted
Mounting position	Horizontal

Input

permissible voltage	200...240 V
Max line current	60 A
Input current limits	60 A
Load Capacity	10000 VA
Input Frequency	45...65 Hz
Number of input connectors	1 Hard Wire 3-wire (2PH + G)

Output

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum Total Current Draw per Phase	60 A
Number of power socket outlets	4
Number of power socket outlets	2 NEMA L5-20R 2 NEMA L14-30R

Conformance

Product Certifications	CE CSA UL Listed
------------------------	------------------------

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0...15240 m)

Ordering and shipping details

GTIN	731304318859
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	16.0 in (40.6 cm)
Package 1 Width	39.4 in (100 cm)
Package 1 Length	23.6 in (60 cm)
Package weight(Lbs)	275.005 lb(US) (124.74 kg)

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	11 351 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	441 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	9 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	10 893 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	8 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	A64c500c-f72a-458b-8faa-8175a94429fe

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	86
Circularity Profile	End of Life Information
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative



