

Product data sheet

Specifications



APC NetShelter SX, Server Rack Enclosure, 24U, Shock Packaging, 1250 lbs, Black, 1200H x 600W x 1070D mm [TAA]

AR3104SP1

Overview

Presentation NetShelter SX cabinet and packaging system designed to safely integrate, transport, unload and deploy up to 1250 lbs (566 kg) of IT equipment. The cabinet is paired with a shock absorbing pallet, unloading ramp, and impact resistant shell. The system has been engineered, tested and approved for secure shipment of fully converged systems such as being certified with Cisco® for pre-racking and shipping Cisco Unified Computing System (UCS).

Lead time Usually in Stock

Main

Product or Component Type Rack enclosure

Number of rack unit 24U

Provided equipment

- Baying hardware
- Doors
- Installation guide
- Keyed-alike doors and side panels
- Leveling feet
- Mounting Hardware
- Pallet ramps
- Pre-installed casters
- Reusable packaging
- Roof
- Side Panels

Physical

Height 47.2 in (1200 mm)

Width 23.6 in (600 mm)

Depth 42.1 in (1070 mm)

Net Weight 196.41 lb(US) (89.09 kg)

Color Black

Mounting preference No preference

Mounting Mode Not rack-mountable

Maximum Mounting Depth 36.02 in (914.9 mm)

Minimum Mounting Depth 7.5 in (191 mm)

Rack Width 19"

Marking

- 14 gauge EIA mounting rail
- 16 gauge front door
- 16 gauge post
- 18 gauge rear door
- 18 gauge roof
- 18 gauge side panels

Permanent permissible load

- 2250 lb(US) (1020.6 kg) dynamic
- 3000 lb(US) (1360.8 kg) static

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Conformance

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

Ordering and shipping details

GTIN	731304262275
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	53.1 in (135 cm)
Package 1 Width	48.0 in (121.9 cm)
Package 1 Length	35.4 in (89.9 cm)
Package weight(Lbs)	235.50 lb(US) (106.82 kg)

Compliance

Compliance	TAA Compliant BAA Compliant via COTS
------------	---

Contractual warranty

Warranty (in months)	60
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	375 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	358 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	9 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	8 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture


Recyclability potential, in %	95
Circularity Profile	End of Life Information
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

