

Product data sheet

Specifications



APC Smart-UPS On-Line SRT Rackmount Battery Pack for 2.2kVA Extended runtime model 72V

SRT72RMBP

Product availability: Non-Stock - Not normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Product or Component Type External battery pack

Number of rack unit 2U

Battery Type Lead-Acid battery

Provided Equipment Documentation CD
Installation guide
Rack Mounting brackets

Range of Product Smart-UPS Battery Systems

Batteries & Runtime

Battery Slots Empty 0

Included Battery Modules 0

Battery Voltage 72V

RBC Quantity 2

Replacement battery [APCRBC141](#)

Physical

Color Black

Height 3.3 in (85 mm)

Width 17.008 in (432 mm)

Depth 23.4 in (594 mm)

Net Weight 74.7 lb(US) (33.9 kg)

Mounting Mode Rack-mounted

Output

Battery Capacity 20 Ah

Conformance

Standards OSHPD

Environmental

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0...15240 m)
Storage Relative Humidity	0...95 % non-condensing

Ordering and shipping details

GTIN	731304317715
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.409 in (23.900 cm)
Package 1 Width	23.583 in (59.900 cm)
Package 1 Length	32.717 in (83.100 cm)
Package weight(Lbs)	89.993 lb(US) (40.820 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	2
Package 2 Height	39.370 in (100.000 cm)
Package 2 Width	39.370 in (100.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	206.441 lb(US) (93.640 kg)

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	187 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	151 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	10 kg CO2 eq.
Carbon footprint of the installation phase [A5]	11 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	142 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	14 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	5ac12844-46eb-471b-94f1-318e06a714a6
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	48
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Image of product / Alternate images

Alternative

