

Product data sheet

Specifications



APC Smart-UPS SRT 96V 3kVA RM Battery Pack



SRT96RMBP

Overview

Lead time Usually in Stock

Main

Product or Component Type External battery pack

Number of rack unit 2U

Battery Type Lead-Acid battery

Provided Equipment Rack Mounting brackets
User Manual
Warranty card

Range of Product Smart-UPS Battery Systems

Batteries & Runtime

Battery Slots Empty 0

Included Battery Modules 0

Device mounting Stand alone battery stack

Battery Voltage 96V

RBC Quantity 2

Replacement battery [APCRBC152](#)

Physical

Color Black

Height 3.3 in (85 mm)

Width 17.008 in (432 mm)

Depth 23.4 in (594 mm)

Net Weight 89.5 lb(US) (40.6 kg)

Mounting Mode Rack-mounted

Two post mountable 1

Output

Battery Capacity 19 Ah

Conformance

Standards OSHPD

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0...15240 m)
Storage Relative Humidity	0...95 % non-condensing

Ordering and shipping details

GTIN	731304317739
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.4 in (23.9 cm)
Package 1 Width	23.6 in (59.9 cm)
Package 1 Length	32.7 in (83.1 cm)
Package weight(Lbs)	98.106 lb(US) (44.500 kg)

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	204 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	165 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	11 kg CO2 eq.
Carbon footprint of the installation phase [A5]	13 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	155 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	16 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	488c31fb-3af8-42cf-9558-1362d000a07e
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	48
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

