

Product data sheet

Specifications



Rack PDU, Switched, 2U, 32A, 230V, (16)C13



AP7922B

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	9.8 ft (3 m)
Number of cables	1
Provided equipment	Documentation CD Installation guide Rack mounting brackets

Complementary

Input Voltage	200 V 208 V 230 V
Height	3.5 in (89 mm)
Width	17.5 in (445 mm)
Output Voltage	230 V
Depth	4.5 in (114 mm)
Net weight	9.9 lb(US) (4.5 kg)
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted
Rack units	2U
Mounting position	Horizontal
permissible voltage	220...240 V
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Outlet type and quantity	16 IEC 60320 C13

Environment

Product certifications	CE GOST IRAM MIC VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
Ambient air temperature for operation	32...113 °F (0...45 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0...15240 m)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 in (14 cm)
Package 1 Width	14.5 in (36.8 cm)
Package 1 Length	20.0 in (50.8 cm)
Package 1 Weight	14.44 lb(US) (6.55 kg)

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 191 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	36 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 151 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	71
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

