

# Product data sheet

Specifications



## UPS Network Management Card 2 w/ Environmental Monitoring, Out of Band Access and Modbus

AP9635

⚠ To be discontinued

⚠ To be discontinued on: Jul 15, 2025

⚠ To be end-of-service on: Aug 15, 2025

**Product availability: Stock - Normally stocked in distribution facility**

### Overview

Lead time Usually in Stock

### Main

Provided Equipment CD with software  
Temperature Sensor  
User Manual

### Physical

Height 1.50 in (3.81 cm)

Width 4.76 in (12.1 cm)

Depth 4.25 in (10.8 cm)

Net Weight 0.31 lb(US) (0.14 kg)

Mounting preference No preference

Mounting Mode Not rack-mountable

### Conformance

Standards EN 55022 Class A  
FCC Part 15 class A  
ICES-003

Product Certifications AS/NZS 3548 (C-Tick) Class A  
GOST  
VCCI Class A

### Environmental

Ambient air temperature for operation 23...113 °F (-5...45 °C)

Operating altitude 0...10000 ft

Relative Humidity 0...95 % non-condensing

Ambient Air Temperature for Storage 5...149 °F (-15...65 °C)

Storage altitude 0...50000 ft (0.0000000000...15240.0000000000 m)

Storage Relative Humidity 0...95 %

### Communications & Management

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Authentication	Radius
----------------	--------

## Ordering and shipping details

---

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304267768
Returnability	No
Country of origin	PH

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.97 in (5.000 cm)
Package 1 Width	9.25 in (23.500 cm)
Package 1 Length	6.38 in (16.200 cm)
Package 1 Weight	20.670 oz (586.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	3
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	4.409 lb(US) (2.000 kg)

## Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)

192

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation

[REACH Declaration](#)

### Energy efficiency

Optimized Energy Efficiency

Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Halogen content performance

Product contains halogen above thresholds

Take-back

Yes