

Product data sheet

Specifications



APC NetShelter SX, Server Rack Enclosure, 24U, Black, 1198.5H x 600W x 1070D mm [TAA]

AR3104

Overview

Presentation An industry-standard rack with the most standard features for speed of deployment and installation. Ready for low to medium density edge computing.

Lead time Usually in Stock

Main

Product or Component Type Rack enclosure

Number of rack unit 24U

Provided equipment
Casters
Doors
Key(s)
Leveling feet
Roof
Side Panels

Physical

Height 47.2 in (1198.5 mm)

Width 23.6 in (600 mm)

Depth 42.1 in (1070 mm)

Net Weight 196.41 lb(US) (89.09 kg)

Color Black

Mounting preference No preference

Mounting Mode Not rack-mountable

Maximum Mounting Depth 36.02 in (914.9 mm)

Minimum Mounting Depth 7.5 in (191 mm)

Rack Width 19"

Marking
14 gauge EIA mounting rail
16 gauge front door
16 gauge post
18 gauge rear door
18 gauge roof
18 gauge side panels

Permanent permissible load
2250 lb(US) (1020.6 kg) dynamic
3000 lb(US) (1360.8 kg) static

Conformance

Standards
UL 2416
UL 60950-1
EIA-310E

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

GTIN 731304261889

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	52.05 in (132.2 cm)
Package 1 Width	29.4 in (74.6 cm)
Package 1 Length	45.5 in (115.6 cm)
Package weight(Lbs)	235.50 lb(US) (106.82 kg)

Compliance

Compliance TAA Compliant
BAA Compliant via COTS

Contractual warranty

Warranty (in months) 60



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	375 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	358 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	9 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	8 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture


Recyclability potential, in %	95
Circularity Profile	End of Life Information
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative







