


# Product data sheet

Specifications



## SmartUPS Industrial Battery Harness SBS75 Cabinet Accessory 4 ft

XHXXS7A4F

### Overview

|           |                  |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

### Main

|                           |                    |
|---------------------------|--------------------|
| Product or Component Type | Battery accessory  |
| Provided Equipment        | Installation guide |

### Physical

|               |                     |
|---------------|---------------------|
| Height        | 1.0 in (25 mm)      |
| Width         | 48.03 in (1220 mm)  |
| Depth         | 1.0 in (25 mm)      |
| Net Weight    | 4.9 lb(US) (2.2 kg) |
| Mounting Mode | Not rack-mountable  |

### Environmental

|                                       |                            |
|---------------------------------------|----------------------------|
| Ambient Air Temperature for Operation | -35...165 °F (-37...74 °C) |
| Relative Humidity                     | 0...95 % non-condensing    |
| Operating altitude                    | 0...3000 ft                |
| Ambient Air Temperature for Storage   | 5...113 °F (-15...45 °C)   |
| Storage Relative Humidity             | 0...95 % non-condensing    |
| Storage altitude                      | 0...50000 ft (0...15240 m) |

### Ordering and shipping details

|      |              |
|------|--------------|
| GTIN | 731304345480 |
|------|--------------|

### Packing Units

|                        |                   |
|------------------------|-------------------|
| Unit Type of Package 1 | PCE               |
| Nbr. of units in pkg.  | 1                 |
| Package 1 Height       | 6.9 in (17.5 cm)  |
| Package 1 Width        | 11.8 in (30 cm)   |
| Package 1 Length       | 14.6 in (37 cm)   |
| Package weight(Lbs)    | 6.6 lb(US) (3 kg) |

### Contractual warranty

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 593 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 24 kg CO2 eq.                                 |
| Carbon footprint of the distribution phase [A4]        | 0.3 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 569 kg CO2 eq.                                |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.2 kg CO2 eq.                                |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                        |
|----------------------------------------|----------------------------------------|
| Packaging made with recycled cardboard | Yes                                    |
| Packaging without single use plastic   | No                                     |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a> |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                               |                                                                                                                                                                                                                  |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in % | 65                                                                                                                                                                                                               |
| Circularity Profile           | <a href="#">End of Life Information</a>                                                                                                                                                                          |
| Removable battery             | User replaceable                                                                                                                                                                                                 |
| Take-back                     | Yes                                                                                                                                                                                                              |
| WEEE Label                    |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |