

Product data sheet

Specifications



APC Symmetra LX Extended Run Rack-mount w/ 3 SYBT5, 208V

SYARMXR3B3

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or Component Type	Battery accessory
Number of rack unit	5U
Number of cables	1
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide User Manual
Range of Product	Symmetra Battery Systems

Batteries & Runtime

Battery Placement	Battery Cabinet
Battery Slots Empty	0
Included Battery Modules	0
Battery manufacturer	Panasonic
Device mounting	Enclosed battery cabinet
RBC Quantity	3

Physical

Color	Black
Height	8.5 in (215 mm)
Width	18.6 in (472 mm)
Depth	27.008 in (686 mm)
Net Weight	251.53 lb(US) (114.09 kg)
Mounting Mode	Rack-mounted

Conformance

Standards	UL 1778
Product Certifications	CSA

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...15000 ft (0...4572 m)
Storage Relative Humidity	0...95 %

Ordering and shipping details

GTIN	731304740032
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	13.5 in (34.3 cm)
Package 1 Width	38.6 in (98 cm)
Package 1 Length	23.6 in (59.9 cm)
Package weight(Lbs)	281.60 lb(US) (127.73 kg)

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	23 832 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 813 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	17 kg CO2 eq.
Carbon footprint of the installation phase [A5]	17 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	46 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	66
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Image of product / Alternate images

Alternative





