

APC Smart-UPS, Line Interactive, 500VA, Lithium-ion, Rackmount 1U, 230V, 4x IEC C13 outlets, SmartConnect Port, Short Depth

Intelligent and efficient network power protection from entry level to scalable runtime.

SCL500RMI1UC

#### **Overview**

Presentation

	Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock
Main	
Main Input Voltage	230 V
Main Output Voltage	230 V
Kw Rating	400 W
Rated power in VA	500 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
output connection type	4 IEC 60320 C13
Number of rack unit	1U
Battery Type	Li-lon (Lithium Ion)
Provided equipment	Installation guide Rack Mounting support rails USB cable
Range of Product	Smart-UPS

### Complementary

Communication port type	SmartConnect Ethernet port
Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use

### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
Extendable Run Time	0
Battery design life	810 year(s)
Battery Charge Power (Watts)	10 W rated

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## General

product web sub-family	Cloud-enabled monitoring
Redundant	No

# **Physical**

_	
color	Black with silver front bezel
Height	1.73 in (4.4 cm)
Width	17.01 in (43.2 cm)
Depth	9.13 in (23.2 cm)
Net Weight	8.95 lb(US) (4.06 kg)
Mounting preference	No preference
Mounting Mode	Rack-mounted
USB compatible	Yes

# Input

Input protection type	Circuit breaker
Efficiency at full load	208253 V
Input Frequency	50/60 Hz +/- 3 Hz auto sensing

# Output

Harmonic distortion	Less than 5%
Maximum configurable power in VA	500 VA
Max Configurable Power (Watts)	400 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Wave type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

# Conformance

Product Certifications	C-tick CE EAC RCM UK PSTI
Equipment protection policy	Lifetime : \$150000
Standards	EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## **Environmental**

Acoustic level	45 dBA
Online Thermal Dissipation	41.61 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	32104 °F (040 °C)
Ambient Air Temperature for	5113 °F (-1545 °C)

Storage altitude	025000 ft (0.00000000007620.0000000000 m)
IP degree of protection	IP20
Relative Humidity	095 % non-condensing
Storage Relative Humidity	095 % non-condensing

## **Communications & Management**

control panel	LED status display with On Line : On Battery : Replace Battery and Building Wiring Fault
Free slots	0
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
	Alarm when on battery : distinctive low battery alarm : configurable delays

# **Surge Protection and Filtering**

Surge energy rating	510 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping

# Ordering and shipping details

GTIN	731304402558	
Country of origin	PH	

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	6.61 in (16.8 cm)	
Package 1 Width	13.27 in (33.7 cm)	
Package 1 Length	23.23 in (59 cm)	
Package 1 Weight	13.2 lb(US) (6 kg)	

## Contractual warranty

Warranty	5 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	596
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
Product contributes to saved and avoided emissions	Yes

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No