

Product data sheet

Specifications



APC Smart-UPS Ultra On-Line Lithium-ion XBP 180V 2U Rack/ Tower



SRTL180RM2UBP

Overview

Lead time Usually in Stock

Main

Product or Component Type External battery pack

Number of rack unit 2U

Battery Type Li-Ion (Lithium Ion)

Provided Equipment Rack Mounting brackets
Vertical mounting brackets

Range of Product Smart-UPS Ultra

Batteries & Runtime

Battery Slots Empty 0

Included Battery Modules 0

Battery Voltage 180 V

RBC Quantity 2

Physical

Color Silver grey

Height 3.4 in (86 mm)

Width 17.008 in (432 mm)

Depth 28.5 in (724 mm)

Net Weight 71.4 lb(US) (32.4 kg)

Mounting Mode Rack-mounted with kit
Tower-mounted with kit

Output

Battery Capacity 8 Ah

Conformance

Product Certifications UL 1973

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)

Operating altitude 0...10000 ft

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0...15240 m)
Storage Relative Humidity	0...95 % non-condensing

Ordering and shipping details

GTIN 731304437024

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	15.4 in (39.2 cm)
Package 1 Width	23.03 in (58.5 cm)
Package 1 Length	38.7 in (98.4 cm)
Package weight(Lbs)	92.6 lb(US) (42 kg)
SCC14	10731304437024

Contractual warranty

Warranty (in months) 60



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	310 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	297 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	6 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	5ee38369-4dfb-4636-ab65-b08aa3242891
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	95
Removable battery	User replaceable
Take-back	Yes

Image of product / Alternate images

Alternative



