

Product data sheet

Specifications



APC Replacement Battery Cartridge, VRLA, 9Ah, 72V DC, 2-year warranty

APCRBCV202

Overview

Lead time Usually in Stock

Main

Product or Component Type Replacement battery cartridge
Number of rack unit 0U
Battery Type VRLA
Range of Product Replacement Battery Cartridges

Batteries & Runtime

Battery Placement Internal Battery
Battery blocks per string 6
Battery Slots Empty 0
Included Battery Modules 0
Battery Voltage 72V
RBC Quantity 1

Physical

Height 2.6 in (64.8 mm)
Width 5.9 in (150.9 mm)
Depth 3.9 in (98.6 mm)
Net Weight 33.07 lb(US) (15 kg)
Mounting Mode Rack-mounted
USB compatible No

Output

Battery Capacity 9 Ah

Conformance

Product Certifications CB

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)
Operating altitude 0...6561.68 ft (0...2000 m)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Relative Humidity	0...90 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...9842.5 ft (0...3000 m)
Storage Relative Humidity	0...95 % non-condensing

Ordering and shipping details

GTIN	731304451044
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	13.8 in (35 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	7.9 in (20 cm)
Package weight(Lbs)	36.4 lb(US) (16.5 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	20
Package 2 Height	44.09 in (112 cm)
Package 2 Width	39.4 in (100 cm)
Package 2 Length	47.2 in (120 cm)
Package 2 Weight	756.2 lb(US) (343 kg)

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	109 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	56 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	6 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	43 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	9d64af64-ba09-487b-83a8-542c851816cc

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	1
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

