

Product data sheet

Specifications



Rack Mount, Security and Environmental Appliance, NetBotz, 250A

NBRK0250A

Overview

Presentation	NetBotz Rack Monitor 250 with embedded NMC3
Lead time	Usually in Stock

Main

Product or Component Type	Industrial rack PC
Range of Product	Netbotz
Number of rack unit	1U
Communication Port Protocol	HTTPS HTTP SNMP SNMP v3 Modbus
Provided Equipment	Installation guide Rack Mounting brackets Temperature/Humidity Sensor Installation gasket

General

APC Universal Sensors Supported	0-5V Door contact Dry Contact Fluid Spot Leak Humidity Temperature Smoke
Number of Universal Sensor Ports	6
Number of Sensor Pods Supported	6

Physical

Height	1.7 in (4.4 cm)
Width	1.7 in (43.2 mm)
Depth	2.3 in (5.9 cm)
Net Weight	2.80 lb(US) (1.27 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Vertical

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0...15240 m)

Communications & Management

Communication Network Type	RJ-45 10/100 Base-T
----------------------------	---------------------

Ordering and shipping details

GTIN	731304563365
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.6 in (6.6 cm)
Package 1 Width	8.9 in (22.6 cm)
Package 1 Length	18.0 in (45.7 cm)
Package weight(Lbs)	6.50 lb(US) (2.95 kg)

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	250 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	31 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.5 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.4 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	213 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	5 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	49
Circularity Profile	End of Life Information
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Offer Marketing Illustration

Product benefits / Features

NetBotz 250A

Benefits



Secure Rack Access

Ensure only authorized entry with permission-based access and full audit trails, strengthening physical security and control in your IT environment.



Reliable Budget Monitoring

Gain dependable, cost-effective monitoring for essential IT environments, providing confidence and protection without the need for complex surveillance systems.



Prevent Environmental Risks

Get real-time alerts on temperature, humidity, smoke, and leaks to protect equipment and avoid costly environmental-related downtime.



Image of product / Alternate images

Alternative



