Product data sheet

Specifications



Schneider OffGrid Portable Power Station 330, 120V, 332Wh Lithium-ion, LCD, 2 NEMA, Sinewave, 3 USB-A, 1 USB-C, Wireless Charger

PPS330

Overview

Lead time	Usually in Stock

Main

Product or Component Type	Portable power station
Battery Type	Li-Ion (Lithium Ion)
Battery capacity in Wh	332 W.h
Number of input connectors	(1) 12...30 V DC, 8 A, (100 W) (1) USB type C (60 W)
Number of output connectors	(2) NEMA 5-15, 120 V ,AC, 2.5 A(300 W) 60 Hz, Sine wave (3) USB type A, 5 V ,DC, 2.4 A(12 W) (1) USB type C, 5...20 V ,DC, 3 A(60 W) (1) car cigaratte lighter port, 12 V ,DC, 10 A(120 W) (1) wireless charging,DC(15 W)
Range of Product	Schneider OffGrid
USB Charging Port	USB type A + C

Complementary

Color	Black and Green
Height	6.02 in (153 mm) 6.0 in (152.4 mm)
Width	6.4 in (163 mm) 6.40 in (162.56 mm)
Depth	8.8 in (223 mm) 8.70 in (220.98 mm)
Net Weight	7.3 lb(US) (3.3 kg) 7.3 lb(US) (3.3 kg)
Product Specific Application	For Caravan/Camping Power Supply Mobile wireless charging
Product Certifications	TUV C-US certified FCC Class B BC
Provided Equipment	1 AC adapter 1 car charging cable User Manual
Battery capacity in Wh	332 W.h 500+ cycles with 80% capacity
Max Configurable Power (Watts)	531 W
Minimum illuminance	150 lux

Environment

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Storage	-4…158 °F (-20…70 °C) -4…158 °F (-20…70 °C)
Charging temperature	32…104 °F (0…40 °C) 32…104 °F (-0…40 °C)
Discharging temperature	14…104 °F (-10…40 °C) 14…104 °F (-10…40 °C)

Ordering and shipping details

GTIN	731304736745
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	11.02 in (28 cm)
Package 1 Width	9.4 in (23.8 cm)
Package 1 Length	11.8 in (30 cm)
Package weight(Lbs)	13.9 lb(US) (6.3 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**156 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**90 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**10 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.3 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**46 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**10 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**3**
Circularity Profile	End of Life Information
Take-back	**No**

Image of product / Alternate images

Alternative






Schneider OffGrid 330
100%
12V


Schneider OffGrid 330
100%
12V


Schneider OffGrid