

Product data sheet

Specifications



APC NetShelter Rack PDU,
Switched, 0U, 17.3kW 208V 3-
phase 60A, (42) C13/C15 and (6)
C19/C21 outlets

APDU9967US

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Cord length	5.97 ft (1.82 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Safety guide Serial configuration cable

Complementary

Input Voltage	208 V 3 phase
Height	72.2 in (1833 mm)
Width	4.4 in (111 mm)
Output Voltage	208 V
Depth	3.0 in (76 mm)
Net Weight	32.06 lb(US) (14.54 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 60 A 3P+PE
Mounting Mode	Not rack-mountable
Rack units	0U
Mounting position	Vertical
Communication Port Protocol	SNMP Redfish
Line Rated Current	48 A
Max line current	48 A
Input current limits	60 A
Load Capacity	17300 VA
Input Frequency	50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Outlet type and quantity	42C13/C15 6C19/C21
Communication Network Type	10/100/1000BASE-T Wi-Fi (optional)

Environment

Product Certifications	cUL Listed FCC part 15 class A UL Listed VCCI Class A TAA compliance
Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3
Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0...15240 m)

Ordering and shipping details

GTIN	731304435433
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	84.6 in (214.9 cm)
Package 1 Width	4.4 in (11.2 cm)
Package 1 Length	8.7 in (22.1 cm)
Package weight(Lbs)	44.004 lb(US) (19.96 kg)

Contractual warranty

Warranty (in months)	36
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	6 012 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	81 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	5 923 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	6 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	71
Circularity Profile	End of Life Information
Removable battery	No
Take-back	No