

Product data sheet

Specifications



Security and Environmental Appliance, NetBotz, Room Mount, 755, TAA

NBWL0755TAA

Overview

Presentation	The NetBotz Room Monitor 755TAA provides integrated surveillance,sensing, access control, and advanced alerting for IT environmentsof all sizes where IT rack space is unavailable.
Lead time	Usually in Stock

Main

Product or Component Type	Industrial rack PC
Range of Product	Netbotz

General

Camera Frame Rate	Up to 30fps
APC Universal Sensors Supported	0-5V Door contact Dry Contact Fluid Spot Leak Humidity Smoke Temperature Vibration

Physical

Color	Black
Height	5.5 in (14.0 cm)
Width	9.6 in (24.4 cm)
Depth	3.6 in (9.1 cm)
Net Weight	3.44 lb(US) (1.56 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Operating altitude	0...9842.52 ft (0...3000 m)
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Storage altitude	0...49212.6 ft (0...15000 m)

Communications & Management

Communication Network Type	10/100/1000BASE-T
----------------------------	-------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

GTIN	731304755807
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.8 in (12.1 cm)
Package 1 Width	12.5 in (31.8 cm)
Package 1 Length	21.0 in (53.3 cm)
Package weight(Lbs)	8.20 lb(US) (3.72 kg)

Compliance

Compliance	TAA Compliant
------------	---------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 484 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	39 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.6 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.6 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 438 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	7 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	49
Circularity Profile	End of Life Information
Removable battery	No
Take-back	Nej